Carbon dioxide emission and bio-capacity indexing for transportation activities

DOI:

[10.1016/j.jenvman.2018.06.010](https://doi.org/10.1016/j.jenvman.2018.06.010)

Document Version

Accepted author manuscript

[Link to publication record in Manchester Research Explorer](#)

Citation for published version (APA):

Labib, S., Neema, M. N., Rahaman, Z., Patwary, S. H., & Shakil, S. H. (2018). Carbon dioxide emission and bio-capacity indexing for transportation activities: A methodological development in determining the sustainability of vehicular transportation systems. *Journal of Environmental Management*, 223, 57-73.
<https://doi.org/10.1016/j.jenvman.2018.06.010>

Published in:

Journal of Environmental Management

Citing this paper

Please note that where the full-text provided on Manchester Research Explorer is the Author Accepted Manuscript or Proof version this may differ from the final Published version. If citing, it is advised that you check and use the publisher's definitive version.

General rights

Copyright and moral rights for the publications made accessible in the Research Explorer are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Takedown policy

If you believe that this document breaches copyright please refer to the University of Manchester's Takedown Procedures [<http://man.ac.uk/04Y6Bo>] or contact uml.scholarlycommunications@manchester.ac.uk providing relevant details, so we can investigate your claim.

Title Page

Carbon dioxide Emission and Bio-capacity indexing for transportation activities: A methodological development in determining the sustainability of vehicular transportation Systems

S M Labib ^{a*}; Dr. Meher Nigar Neema ^b; Zahidur Rahaman ^c; Shahadath Hossain Patwary ^d; Shahadat Hossain Shakil ^e

Corresponding Author:

S M Labib^{*}

^a PhD Researcher, School of Environment, Education and Development (SEED), University of Manchester.

Email: sm.labib@manchester.ac.uk

Arthur Lewis building (1st Floor); Oxford Road; Manchester; M13 9PL

Co-authors:

^b Professor, Department of urban and regional planning, Bangladesh University of Engineering and Technology (BUET). E-mail: mnneema@yahoo.com

^c Sub-Registrar, Ministry of Law, Justice and Parliamentary Affairs, Government of Bangladesh. Email: abeer.urp@gmail.com

^d Assistant Urban Planner, Sheltech (Pvt.) Ltd. Email: shahadath3.1416@gmail.com

^e Project Management Specialist (Environment), Economic Growth Office, USAID.

U.S. Agency For International Development, American Embassy, Madani Avenue. Dhaka-1212.

Email: sshakil@usaid.gov

Abstract

CO₂ emissions from urban traffic are a major concern in an era of increasing ecological disequilibrium. Adding to the problem net CO₂ emissions in urban settings are worsened due to the decline of bio-productive areas in many cities. This decline exacerbates the lack of capacity to sequester CO₂ at the micro and meso-scales resulting in increased temperatures and decreased air quality within city boundaries. Various transportation and environmental strategies have been implemented to address traffic related CO₂ emissions, however current literature identifies difficulties in pinpointing these critical areas of maximal net emissions in urban transport networks. This study attempts to close this gap in the literature by creating a new lay-person friendly index that combines CO₂ emissions from vehicles and the bio-capacity of specific traffic zones to identify these areas at the meso-scale within four ranges of values with the lowest index values representing the highest net CO₂ levels. The study used traffic volume, fuel types, and vehicular travel distance to estimate CO₂ emissions at major links in Dhaka, Bangladesh's capital city's transportation network. Additionally, using remote-sensing tools, adjacent bio-productive areas were identified and their bio-capacity for CO₂ sequestration estimated. The bio-productive areas were correlated with each traffic zone under study resulting in a Emission Bio-Capacity index (EBI) value estimate for each traffic node. Among the ten studied nodes in Dhaka City, nine had very low EBI values, correlating to very high CO₂ emissions and low bio-capacity. As a result, the study considered these areas unsustainable as traffic nodes going forward. Key reasons for unsustainability included increasing use of motorized traffic, absence of optimized signal systems, inadequate public transit options, disincentives for fuel free transport (FFT), and a decline in bio-productive areas.

Key words: Carbon dioxide (CO₂) Emission, Transportation Sustainability Rating, Bio-Capacity, Urban Transport, Low carbon transport.

1. Introduction

Urban transportation produces significant amounts of overall carbon dioxide (CO₂) emissions in urban areas (Li, 2011). Given an era of global warming and climate change, controlling CO₂ emissions, in support of sustainable development is a major concern in maintaining overall global sustainability and livability. According to the International Energy Agency (IEA), the transportation sector of the global economy was the second highest sectoral emitter of CO₂ emissions in year 2008; accounting for 22% of global CO₂ emissions (Loo and Li, 2012). Urban areas of the global economy with 54.5% (rising to 60% by 2030) of the global population are responsible for 75% of global CO₂ emissions, and intra-urban transportation contributed 17.5% of those CO₂ emissions (Fan and Lei, 2016). Dodman (2009), noted that, major cities around the world produced massive amounts of CO₂ from daily traffic movements. CO₂ emissions in representative cities such as: London (22 percent), New York (23 percent), Toronto (36 percent), and São Paulo (59.7%) support Dodman's observations. Additionally, fast developing countries with large populations such as India and China, are now experiencing steadily intensifying emissions of CO₂ from their burgeoning transportation sectors (Li, 2011; Dodman, 2009). It has long been projected that increasing traffic movements induced globally by both growth and increases in prosperity would be likely to increase transportation CO₂ emissions if energy consumption based on fossil fuels is not reduced (Li, 2011). Therefore, low CO₂ emissions and sustainable transportation initiatives are rising in importance in global agendas related to climate along with initiatives to change energy consumption patterns and production paradigms.

In addition to an ongoing global increase in transportation induced CO₂ emissions from urban areas, previous studies have identified a decline in bio-productive areas in cities, due to both a loss of area and both losses and degradation of vegetation in the remaining bio-productive area. Researchers have explored this reduction in bio-capacity, and concurrent increases in greenhouse gas (GHG) emissions (primarily CO₂) which jointly result in a widening deficit between the ecological footprint and bio-capacity, in turn resulting in a lack of environmental sustainability going forward (Mancini et al., 2016; Niccolucci et al., 2012). In a transport context, this can be a major indicator of the ability to maintain sustainability going forward. Several studies have linked transportation and CO₂ emissions; for example Shu and Lam (2011) studied traffic related CO₂ emissions and found spatial variations in CO₂ emissions from traffic activities correlated to differences in traffic intensity. Fan and Lei (2016), analyzed CO₂ emissions from traffic with a multivariate generalized Fisher index (GFI)

decomposition model to examine the relation between energy structure, intensity and traffic turn-over. Zahabi et al. (2012) explored the effect of the built-environment on urban transport emissions. Labib et al. (2013) investigated the ecological footprint of urban transportation at city scale. Most of the existing transport-environment studies illustrated that growing populations, and the resulting demand for transportation when combined with a lack of available public transportation, influxes of new private vehicles to urban areas and a lack of energy efficient vehicles contributed to increases in CO₂ and other pollutant emissions (Perveen et al., 2017; Fan and Lei, 2016; Yigitcanlar and Kamruzzaman, 2014).

Currently, in the extant literature there is a paucity of research that studies specific locations, zones, and routes within urban transportation systems particularly those areas with high net CO₂. However, these same areas are those that would appear to require the most urgent near-term attention from policy-makers, to formulate and implement effective strategies for local CO₂ emissions reduction. This is a matter of particular urgency due to the ongoing decline of micro-climatic conditions in such areas as well as the need to address the decline in the already limited extent of bio-productive areas in cities (Shakil et al., 2014). Most often, transportation related studies have, in past, focused on mobility, accessibility, speed, or shifts in transport modes (Kamruzzaman et al., 2015). However, these studies do not provide data on existing conditions related to traffic related pollution as defined by net GHG emissions at particular locations. Nor do they provide data on co-located bio-productive areas with the capacity to diffuse or absorb emissions from local traffic.

Available ecological footprint studies at local scale (e.g. city or neighborhood level) have provided gross estimations of CO₂ emissions from residential energy, food, waste generation and fuel consumption, and compared these with area based bio-capacities (Shakil et al., 2014; Minx et al., 2006). However, such studies do not focus on the particulars of transportation related problems. Such studies have measured overall fuel consumption for transportation movements, without either breaking down transportation movements by types or making specific transportation related recommendations to improve transportation sustainability. Hence, there is a gap in the current literature in terms of understanding how traffic related carbon emissions correlate with local available bio-capacity particularly on the specific transportation routes or given zones in cities that have the highest net levels of CO₂.

In order to potentially create real world scenarios that implement sustainable transportation strategies, characterized by low CO₂ emissions and full carbon sequestration, it will be required to understand currently existing conditions related to CO₂ emissions from

traffic as well as current carbon sequestration capacity. To facilitate such understanding the present study has rigorously utilized traffic volume and image-based remote sensing technologies to identify traffic zones which are critical, i.e. very heavily loaded, traffic nodes adjacent to bio-productive areas wherein the traffic zones are defined as the area within a 500 metre radius of the critical traffic node as areas of interest (AOI). This study measured net CO₂ emissions from transportation activities/movements in these AOIs utilizing an inventory based carbon estimation methodology (Iqbal et al., 2016). The study specifically focused on the meso-scale level of analysis, in order to gain detailed insight into the differing characteristics of transport movement at study identified AOIs.

The present study presents a new index specifically created to correlate CO₂ emissions at critical traffic nodes with adjacent bio-capacity within the studied AOIs in order to calculate a net CO₂ emission value. This quantitative index will provide an opportunity to compare CO₂ emissions with sequestration capacity at specific locations in transport networks. In aggregate, data generated by applying this index to each critical node in a transport network will provide further data supporting policy and remediation both in real-time and as part of computer-simulations of ‘what-if’ scenarios. Furthermore, changes in the index values for a location based on either changes in traffic composition or changes in local vegetation will allow policy makers to easily grasp the effect of changes to environmental parameters which will, in turn, allow them to correlate index values to any costs of changing traffic or environmental parameters allowing for easier cost-benefit calculations.

2. Materials and Methods

2.1 Conceptual Design of “Emission, Bio-Capacity Index (EBI)”

Calculation of EBI values requires two types of activities; the first is related to the determination of CO₂ emissions from different vehicle types, based on different levels of activity, fuel type and emissivity (Fig 1). EBI calculations determine the total daily and yearly CO₂ emissions from vehicular traffic activities for a given area AOI, and converts the yearly CO₂ emission value into the equivalent carbon uptake land measure (C, in global hectare) (Wiedmann and Barrett, 2010). The second type of activity requires determining the land cover types within the AOI and finding the corresponding bio-capacity for each land cover type. Index values are then generated by dividing the carbon uptake land estimated from yearly traffic CO₂ emissions by the total bio-capacity of the AOI, thus providing the value for the EBI

for that AOI (Fig 1). This relatively simple index combines the emissions of CO₂ emissions from traffic in a given area and co-located bio-capacity at the meso-scale into a single value. The basis of the model was derived from the concept of ecological footprints, and their relationship with biological capacities (Mancini et al., 2016; Ontl and Schulte, 2012; Wiedmann and Barrett, 2010).

The index developed for the present study is a new approach to providing tools that are easily and quickly comprehensible to policy-makers and non-experts and which will assist in determining the sustainability of a given transportation network as defined by net GHG emissions. Thus, this index will provide a sustainability-rating system for given locations and/or zones within a transportation network. Previously transportation networks' ecological footprints have been estimated by researchers; however combining the ecological footprint with co-located bio-capacity has heretofore only been explored in non-transport sectors such as housing, food and energy consumption (Nakajima and Ortega, 2016; Moore et al., 2013).

[Figure 1 Near Here]

2.2 Case Study Area

In order to conduct the present study of traffic-related CO₂ emissions and co-located carbon sequestration capacity, a detailed spatial extent was selected. The present study was conducted at meso-scale, at ten major intersections (nodes) within the transportation network of Dhaka. Dhaka, is one of the fastest growing mega-cities globally and a major area of urban agglomeration. As a result, the city generates millions of trips every day, and traffic activity is both intense and intensifying (Iqbal et al., 2016). A complex network of roads of varied capacity, growing demands for private vehicles, and overall increase in motorization from year to year due to better economic growth and prosperity, are driving commensurate increases in CO₂ emissions. Dhaka's major arteries are characterized by chronic traffic congestion further exacerbating fuel consumption and related CO₂ emissions (Labib et al., 2013; Karim, 1999).

In addition to traffic emissions, the city is experiencing a loss of bio-productive areas capable of sequestering CO₂ emissions. Dewan and Yamaguchi (2009) found that the city was changing its land cover types, and built up areas were increasing with concomitant decreases in vegetation, bodies of water and fallow land (Hassan and Southworth, 2017; Dewan and Yamaguchi, 2009). For example, in the period from 1999 to 2009 built up areas within Dhaka increased by 16.86% of the total urban area, while vegetative cover, bodies of water and fallow

land decreased by 3.23%, 1.98% and 10.80% respectively (Ahmed and Ahmed, 2012). Each of these declines could also be understood as a decline in available bio-productive areas. Thus, the continuing increases in CO₂ emissions combined with decreases in capacity to sequester carbon within city boundaries are resulting in continual increases in net CO₂ generation (Labib et al., 2013).

The ten study zones selected for the present study are major nodes in Dhaka's urban transportation network. The researchers delineated a buffer of one half of a kilometer radius around each node to create study zones/AOIs that allowed explicit determination of the spatial domain of measurement. The sites selected were: Mirpur 10 no., Technical Morh, Shymoli, Framgate, Mohakhali, Gulshan 1, Mog bazaar, Science lab, Motijheel and Jatrahari (Fig 2). While city-level macro scale studies (Labib et al., 2013) can provide a general overview of overall emissions and extant bio-capacity, they are lacking in the specificity and detail required for meso-level analysis (Iqbal et al., 2016; Dias et al., 2016). Therefore, the present study focused on specific sites for detailed examination of GHG emissions as well as associated bio-capacity. Study site selection was focused on traffic nodes characterized by high levels of traffic volume, connectivity and diverse trip type generation. (Labib et al., 2014).

[Figure 2 Near Here]

2.3 Vehicular Emission Estimation method

2.3.1 Emission Modeling

In order to determine the amount of CO₂ emitted due to vehicular activity in Dhaka at selected AOIs; an inventory based emission model was utilized based on vehicular travel within the AOIs. In such models "bulk" emission factors (emissivity) and vehicle activity (distance travelled) are considered in determining an emission level from each different class of vehicles. This creates an aggregate, top-down, approach to estimating transport related CO₂ emissions (Kamruzzaman et al., 2015; Wadud and Khan, 2011; Afrin et al. 2012). The specific model that was utilized to estimate carbon dioxide emissions is given in eq1 (Pan et al., 2016; Kamruzzaman et al., 2015; Neema and Jahan, 2014).

$$E_i = \sum_{j=1}^n \sum_{k=1}^n E F_{ijk} A_{jk} \quad (\text{eq1})$$

Where,

i = Type of a pollutant (in this case CO₂)

j = Fuels consumed (e.g. CNG, Gasoline)

k = Emitting Vehicular type (Volume survey)

E_i = Emissions from pollutant

EF_{ijk} = Emission Factor (g/km)

A_{jk} = Activity level for each pollutant source.

The activity level for each pollutant source within a particular study site has been determined by the following relationship in eq2;

$$A_{jk} = VKT = L \times AADT \quad (\text{eq2})$$

Where,

A_{jk} = Activity level for each pollutant source for each study area (km/day)

VKT = Vehicle Kilometers Traveled (km/day).

L = Road length (km) of the selected links within the study area

$AADT$ = Annual Average Daily Traffic (traffic volume/day)

2.3.2 Vehicle Kilometers Traveled (VKT)

The three methodological processes typically used to measure CO₂ emissions in aggregate, top-down, approaches to emissions modeling, are: (i) fuel consumption, (ii) specific vehicle tagging/tracking, or (iii) travel distance methods (e.g. VKT). In the present study vehicle activity level was determined by measurement of VKT, the most widely used method in determining CO₂ emissions at meso or micro scales (Kamruzzaman et al., 2015; Iqbal et al., 2016). For each study area, the selected road links' lengths were determined using GIS data for the Dhaka city traffic network drawn from the Detailed Area Plan database, developed by RAJUK, the city development authority. The present study made the assumption that, once a vehicle entered the study zone, and traveled the zone's road links, that this travel represented their total distance or VKT within the AOI zone(s).

2.3.3 Vehicle Fuel Usage Type

Emission levels and emissions factors for each vehicle type depend on the fuel usage as well as fuel types consumed by that particular type of vehicle (Andrews, 2008). The emission estimation model suggests that while fuel usage is a factor of major significance in determining the total amount of emissions, the type of fuel a vehicle consumes during the process of

combustion also impacts on the levels of CO₂ emitted. Thus, for the present study a detailed database summarizing the type of fuel used by each different type of vehicle found in the present study was necessary. Table 1 presents the fuel types each class of vehicle found in the present study could use and the percentage of use of each fuel type within each vehicle class. The table also correlates the fuel type usages for each vehicle class with the grams per kilometer of CO₂ emitted (Neema and Jahan, 2014; Wadud and Khan, 2011).

The specific fossil fuel types identified in Table 1 are: diesel, gasoline (petrol) and compressed natural gas (CNG). Among different vehicle classes, 100% of motorcycles observed used only gasoline, while 100% of all auto rickshaws, taxi cabs, and legunas (a partially open microbus converted to increase capacity) observed in the AOIs used CNG. A comparison of fuel usage values shows that CNG is the most used fuel amongst all vehicle classes in Dhaka due to the wide availability of natural Gas within Bangladesh.

[Table 1 Near Here]

2.3.4 Emissivity of various vehicles based on different fuel types

In the inventory based emission model, emissivity represents per unit emissions expressed in grams per kilometer of vehicle travel (gm/km) (Pan et al, 2016; Kamruzzaman et al., 2015). In order for the emissions model to provide valid results it requires the emission factors (EFs) to be accurately measured. Studies conducted by: Labib et al., (2013), and Neema and Jahan, (2014) of Dhaka's transport network used emission factors developed by Wadud and Khan (2011) and showed that these EFs do provide acceptable level of accuracy for emissions from vehicles, operating under typical traffic conditions in Dhaka. Table 1 presents the corrected emission factors correlated with the relevant different vehicles categories and fuel types. It should be noted that, table 1 shows that for some vehicle classes (e.g. buses and jeeps) have higher emission factors associated with combustion of CNG compared to diesel or petrol. However, most vehicle classes (e.g. cars, micro-buses, pickups) had lower values for their emissions factors when fueled with CNG compared to diesel and petrol. The researchers note, that the efficiency of internal combustion engines under varying fuel regimes is a complex topic impacted by many factors beyond the scope of this study and further note that both the potential quality of liquid fuel to CNG conversions (Diesel-to-CNF, Petrol-to-CNG) and overall vehicle maintenance are impacted by both parts availability and economic constraints that many vehicle operators in developing countries face (Wadud and Khan, 2011).

Overall, the researchers suggest that it may be argued that these EFs are an estimate of per-unit emissions for different modes where the vehicles involved are at least likely to have reached normal engine operating temperatures. They also note that different per-unit emission values might be calculated if all factors including: fuel efficiency, engine type, age of vehicle, quality of engine conversion from liquid to CNG fuel, and hot/cold emission values could be provided for detailed emissions modeling. However, failing the ability to do such data-intense modeling, and in light of the fact that the emissions data gathered by the current study was analyzed utilizing empirically based values for Dhaka emissions from the Wadud and Khan (2011), where they estimated and validated the EFs for the vehicle classes by their field observation and tests. The researchers are confident that EF values derived for vehicular emissions for this study represent values based on the real world traffic composition found in Dhaka by taking account of vehicle condition, fuel use and vehicle efficiency in terms of traffic operation in Dhaka.

Furthermore, as the presents study was focused on the meso-scale and based on the aggregate method of data collection, The EF values used were a necessary compromise to cover larger volume of traffic in the major streets of Dhaka city. Therefore, intensive emission modelling (usually micro-scale) was not adopted in this case study, also other issues related to congestion emission (i.e. idle emission), vehicle speed based emission variations was not considered. Such details are primarily considered for micro level studies, where in this case mesoscopic studies focused on spatial variation across transportation network at selected areas (Dias et al., 2016).

2.3.5 Traffic Volume Data Collection

Traffic volume data in the AOIs was captured manually on weekdays from February to March, 2014. Utilizing the peak hour volume survey data for each area the peak hour traffic (7.00 am to 10.00 am) value was converted to a value for daily traffic by multiplying the data captured by an empirically derived conversion factor developed for previous traffic studies in Dhaka conducted by Jahan (2013) and Neema and Jahan, (2014). These conversion factors were validated by Jahan (2013) by comparing the annual average daily traffic (AADT) at the time of Jahan's study with emissions and traffic data found in the strategic transportation plan (2005) for Dhaka (STP, 2005). Therefore, the estimated daily weekday traffic was assumed to be representative of the annual average day daily traffic (AADT) for the surveyed links within the study areas. It should be noted that, due to AADT data unavailability during the study period, this research required the application of such a conversion factor. However, if AADT

data were available for the study period for the nodal sites under study, being based on yearly observed traffic data, using actual AADT data instead of applying a conversion factor, would provide more robust results.

Based on volume of vehicular traffic, vehicle activity levels, and the fuel types of the observed vehicles, the corresponding emission factors, eq 2, and eq 1 were estimated for each AOI for a single day. This data was then converted to an annual carbon dioxide emissions value by multiplying the average number of days in a year with the daily value for each study area.

2.4 Carbon Uptake Land Estimation

The calculated total CO₂ emissions for each year were used for the estimation of the hectares of carbon uptake land that would be required to wholly neutralize these emissions. In order to determine the total biologically productive hectares of area needed to sequester total emissions a soil carbon sequestration factor was used (Moore et al., 2013; Ontl and Schulte, 2012; Monfreda et al., 2004; Wackernagel and Rees, 1996). A soil carbon sequestration factor of 1.6175 per acre of land was applied (Xu and Martin, 2010) and it was then converted to local hectare values by multiplying the resulting value by 0.4047 (Shakil et al. 2014). The obtained local hectare values were then converted to global hectare (gha) by an equivalence factor (EQF) of 1.26 (Ewing et al., 2010; Monfreda et al., 2004). In this case, eq3 summarizes the calculations required to determine the carbon uptake land value for the relevant AOIs (Moore et al., 2013; Xu and Martin, 2010).

$$C = \left(\frac{TC}{S} \right) \times EQF \quad (eq3)$$

Where,

C = Carbon uptake land (in global Hectare, gha)

TC = Total CO₂ in tons in a year (in tons)

S = Soil carbon sequestration factor (tons CO₂/acre/year)

EQF = Equivalency factor (gha/hectare)

Using eq3 total CO₂ produced in each study area could be converted to a carbon foot print expressed in gha (Global Hectare) units. This calculated area was then utilized to estimate the EBI value.

2.5 Bio-Capacity Estimation Process

2.5.1 Bio-capacity estimation

Bio-capacity (BC) is the capacity of an ecosystem to produce biological materials of use to humans and also to absorb waste they generate (including CO₂ emitted by combustion of fossil fuels) (Mancini et al., 2016;). Land areas that contribute to bio-capacity may include cropland, grazing land, fishing grounds, forest and built up areas (Wackernagel et al., 2005; Monfreda et al., 2004), eq4 is the equation for bio-capacity estimation for each AOIs considered in the present study (Mancini et al., 2016).

$$BC = \sum_{i=1}^n Ar_i * YF_i * EQF_i \quad (\text{eq4})$$

Where,

BC = Bio-capacity (in global hectare, gha)

Ar_i = Area of i land use type (hectare)

YF_i = Yield factor i type land use type (ratio of national yield and world average yield)

EQF_i = Equivalency factor for i type land use type

In this case, BC represents the total bio-capacity within an AOI. This BC is a summation of the bio-productivity of each land use type based on their yield and equivalence factor. Here, ' i ' indicates the specific type of land use, for example forest, or water. For each land use type, there is an associated specific Yield factor (YF_i) calibrated to Bangladeshi conditions, and the specific equivalency factor (EQF_i) has been accounted for in the estimation process. Satellite image analysis was used to determine the area devoted to each identified land use type (Ar). The amounts of land devoted to built-up areas, vegetation and water bodies in the AOI were estimated utilizing the following image classification method. It should be noted that, Bangladesh specific yield factor and equivalency factors were obtained from Shakil et al. (2014) and Labib et al., (2013), based on Global Footprint Network, and the YF and equivalency factors for different land cover types as listed in table 1S and 2S in the supplementary document.

2.5.2 Land use classification

Detailed land use type information for each AOI was derived by applying a supervised classification-maximum likelihood algorithm to high resolution satellite images of the areas of interest (Lillesand et al., 2014; Ahmed and Ahmed, 2012). In this case, *DigitalGlobe* satellite images (25, November 2013) were obtained and geo-referenced, as universal transverse Mercator (UTM) within the zone 46 N–datum world geodetic systems (WGS) 84. The per pixel size of the satellite images resolved at 0.6 meter. The present study's scale of analysis required

higher spatial resolution images in order to identify detailed land use types. Vegetation, water bodies, vacant land, buildings, and other infrastructure (e.g. the transport network) were land use classes utilized to determine bio-capacity. Details of these land use classes can be found in Table 3S in the supplementary document.

A sufficient number of training samples that are representative of the area under analysis are critical for accurate image classification using ERDAS Imagine software as used in the present study. Training sites within the image are required to calibrate the software to accurately identify each land cover type found within a given image being analyzed (Campbell and Wynne, 2011). The sites used for the training samples were chosen based on reference data and ancillary information collected from secondary sources; in this case Detailed Area Plans for Dhaka, 2010 maps, and Dhaka City Corporation (DCC) Ward maps. After training sites development, signature creation, and running maximum-likelihood classification algorithms in ERDAS Imagine, five classified land cover types in the AOI's were identified. These five land cover types were merged into three broader types for the purpose of analyzing bio-capacity they comprised: built-up areas, vegetation, and water bodies. In turn areas in the images identified as one of these three types were assessed for classification accuracy. In the present study, this accuracy assessment was conducted by a ground truthing cross check process. For each land use class, GPS readings at five points were taken during field visits at each AOI. Therefore, a total fifty points were available for the ten study areas (Table 45S, supplementary document), with known land use for each point and these were then geo-referenced as point features in GIS. Finally, from the error matrix, producers' accuracy, user accuracy and overall accuracy was estimated (Labib and Harris, 2018). The classified images were then utilized to find the total area of each land cover type within each study area. These total areas were then inputted into the bio-capacity estimation equation (eq4) and the bio-capacity of each study area was determined.

2.6 Emission and bio-capacity index estimation

After completing the calculation of the amount of carbon uptake land that would be required to completely neutralize a given study area's CO₂ emissions versus the bio-capacity in global hectares (gha) for each of the ten AOIs an "Emission and bio-capacity index" value was calculated for each AOI. The calculation of the index value is shown in eq5.

$$EBI = \frac{BC}{C} \quad (eq5)$$

Where,

EBI = Emission bio-capacity index (EBI)

BC = Total bio-capacity of an area (gha)

C =Carbon Uptake land of that particular area (gha)

The emission bio-capacity index value represents the over or undershoot between the value of carbon uptake land equivalent to 100% sequestration of GHG emissions and the actually measured bio-capacity. Thus, EBI values of ≥ 1 imply that the bio-capacity is adequate to sequester observed CO₂ emissions produced from vehicle operations within the AOIs. EBI values of < 1 indicate that bio-capacity or bio-productivity are not great enough for full CO₂ sequestration and or not producing enough bio-products of a value to offset the CO₂ impact of traffic related CO₂ emissions. It should be noted that, Carbon uptake land have only been estimated for traffic related CO₂ emissions, other CO₂ emissions such as industries, household waste not been considered. Therefore, EBI values in this case only represent the traffic CO₂ emissions situation and related bio-capacities. If other emission sources (e.g. Industries) been considered, the overall EBI values may have changed, and then comprehensive bio-capacity and emission scenarios might be identified, which is beyond the scope of this study.

For current study, EBI values less than 1 are categorized into three classes. These classes are generated using the equal class interval method. Based on these classes, index values are translated into an easy to understand single digit, whole number emission bio-capacity score (EBS) value (1 to 4) and equivalent color code (e.g. red, orange, yellow, and green), in which the value one which correlates with red represents very high net CO₂ emissions and correspondingly low bio-capacity as illustrated in Table 2. As presented in table 2, the EBI value ranges and corresponding scores have descriptors to that convert the number values into easily interpretable descriptions for wider audiences. The researchers chose the equal class interval method as other approaches to classification such as the natural breaks method. Despite natural break method provide better fit for the studied AOIs by optimizing the classes based on EBI values, however this classification approach do not let standardization of this method for other study areas, such as other cities. Nonetheless, the details of utilizing the natural breaks method of classification can be found in Table 4S in the Supplementary document.

[Table 2 Near Here]

3. Results

3.1 Vehicular CO₂ emission scenario in study areas

Bio-productive areas in the AOI's was generally fixed or in decline (Ahmed and Ahmend, 2012). Thus, the significant variable governing changes in net CO₂ emissions and the EBI index value was derived from vehicular exhaust. In turn, the composition of such exhaust was dependent upon three sub-variables: vehicle type, fuel use and activity levels. The results for these major sub-variables are discussed for each AOI in the following sections.

3.1.1 Vehicle type composition

Volume survey data represents the vehicle composition in the AOI under study. Fig 3 depicts the vehicle type composition in different study areas. Fig 3 shows that in most areas automobiles generated the highest share of traffic volume. It also indicated that the highest automobile usage was observed in areas V, VI and VIII (namely Gulshan 1, Science lab and the Farm-gate area). By contrast, the greatest concentration of bus traffic was observed in areas I, VII, X, IX (namely Mirpur 10, Mog-bazaar, Jatrabari and Motijheel area). CNG auto-rickshaw and motorcycle were a moderately dominant mode of travel in all study areas. Other modes (jeep, pick-up, leguna, and taxi) comprised an insignificant share of overall traffic composition.

[Fig 3 Near Here]

3.1.2 Vehicle classes aggregate share of CO₂ emissions and per-capita emissions

Each vehicle class has different emission characteristics and emission factors based on its engine type and power, age of engine, type of fuel consumed, fuel efficiency etc. Fig 4 shows variations in CO₂ emissions from different vehicle types in all AOIs. It is clear that except Area V the highest levels of CO₂ emissions observed were derived from bus service, followed by automobiles. CNG fueled buses were found to have the highest per vehicle emission factor (968 gm/km) among all the types of vehicles observed. For example, the emission factor for CNG fueled automobiles was less than one-third (237 gm/km) as much as that for CNG fueled buses. Despite automobiles comprising the majority of traffic, due to their lower emission factors they contributed less CO₂ emission compared to buses on a per vehicle basis. Overall, however, Fig 4 makes clear that automobiles and buses generated between 60 and 70% of all CO₂ emissions in the AOIs.

[Fig 4 Near Here]

Emissions per vehicle is an insufficient measure of CO₂ emissions versus person-miles traveled in urban traffic. What is key to understanding traffic volume versus emissions observed is to examine the value for the *per-capita* emissions for different vehicle classes in the AOIs. For example a full bus may have a much lower per-capita emissions value than other classes of vehicles in traffic despite having the largest per vehicle emissions value. Per-capita emissions for each vehicle class (Figure 1S, supplementary document), have been estimated using vehicle occupancy data obtained from Labib et al., (2014). Analysis of estimates of per-capita vehicle usage show that emissions per passenger are highest from automobiles. By contrast, public transit buses have the lowest per-capita emissions. Aggregating all the AOIs studied, the per-capita emissions generated by automobiles were ten times higher than the per capita value for buses. This result is consistent with other studies such as Wang et al. (2017) and Wang et al. (2015), whose reported results were similar to those in the present study, with buses having the highest occupancy and thus the lowest per-capita CO₂ emission levels.

3.1.4 Total CO₂ emissions in each AOI

This section provides estimates of total CO₂ emissions from the transportation sector for the studied AOIs. In order to determine the total daily CO₂ emissions from each AOI, emissions data for traffic on all links within each study area were combined. Annual emissions were projected by multiplying the number of days in a non-leap year by the net CO₂ emissions calculated for each AOI daily, as shown in Table 3. Details of daily and yearly CO₂ emission for all AOIs can be found in Table 47S, in the supplementary document. As illustrated in table 3 ‘Total tons of CO₂ in a year’ column, the lowest CO₂ emissions occurred in Area I; by contrast the highest CO₂ emissions were observed in Area X the most active node in the city transportation network. Higher CO₂ emissions levels correlated with higher levels of transportation activities in the AOI’s in the present study. This was not only illustrated by very high levels of traffic in Area X but also by the low levels of traffic in Area I. Detailed Area Plan land use data supported this as well as our findings that Area I was predominantly residential and thus supporting fewer commercial and administrative activities (Labib et al., 2014). As a result, Area I generated less transportation activity and hence fewer emissions. Its predominantly residential nature also meant that it was an area of trip production, rather than trip attraction. Combining all AOIs in the present study generated an average value for CO₂ emissions of thirteen tons of CO₂ emitted per day. Fig. 5 and Fig 6 show the quantity of CO₂ emissions mapped to the AOI’s in the present study. The emissions calculation for each link within each AOI is presented in Table 5S-46S, Supplementary Document.

[Figure 5 Near Here]

[Figure 6 Near Here]

3.2 Carbon Uptake Land equivalent to CO₂ emissions in AOIs

Utilizing the estimated CO₂ emissions from transportation activities in each AOI, the carbon uptake land value that would be required to absorb all CO₂ emissions in each AOI was determined. Table 3 presents a summary of the estimated amount of carbon uptake land that would be required to neutralize and sequester all CO₂ emissions at the time of the present study. The table shows that the largest carbon uptake land value would be required for areas IV and VIII (Farm-gate and Science Lab). By contrast the lowest carbon footprint was found in areas I and VII (Mirpur 10 and Mog-bazaar). For all cases, the carbon uptake land value required was calculated by multiplying total net annual CO₂ production with the appropriate conversion factors, first for sequestration of all CO₂ emitted expressed in tons per acre per year, followed by a conversion of this value to hectares and finally a conversion of the hectare value to global hectares to arrive at the estimated carbon uptake land area expressed in global hectares. These estimated carbon uptake land (C) values were then utilized as input values to eq5 in determining the EBI values.

[Table 3 Near Here]

3.3 Bio-capacity of each AOI

Bio-capacity is one of the major constituents of the EBI. Therefore, the value for the biological capacity of each AOI was estimated utilizing eq4 in the methodology section. The outcomes of the bio-capacity estimation process are described below.

3.3.1 Bio-productive areas

For bio-capacity estimation three broad categories of land use types were identified namely: i) built-up areas (comprising buildings, infrastructure, roads), ii) vegetation, and iii) bodies of water. Figures 7 and 8 represent the results of the present study's land surface classifications in each AOI. It is evident that, among the three classes, built-up land represented most of the hectarage in each AOI with the exception of areas V (Gulshan 1) (Figure 7d) and II (Technical Morh) (Figure 8f). Nine of the AOIs had limited areas of open water and area VI (Farm-gate) within the selected buffer range (Fig. 8j) had no open water area whatsoever. The greatest quantities of vegetation were found in areas II (Technical morh) as shown in Fig. 8 (f) and I (Mirpur 10) as shown in Fig. 7 (a). The lowest quantity of vegetation was found in area

X (Jatrabari area) as presented in Fig. 8 (g). The hectareage values calculated for each of the three classes of land use types were utilized to determine the actual bio-capacity of the AOIs.

[Fig 7 Near Here]

[Fig 8 Near Here]

Employing an error matrix accuracy test on the classified images was required to check the accuracy of the classification process. Correlating the error matrix producer's accuracy and the user's accuracy provided a determination of overall accuracy (Table 49S, Supplementary Document). The Kappa coefficient was also verified. Producers' and users' accuracies were found to be over 80% for the built-up and vegetation classes. Overall accuracy of image classification was 84% and the kappa coefficient value was 0.75 (Table 50S, Supplementary Document). Kappa values. Generally a kappa value of more than 0.80 indicates that image classification was both very good and highly acceptable, however values of more than 0.75 are widely acceptable (Lillesand et al., 2014; Campbell & Wynne, 2011). Accuracy Test points, with GPS coordinate values for UTM zone 46 N for the AOIs are presented in Table 48S in Supplementary Document.

3.3.2 Bio-capacity of selected areas

Utilizing the land use areas identified from the analyzed images and eq4, the bio-capacity (BC) value for each AOI was determined. As an example, Table 4 illustrates the calculation process utilized to calculate the bio-capacity for Area I (Mirpur 10). It was found that the total bio-capacity was approximately 267.8 gha. Employing this calculation methodology the bio-capacity for each AOI was determined. The results for each AOI are summarized in Table 5 under the 'Bio-capacity Area' column. The actual bio-capacity estimation calculations for each AOI are provided in Table 51S in the supplementary document.

[Table 4 Near Here]

Table 4 illustrates that, the yield factors for built-up areas are greater than those for forest or bodies of water, hence the estimated bio-capacities of built-up areas have higher values than those for vegetation and water bodies. This apparently counter-intuitive result can cause confusion for readers not familiar with the theory supporting the concept of National Footprint Accounts (NFA) and bio-capacities. According to the NFA bio-capacity is defined

as “the biosphere’s supply (bio-capacity) of ecosystem products and services in terms of the amount of bio-productive land and sea area needed to supply these products and services.” (Borucke et al., 2013, p 518). However, due to lack of data unavailability regarding the bio-productivity of built-up areas, built-up land is considered the *equivalent* of cropland in terms of world average productivity (Galli, 2015; Borucke et al., 2013). This assumption is developed on the basis of the observation that, in general human settlements (e.g. Urban areas, built infrastructure) are located in fertile areas which may have the potentials for high yielding cropland (Borucke et al., 2013; Wackernagel et al., 2002). As a result of this assumption, despite having no photosynthesis and thus no direct bio-productivity from built-up land, considering yield factor of cropland as yield factor for built-up areas over or underestimates total bio-capacity.

In this case, as cropland in Bangladesh has a higher yield factor than either forest or bodies of water (Table S1, Supplementary document), and cropland is used as a value equivalent for built-up areas, the consequence is that built-up areas have a higher yield factor than forest’s or bodies of water. Nonetheless, this equivalence allows to create a dummy-value for the productivity that occurs in these areas. It should be noted that, due to inherent theoretical limitation of NAF’s bio-capacity estimation process, current study may over/under estimated the bio-productivity of built-up areas compared to vegetation and waterbodies. In reality to improve overall bio-capacity, more vegetation cover and water bodies with greater yields would act as positive contributors, in contrast increasing built-up areas would only reduce overall bio-capacity.

3.4 Emission and bio-capacity index values

Dividing the bio-capacity (BC) area by the estimated carbon uptake land value (C) allows the EBI to be determined. Table 5 shows that nine out of ten areas possess EBI value of <0.33 which equates to a EBS of 4, both of these values imply that bio-capacity is in critically short supply in these areas and net CO₂ emissions are extremely high. With the exception of Area I (Mirpur 10) all other AOIs would require the addition of very large amounts of bio-productive land within their geographical boundaries if they were to have the capacity to absorb all the net CO₂ emissions currently emitted by the transportation sector in each respective AOI. The very high amounts of net CO₂ emissions are strongly related to high and continuously increasing traffic volumes and high usage levels for private vehicles but may also suggest that there are inefficiencies inherent in operating old or poorly maintained vehicles, related to poorly tuned engines, nonfunctioning or ineffective pollution controls on engines and related

issues pertaining to excessive use of fuel. Overall, Table 5 conclusively demonstrates that the amount of bio-productive area within the AOI's is inadequate to sequester all emitted CO₂, and illustrates the serious gap between levels of CO₂ production and CO₂ sequestration.

[Table 5 Near Here]

Both the raw data-take and the calculated EBI values are highly indicative of the very high levels of CO₂ emissions from transportation activities in nine of the ten AOIs. It clearly indicates that the overall emissions of CO₂ from the transportation sector in Dhaka are well in excess of levels that available bio-capacity can remediate or counter balance. Indeed, the carbon uptake land value that equates to the ability to sequester all CO₂ emissions from the transportation sector in Dhaka is a hectare value larger than the hectare value for all land within the city limits (Labib et al. 2013).

4. Discussions

4.1 Major Factors Contributing to higher CO₂ emissions and lower EBI values

The present study's analysis highlighted several factors responsible for the high net CO₂ emissions in Dhaka. Results showed that both the composition of vehicular traffic and the limited bio-capacity of extant land cover types contributed to observed high net emissions. Those AOIs with lower EBI values closely correlated with higher levels of vehicular activity and more built-up land use area within the AOI. In these areas, the volume of daily vehicular traffic through the links of each AOI was quite large. These AOIs were exemplified by high traffic volume, host intersections characterized by intermittent spikes in volume, and differentiation between trip originating and terminating traffic. Traffic nodes in AOIs such as Farmgate (Area X) and Science Lab (Area IX) explicitly exhibit these characteristics. Therefore, it can be implied that, intermittent nodes (usually having higher connectivity) which connect more trips need careful design, and more effective traffic regulations to assist in controlling CO₂ emissions, as higher traffic density would likely raise levels of such emissions (Ferreira and d'Orey, 2012).

The results of the present study also indicate that lower EBI value (and corresponding high EBS score) traffic network nodes are characterized by high levels of private vehicle usage (e.g. automobiles and motor bikes) versus the use levels of public transit such as buses. This finding is common to a number of recent studies including Iqbal et al, (2016), Kamruzzaman et al., (2015); and Druckman and Jackson, (2008). Equally, it is clear from the present study's results combined with that increases in motorized traffic both public and private are the driving

force for increases in overall net CO₂ emissions from the transportation sector in Dhaka (Labib et al., 2013). As Bangladesh continues to experience a growing economy, the affordability of private vehicles increases in lock-step among private citizens (Islam et al., 2016). Furthermore, until now there has been no effort made to control the usage of private vehicles in Dhaka, and no restrictions for private vehicles on busy and crucial nodes. Thus, a large and increasing component of the increase in motorized traffic comprises of personal vehicles which are becoming a major component in future increases in CO₂ emissions in Dhaka from transportation.

Another factor contributing to CO₂ emissions in Dhaka is an obsolescent traffic signal system. In Dhaka no coordinated system of traffic signals geared to optimizing traffic patterns and traffic throughput exists. The current signal system was not designed for either current or projected levels of traffic. Indeed, the current signal system has such limited capacity that in the AOIs researchers observed traffic police manually attempting to coordinate traffic signals during periods of high traffic volume, for example Farmgate (Area X) experiences massive traffic congestion the majority of each day. This congestion is abetted by the fact that the signal systems on different links in the area are not coordinated with each other. As a result, traffic police are required to assist in controlling traffic. However, they must use their personal judgment, uninformed by conditions at other intersections, as to how much time ought to be allocated to each phase of the signal cycle in order to optimize overall traffic flow in all links in the intersection they are attempting to control. These inadequacies of the present system observed during the present study appear to actually contribute to inducing massive congestion on some links in the AOIs. Unfortunately, such congestion is associated with increased trip times, increased costs to human health and much increased CO₂ emissions (Iqbal et al., 2016; Labib et al., 2013). Ferreira and d'Orey, (2012) demonstrated that, a well-organized intelligent transportation system (ITS) based traffic signaling system is effective in mitigating CO₂ emissions in high density traffic areas.

The major arterial roads of Dhaka do not provide access for fuel free transport modes such as bicycles or rickshaws (Mahmud et al., 2012). In this study, the nodes examined in the AOIs were connecting major arterial roads, It must be noted that FFTs do not emit CO₂, and they are widely used in secondary or access roads in Dhaka city (Labib et al., 2016). However, while it might be speculated that the absence of FFTs on major roads might be a reason for greater CO₂ production in these nodes due to the increased use of motorized alternatives there is the issue highlighted by the present study that major arteries in Dhaka are near, at, or over

their capacity limits. Injecting slow-moving FFTs with limited passenger carrying capacity into arterial traffic could actually lower overall passenger throughput on these arteries and increase emissions due to further increasing congestion caused by mixing FFTs with motorized traffic on major arteries. Furthermore, mixing FFT's and motorized transport on major roadways causes serious safety issues and is a practice discouraged world-wide in urban settings. However, given the popularity of FFT's in Dhaka and their environmentally benign nature it is possible that exploring the possibility of providing dedicated lanes for FFTs might provide the path to an effective solution.

Another major problem existing in Dhaka's traffic is related to the abundance of unfit vehicles on the road. During the traffic volume survey the researcher observed a predominance of older vehicles often exhibiting major deficiencies in maintenance, both public (e.g. bus) and private (e.g. jeep, station wagon) in traffic. Field observation showed, that often these vehicles had been marked by the traffic police as unfit. Upon inquiry as to why so many such vehicles were to be seen in traffic it became apparent that irregular inducements provided by the owners of the vehicles to avoid formal legal action were common. Thus, weaknesses both in the practice of policing and in the justice system are transport issues insofar as they contribute to allowing both unsafe and high emitting vehicles to remain on the road in Dhaka.

A final issue is the levels of vegetation growing in the AOIs. Neema and Jahan (2014), found that the presence of increased amounts of road side vegetation correlates with higher levels of CO₂ sequestration along such roadsides. However, the AOIs in the present study had little greenery growing directly along their links or, indeed, anywhere within their overall areas.

4.2 Impacts and way forward

From an ecological point of view, the transportation system in Dhaka is not sustainable due to the fact that its extant bio-productive areas cannot sequester even a large fraction of current CO₂ emission levels. Furthermore, the areas of the city devoted to land uses that support what bio-capacity exists are shrinking (Hassan and Southworth, 2017). Further shrinkage of bio-capacity in a city whose population and hence, traffic levels continue to increase suggest that net CO₂ emissions both from traffic activities and other activities will also continue to increase. Such increases will, in turn intensify heat-island effects as well as supporting increases in other air pollutants besides CO₂ (Harlan and Ruddell, 2011; Han and Naeyer, 2006).

4.2.1 Policy Implications

The rating system created for the present study may aid in both planning professionals and policy makers being able to more easily grasp the severity of the CO₂ emissions problem under current and projected conditions. The index may also act as a surrogate value for the negative impact emissions have on health, livability and the environment in Dhaka. Based on the results of the current, several policy initiatives recommended to improve the overall sustainability, livability and environment of Dhaka.

Public Transit

The Strategic Transport Plan 2005 for Dhaka recommended introducing bus rapid transit (BRT) in the main corridors of the city as an effective and efficient solution to resolve the poor service quality and capacity constraints of current bus systems in Dhaka. Despite having been recommended as long ago as 2005 this is an excellent suggestion with even greater merit, due to urban growth, than when it was first mooted (Rahman et al., 2012). Additionally, as of 2017 the authors note that a new Mass Rapid Transit is under construction in Dhaka in association with JICA, and this may change the composition of traffic in Dhaka with a greater emphasis on public transit. However, experience in other major cities particularly in developing economies suggests that as long as the numbers of private vehicles continues to increase; a highly likely scenario in a country with a growing economy and a growing middle-class, any reduction in overall CO₂ emissions and congestion on surface routes will likely be a transitory one.

Low Emissions Zones

Apart from attempts to engender a travel demand shift by promoting public transit (e.g. Metro, BRT), FFTs, and encouraging mixed land use (McBain et al., 2017; Nakamura and Hayashi, 2013) in Dhaka, low-emission zone initiatives could be an effective solution to calm traffic intensities and CO₂ production in key nodes (or highly connective nodes). For example, nodes in AOIs VIII, IX, and X might have low emission zoning strategies implemented to discourage the number of trips with private vehicles. Despite having potential political difficulties in implementation, low emission zoning policy could be implemented with relatively little cost and within a short period of time. Implementation of low emission zones appears a reasonable solution, similar to the low emission zones in London (Ellison et al., 2013) and other European cities (Dias et al., 2016; Holman et al., 2015).

Improved Traffic Management

Another policy intervention might be needed in improving the traffic management system. A key component to minimizing both emissions and maximizing quality of life is the design of a modern traffic management plan for Dhaka supported by a high-capacity and fully functional traffic signaling system optimized to maximize traffic throughput. The authors strongly recommend replacing the current obsolete system requiring continuous human intervention by traffic police with a new optimized signaling system using ITS (Satyanarayana et al., 2018). Gains in economic efficiency and productivity within Dhaka may well yield more than the cost of such a system.

4.2.2 Other potential low-carbon interventions

In addition to a traffic calming strategy, a ride-share program may be an effective solution in the context of Dhaka's needs. Labib et al., (2013) suggested that, carpool or car share initiatives might be effective in Dhaka and as of 2016 such services have been implemented in the city in with relatively limited coverage. Additionally, private rideshare services such Uber and Pathao-Moving Bangladesh (a local ride-sharing company providing motor-cycle rides), both introduced in 2017, have been gaining popularity among those needing transportation in Dhaka. At least two recent studies had results suggesting that ride-share services have successfully reduced private/personal vehicle usage and congestion in urban areas in which such services were introduced (Li et al., 2017; Alexander and González, 2015). Thus, officially encouraging and monitoring ride-share services may to some extent, assist in ameliorating traffic induced CO₂ emissions.

Urban greening initiatives including road side tree plantation, green roof creation, green wall installation and other green infrastructure creation would not only assist in CO₂ sequestration but also in overall improvements in living conditions, quality of life and even storm water control. In particular among the studied AOIs due to their extremely low EBI values, Area V, VI, IX, and X would appear to require immediate action to improve their vegetative coverage utilizing some rapid measure such as Green roofs and green walls (Rowe, 2011).

5. Conclusion and further development

With the growing concern for CO₂ emissions resulting from vehicular traffic it has become necessary to better understand and identify the areas within cities such as Dhaka where CO₂ emissions from vehicles have outstripped the local capacity to absorb and sequester such

emissions along with associated emissions that can be a direct threat to human health. In light of this need the present study has as one of its key purposes the development of an EBI rating system that would assist in identifying the traffic routes and zones within an urban transportation network that are deemed ecologically unsustainable due to high net CO₂ emissions and low local bio-capacity. This rating system combines the domain of traffic emission related studies with ecological footprint and bio-capacity related studies. In turn this has allowed the establishment of index values for the previously missing relationship between urban transportation systems and their local environments.

The present study utilizing the EBI successfully mapped and measured net CO₂ emissions at key traffic nodes in Dhaka. As a result, it provided an understanding of the CO₂ sequestration capacity associated with each AOI but more importantly it created a map overlaying the traffic network highlighting problem areas using an index that is easy to grasp for policy makers. The EBI rating system found very high (level 4, code red) index values correlated with very low CO₂ absorption and high net CO₂ emissions at nine out of ten key nodes. Thus of the ten nodes only one was moderately sustainable as defined by having the capacity to absorb a considerable amount of the CO₂ emissions in its local area. Based on the results, it is reasonable to conclude that the nodes with lowest EBI values require urgent attention to ameliorate both their current net CO₂ emissions as well as control future increases in such emissions.

While identifying critical nodes as ecologically unsustainable as they currently stand, in the Dhaka road network was one proximate reason for conducting the present study a wider goal was to create an index that reduces the many potential factors impacting net emissions to a single digit number and associated colour. This, in turn, allows the creation of coloured map overlays for urban areas highlighting problem areas clearly while also showing their relationship to one another and to the underlying transportation networks at a glance. It is the opinion of the authors that it is not enough to know the facts but necessary to be able to convey them clearly and easily especially to policy makers and potentially to other interested groups and/or the wider urban population. Finally, given sufficient data and adequate simulation software the EBI could be valuable as one output modality for modeling different outcomes in 'What-if' scenarios of CO₂ emissions, with the EBI value and color changing as parameters such as: traffic intensity, signal optimization, different road surfaces and differing levels of vegetation inter alia are varied.

Despite the careful attention of the authors, this study is not presented as being comprehensive. It would benefit from further testing of the new index as well as potentially improving on the measurement techniques used in the index creation process in order to further refine the index to ensure the most robust results.

Conflict Of Interests

No potential conflict of interest was reported by the authors

Acknowledgement

We would like to thank Mr. Zahid Hasan Siddiquee of Institute of Water Modelling, Bangladesh for his input regarding the collection of remote sensing data for the study area. Thanks to Dr. Md. Musleh Uddin Hasan and Jinat Jahan of Department of Urban and Regional Planning for their comments in conducting this study. We would also like to thank the anonymous reviewers of this paper for their constructive comments and suggestions.

References

- Afrin, T., Ali, M. A., Rahman, S. M., & Wadud, Z. (2012). Development of a Grid-Based Emission Inventory and a Source-Receptor Model for Dhaka City. In *Floria: The US EPA's International Emission Inventory Conference. Accessed April* (Vol. 4, p. 2013).
- Ahmed, B., & Ahmed, R. (2012). Modeling urban land cover growth dynamics using multi-temporal satellite images: a case study of Dhaka, Bangladesh. *ISPRS International Journal of Geo-Information*, 1(1), 3-31. DOI: [10.3390/ijgi1010003](https://doi.org/10.3390/ijgi1010003)
- Alexander, L. P., & González, M. C. (2015). Assessing the impact of real-time ridesharing on urban traffic using mobile phone data. *Proc. UrbComp*, 1-9.
- Amekudzi, A. A., Khisty, C. J., & Khayesi, M. (2009). Using the sustainability footprint model to assess development impacts of transportation systems. *Transportation Research Part A: Policy and Practice*, 43(4), 339-348. DOI: <https://doi.org/10.1016/j.tra.2008.11.002>

- Andrews, C. J. (2008). Greenhouse gas emissions along the rural-urban gradient. *Journal of Environmental Planning and Management*, 51(6), 847-870. DOI: <https://doi.org/10.1080/09640560802423780>
- Borucke, M., Moore, D., Cranston, G., Gracey, K., Iha, K., Larson, J., Lazarus, E., Morales, J.C., Wackernagel, M. and Galli, A., (2013). Accounting for demand and supply of the biosphere's regenerative capacity: The National Footprint Accounts' underlying methodology and framework. *Ecological Indicators*, 24, pp.518-533.
- Campbell, J.B., & Wynne, R.H. (2011). *Introduction to remote sensing*. New York, NY: Guilford Press.
- Dewan, A. M., & Yamaguchi, Y. (2009). Land use and land cover change in Greater Dhaka, Bangladesh: Using remote sensing to promote sustainable urbanization. *Applied Geography*, 29(3), 390-401. DOI: <https://doi.org/10.1016/j.apgeog.2008.12.005>
- Dias, D., Tchepel, O., & Antunes, A. P. (2016). Integrated modelling approach for the evaluation of low emission zones. *Journal of environmental management*, 177, 253-263. DOI: <https://doi.org/10.1016/j.jenvman.2016.04.031>
- Dodman, D. (2009). Blaming cities for climate change? An analysis of urban greenhouse gas emissions inventories. *Environment and Urbanization*, 21(1), 185-201. DOI: 10.1177/0956247809103016
- Druckman, A., & Jackson, T. (2008). Household energy consumption in the UK: A highly geographically and socio-economically disaggregated model. *Energy Policy*, 36(8), 3177-3192. DOI: <https://doi.org/10.1016/j.enpol.2008.03.021>
- Ellison, R. B., Greaves, S. P., & Hensher, D. A. (2013). Five years of London's low emission zone: Effects on vehicle fleet composition and air quality. *Transportation Research Part D: Transport and Environment*, 23, 25-33. DOI: <https://doi.org/10.1016/j.trd.2013.03.010>
- Ewing, B., Reed, A., Galli, A., Kitzes, J. and Wackernagel, M., 2010. Calculation methodology for the national footprint accounts.
- Fan, F., & Lei, Y. (2016). Decomposition analysis of energy-related carbon emissions from the transportation sector in Beijing. *Transportation Research Part D: Transport and Environment*, 42, 135-145. DOI: <https://doi.org/10.1016/j.trd.2015.11.001>

- Ferreira, M., & d'Orey, P. M. (2012). On the impact of virtual traffic lights on carbon emissions mitigation. *IEEE Transactions on Intelligent Transportation Systems*, 13(1), 284-295. DOI: [10.1109/TITS.2011.2169791](https://doi.org/10.1109/TITS.2011.2169791)
- Galli, A., (2015). On the rationale and policy usefulness of Ecological Footprint Accounting: The case of Morocco. *Environmental science & policy*, 48, pp.210-224. DOI: <https://doi.org/10.1016/j.envsci.2015.01.008>
- Global Footprint Network, (2011). National Footprint Accounts, 2011. Available at: www.footprintnetwork.org
- Hassan, M. M., & Southworth, J. (2017). Analyzing Land Cover Change and Urban Growth Trajectories of the Mega-Urban Region of Dhaka Using Remotely Sensed Data and an Ensemble Classifier. *Sustainability*, 10(1), 10. DOI: [10.3390/su10010010](https://doi.org/10.3390/su10010010)
- Harlan, S. L., & Ruddell, D. M. (2011). Climate change and health in cities: impacts of heat and air pollution and potential co-benefits from mitigation and adaptation. *Current Opinion in Environmental Sustainability*, 3(3), 126-134. DOI: <https://doi.org/10.1016/j.cosust.2011.01.001>
- Han, X., & Naeher, L. P. (2006). A review of traffic-related air pollution exposure assessment studies in the developing world. *Environment international*, 32(1), 106-120. DOI: <https://doi.org/10.1016/j.envint.2005.05.020>
- Holman, C., Harrison, R., & Querol, X. (2015). Review of the efficacy of low emission zones to improve urban air quality in European cities. *Atmospheric Environment*, 111, 161-169. DOI: <https://doi.org/10.1016/j.atmosenv.2015.04.009>
- Iqbal, A., Allan, A., & Zito, R. (2016). Meso-scale on-road vehicle emission inventory approach: a study on Dhaka City of Bangladesh supporting the 'cause-effect' analysis of the transport system. *Environmental monitoring and assessment*, 188(3), 149. DOI: [10.1007/s10661-016-5151-4](https://doi.org/10.1007/s10661-016-5151-4)
- Islam, I., Mostaquim, M. E., & Biswas, S. K. (2016). Analysis of Possible Causes of Road Congestion Problem in Dhaka City. *Imperial Journal of Interdisciplinary Research*, 2(12).

- Jahan, J. (2013). Towards mitigation of vehicular emission through roadside trees in Dhaka city: a GIS-based simulation approach. *Master's Thesis, Department of URP, Bangladesh University of Engineering and Technology*.
- Jeon, C. M., Amekudzi, A. A., & Guensler, R. L. (2013). Sustainability assessment at the transportation planning level: Performance measures and indexes. *Transport Policy*, 25, 10-21. DOI: <https://doi.org/10.1016/j.tranpol.2012.10.004>
- Kamruzzaman, M., Hine, J., & Yigitcanlar, T. (2015). Investigating the link between carbon dioxide emissions and transport-related social exclusion in rural Northern Ireland. *International Journal of Environmental Science and Technology*, 12(11), 3463-3478. DOI: <https://doi.org/10.1007/s13762-015-0771-8>
- Karim, M. M. (1999). Traffic pollution inventories and modeling in metropolitan Dhaka, Bangladesh. *Transportation Research Part D: Transport and Environment*, 4(5), 291-312. DOI: [https://doi.org/10.1016/S1361-9209\(99\)00010-3](https://doi.org/10.1016/S1361-9209(99)00010-3)
- Labib, S.M. and Harris, A., (2018). The potentials of Sentinel-2 and LandSat-8 data in green infrastructure extraction, using object based image analysis (OBIA) method. *European Journal of Remote Sensing*, 51(1), pp.231-240. DOI: <https://doi.org/10.1080/22797254.2017.1419441>
- Labib, S. M., Rahaman, M. Z., & Patwary, S. H. (2016). Comprehensive evaluation of urban public Non-Motorized Transportation Facility services in Dhaka. 8th MAC- 2016. Prague, Czech Republic.
- Labib, S. M., Rahaman, M. Z., & Patwary, S. H. (2014). Green transport planning for Dhaka city: Measures for environment friendly transportation system. *Undergraduate thesis, Bangladesh University of Engineering and Technology, Department of Urban and Regional Planning*. DOI: 10.13140/RG.2.2.21578.26564
- Labib, S. M., Mohiuddin, H., & Shakil, S. H. (2013). Transport sustainability in Dhaka: a measure of ecological footprint and means of sustainable transportation system. *Journal of Bangladesh Institute of Planners*, 6, 137–147.
- Li, J. (2011). Decoupling urban transport from GHG emissions in Indian cities—A critical review and perspectives. *Energy policy*, 39(6), 3503-3514. DOI: <https://doi.org/10.1016/j.enpol.2011.03.049>

- Li, Z., Hong, Y., & Zhang, Z. (2017). An empirical analysis of on-demand ride sharing and traffic congestion. Proceedings of the 50th Hawaii International Conference on System Sciences. Hawaii, USA.
- Lillesand, T., Kiefer, R. W., & Chipman, J. (2014). *Remote sensing and image interpretation*. John Wiley & Sons.
- Loo, B. P., & Li, L. (2012). Carbon dioxide emissions from passenger transport in China since 1949: implications for developing sustainable transport. *Energy policy*, 50, 464-476. DOI: <https://doi.org/10.1016/j.enpol.2012.07.044>
- Mancini, M. S., Galli, A., Niccolucci, V., Lin, D., Bastianoni, S., Wackernagel, M., & Marchettini, N. (2016). Ecological footprint: refining the carbon footprint calculation. *Ecological indicators*, 61, 390-403. DOI: <https://doi.org/10.1016/j.ecolind.2015.09.040>
- Mahmud, K., Gope, K., & Chowdhury, S. M. R. (2012). Possible causes & solutions of traffic jam and their impact on the economy of Dhaka City. *Journal of Management and Sustainability*, 2(2), 112. <http://dx.doi.org/10.5539/jms.v2n2p112>
- McBain, B., Lenzen, M., Albrecht, G., & Wackernagel, M. (2017). Reducing the Ecological Footprint of Urban Cars. *International Journal of Sustainable Transportation*, 12 (2), 117-127. DOI: <https://doi.org/10.1080/15568318.2017.1336264>
- Minx, J., Baiocchi, G., Wiedmann, T., Barrett, J., Creutzig, F., Feng, K., Förster, M., Pichler, P.P., Weisz, H. and Hubacek, K., (2013). Carbon footprints of cities and other human settlements in the UK. *Environmental Research Letters*, 8(3), p.035039. DOI:10.1088/1748-9326/8/3/035039
- Monfreda, C., Wackernagel, M., & Deumling, D. (2004). Establishing national natural capital accounts based on detailed ecological footprint and biological capacity assessments. *Land Use Policy*, 21(3), 231-246. DOI: <https://doi.org/10.1016/j.landusepol.2003.10.009>
- Moore, J., Kissinger, M., & Rees, W. E. (2013). An urban metabolism and ecological footprint assessment of Metro Vancouver. *Journal of environmental management*, 124, 51-61. DOI: <https://doi.org/10.1016/j.jenvman.2013.03.009>

- Nakajima, E. S., & Ortega, E. (2016). Carrying capacity using emergy and a new calculation of the ecological footprint. *Ecological Indicators*, 60, 1200-1207. DOI: <https://doi.org/10.1016/j.ecolind.2015.08.054>
- Nakamura, K. and Hayashi, Y., (2013). Strategies and instruments for low-carbon urban transport: An international review on trends and effects. *Transport Policy*, 29, pp.264-274. DOI: <https://doi.org/10.1016/j.tranpol.2012.07.003>
- Neema, M. N., & Jahan, J. (2014). An innovative approach to mitigate vehicular emission through roadside greeneries: A case study on arterial roads of Dhaka city. *Journal of Data Analysis and Information Processing*, 2(01), 32. DOI: 10.4236/jdaip.2014.21005
- Niccolucci, V., Tiezzi, E., Pulselli, F. M., & Capineri, C. (2012). Biocapacity vs Ecological Footprint of world regions: A geopolitical interpretation. *Ecological Indicators*, 16, 23-30. DOI: <https://doi.org/10.1016/j.ecolind.2011.09.002>
- Ontl, T. A., & Schulte, L. A. (2012). Soil carbon storage. *Nature Education Knowledge*, 3(10), 35.
- Pan, L., Yao, E., & Yang, Y. (2016). Impact analysis of traffic-related air pollution based on real-time traffic and basic meteorological information. *Journal of environmental management*, 183, 510-520. DOI: <https://doi.org/10.1016/j.jenvman.2016.09.010>
- Perveen, S., Yigitcanlar, T., Kamruzzaman, M., & Hayes, J. (2017). Evaluating transport externalities of urban growth: a critical review of scenario-based planning methods. *International Journal of Environmental Science and Technology*, 14(3), 663-678. DOI: <https://doi.org/10.1007/s13762-016-1144-7>
- Rahman, M. S. U., Timms, P., & Montgomery, F. (2012). Integrating BRT systems with rickshaws in developing cities to promote energy efficient travel. *Procedia-Social and Behavioral Sciences*, 54, 261-274. DOI: <https://doi.org/10.1016/j.sbspro.2012.09.745>
- Rowe, D.B., (2011). Green roofs as a means of pollution abatement. *Environmental pollution*, 159(8-9), pp.2100-2110. DOI: <https://doi.org/10.1016/j.envpol.2010.10.029>
- Shakil, S. H., Kuhu, N. N., Rahman, R., & Islam, I. (2014). Carbon Emission from Domestic Level Consumption: Ecological Footprint Account of Dhanmondi Residential Area, Dhaka, Bangladesh—A Case Study. *Australian Journal of Basic and Applied Sciences*, 8 (7), 265-276.

- Satyanarayana, M.S., Mohan, B.M. and Raghavendra, S.N., 2018. Intelligent Traffic System to Reduce Waiting Time at Traffic Signals for Vehicle Owners. In *Artificial Intelligence and Evolutionary Computations in Engineering Systems* (pp. 281-287). Springer, Singapore. DOI: https://doi.org/10.1007/978-981-10-7868-2_28
- Shu, Y., & Lam, N. S. (2011). Spatial disaggregation of carbon dioxide emissions from road traffic based on multiple linear regression model. *Atmospheric environment*, 45(3), 634-640. DOI: <https://doi.org/10.1016/j.atmosenv.2010.10.037>
- STP (2005). Strategic transport plan (STP) for Dhaka, final report 2005. *Dhaka Transport Coordination Board, Government of the People's Republic of Bangladesh*.
- Wackernagel, M., Monfreda, C., Moran, D., Wermer, P., Goldfinger, S., Deumling, D., & Murray, M. (2005). National footprint and biocapacity accounts 2005: the underlying calculation method.
- Wackernagel, M., Schulz, N.B., Deumling, D., Linares, A.C., Jenkins, M., Kapos, V., Monfreda, C., Loh, J., Myers, N., Norgaard, R. and Randers, J., (2002). Tracking the ecological overshoot of the human economy. *Proceedings of the national Academy of Sciences*, 99(14), pp.9266-9271. DOI: 10.1073/pnas.142033699
- Wackernagel, M., & Rees, W. (1998). *Our ecological footprint: reducing human impact on the earth* (No. 9). New Society Publishers.
- Wadud, Z., & Khan, T. (2011). Compressed Natural Gas Conversion of Motor Vehicles in Dhaka: Valuation of the Co-benefits. In Transportation Research Board 90th Annual Meeting (No. 11-2764)
- Wang, Y., Yang, L., Han, S., Li, C., & Ramachandra, T. V. (2017). Urban CO₂ emissions in Xi'an and Bangalore by commuters: implications for controlling urban transportation carbon dioxide emissions in developing countries. *Mitigation and Adaptation Strategies for Global Change*, 22(7), 993-1019. DOI: <https://doi.org/10.1007/s11027-016-9704-1>
- Wang, Z., Chen, F., & Fujiyama, T. (2015). Carbon emission from urban passenger transportation in Beijing. *Transportation Research Part D: Transport and Environment*, 41, 217-227. DOI: <https://doi.org/10.1016/j.trd.2015.10.001>

- Wiedmann, T., & Barrett, J. (2010). A review of the ecological footprint indicator—perceptions and methods. *Sustainability*, 2(6), 1645-1693. DOI: [10.3390/su2061645](https://doi.org/10.3390/su2061645)
- Xu, S., & Martin, I. S. (2010). Ecological Footprint for the Twin Cities: Impacts of the Consumption in the 7-County Metro Area. *Minneapolis: Metropolitan Design Centre, College of Design, University of Minnesota*.
- Yigitcanlar, T., & Kamruzzaman, M. (2014). Investigating the interplay between transport, land use and the environment: a review of the literature. *International Journal of Environmental Science and Technology*, 11: 2121. <https://doi.org/10.1007/s13762-014-0691-z>
- Zahabi, S. A. H., Miranda-Moreno, L., Patterson, Z., Barla, P., & Harding, C. (2012). Transportation greenhouse gas emissions and its relationship with urban form, transit accessibility and emerging green technologies: a Montreal case study. *Procedia-Social and Behavioral Sciences*, 54, 966-978. DOI: <https://doi.org/10.1016/j.sbspro.2012.09.812>

Figures

Fig 1: Conceptual design of EBI.

Fig 2: Study Areas, Area of Interest (AOIs)

Fig 3: Vehicle type composition in selected study areas from volume survey data.

Fig 4: CO₂ emission levels from different vehicle types in each AOI.

(a) Carbon dioxide emission tone 6.82/day

(b) Carbon dioxide emission tone 8.57 /day

(c) Carbon dioxide emission tone 11.03 /day

(d) Carbon dioxide emission tone 12.15/day

(e) Carbon dioxide emission tone 12.45/day

Legend

Network Data
carbontond

Coordinate System: WGS 1984 UTM Zone 46N
Projection: Transverse Mercator
Datum: WGS 1984
Units: Meter

Fig 5: Average daily CO₂ emission map for the transport links found within the AOIs

(f) Total carbon dioxide emission 12.84/day

(g) Total carbon dioxide emission 15.46/day

(h) Total carbon dioxide emission 16.23/day

(i) Total carbon dioxide emission 20.53/day

(j) Total carbon dioxide emission 21.20/day

Legend

Network Data carbontond

Coordinate System: WGS 1984 UTM Zone 46N
Projection: Transverse Mercator
Datum: WGS 1984
Units: Meter

Fig 6: Average daily carbon dioxide emission map in different transport links within AOIs

(a); Built-up: 55.8; Vege: 22.5; Water: 0.15 hectare (h)

(b); Built-up: 62.4; Vege: 14.9; Water: 0.94(he)

(c); Built-up: 57.9 Vege: 16.8; Water: 3.7(he)

(d); Built-up: 49.7; Vege: 11.1; Water: 17.6 (he)

(e); Built-up: 67.2; Vege: 11.1; Water: 0.2 (he)

Legend

Land Use Types

- Builtup-Area
- Vegetation
- Waterbody
- Study Area

Coordinate System: WGS 1984 UTM Zone 46N
 Projection: Transverse Mercator
 Datum: WGS 1984
 Units: Meter

Fig 7: Land use classification maps in different AOIs

(f); Built-up: 43.7; Vege: 23.5; Water: 11.2 (he)

(g); Built-up: 71.4; Vege: 6.2; Water: 0.8 (he)

(h); Built-up: 67.2; Vege: 11.1; Water: 0.2 (he)

(i); Built-up: 59.6; Vege: 18.3; Water: 0.57(he)

(j); Built-up: 60.4 Vege: 18.09; Water: 0.00 (he)

Legend

Land Use Types

- Builtup-Area
- Vegetation
- Waterbody
- Study Area

Coordinate System: WGS 1984 UTM Zone 46N
 Projection: Transverse Mercator
 Datum: WGS 1984
 Units: Meter

Fig 8: Land use classification maps in different AOIs

Tables

Table 1: Fuel use type by different vehicle classes in Dhaka, percentage of usage and Emission factors (EFs)

Vehicle Class	Fuel Type	Percentage of Usage ¹	CO ₂ Emission Factor (gm/km) ^{1, 2}
Car	Petrol	13.80%	258
	CNG	86.20%	237
Bus	Diesel	24.20%	887
	CNG	75.80%	968
CNG Auto Rickshaw	CNG	100%	75
Motorcycle	Petrol	100%	40
Microbus/Ambulance	Petrol	6.50%	331
	CNG	85.50%	162
	Diesel	8%	344
Jeep/Station wagon	Petrol	24.70%	331
	CNG	57.80%	363
	Diesel	17.50%	332.5
Taxicab	CNG	100.00%	237
Leguna/Tempo/Human Hauler (Para-transit)	CNG	100.00%	450
Pick up/Minitruck	Diesel	9.00%	500
	CNG	91.00%	450
Truck	Diesel	82.60%	887
	CNG	17.40%	450

Source: (¹Neema and Jahan, 2014, ²Wadud and Khan 2011;)

Table 2: Emission and bio-capacity index classification

Emission bio-capacity index (EBI)	Emission bio-capacity score (EBS)	Descriptor	Color Code
≥ 1.0	1	Bio-capacity is very good and capable of sequestering all CO ₂ emissions in area.	Green
0.67 -1.0	2	Bio-capacity is not adequate to absorb all CO ₂ emissions.	Yellow
0.33 - 0.67	3	Bio-capacity is extremely low in comparison to net CO ₂ emissions.	Orange
< 0.33	4	Bio-capacity is in critically short supply in area and net CO ₂ , emissions are extremely high.	Red

Table 3: Estimated Carbon Uptake land for AOIs

Area	Total tons of CO ₂ in a year ¹	Sequestration (tons CO ₂ /acre/year) ²	Acre to Hectares conversion factor ³	Hectares	Hectares to global hectares conversion factor ⁴	Carbon Uptake Land (C, gha)
	I	II	III	IV= (I/II)*III	V	VI= IV*V
Area I (Mirpur 10)	2,489	1.6175	0.4047	622.83	1.26	784.76
Area II (Mogbazaar)	3,128			782.64		986.13
Area III (Motijheel)	4,025			1007.30		1269.19
Area IV (Gulshan 1)	4,434			1109.58		1398.07
Area V (Shymoli)	4,544			1136.98		1432.59
Area VI (Technical Morh)	4,686			1172.59		1477.47
Area VII (Jatrabari)	5,642			1411.86		1778.94
Area VIII (Mohakhali)	5,923			1482.18		1867.54
Area IX (Science lab)	7,493			1874.87		2362.33
Area X (Farm gate)	7,738			1936.05		2439.43

Source: ¹Field Survey, 2014; ²Ewing et al., (2010); ³Shakil et al. (2014); ⁴Xu and Martin, (2010)

Table 4: Bio-capacity estimation for area I (Mirpur 10)

AOI	Land Class	Area (Hectare) (Ar)		Yield Factor (YF)		Equivalency Factor (EQF) (gha/hectare)		Bio-capacity (gha)
Mirpur 10 (Area I)	Built-Up Land	55.80	×	1.85	×	2.51	=	259.40
	Forestland/ Vegetation	22.58	×	0.35	×	1.26	=	9.99
	Fishing Ground/Water body	0.15	×	1.00	×	0.37	=	0.06
	Total Bio-capacity in Mirpur 10						=	269.44

Table 5: Emission and bio-capacity Index and Score values for each AOI

Area	Carbon Uptake Land (gha)	Bio-capacity Area (gha)	EBI	EBS	Color Code
Area I (Mirpur 10)	785.20	269.43	0.343	3	Orange
Area II (Mog bazaar)	987.08	298.06	0.302	4	Red
Area III (Motijheel)	1269.36	278.20	0.219	4	Red
Area IV (Gulshan 1)	1398.43	242.60	0.173	4	Red
Area V (Shymoli)	1432.89	233.91	0.163	4	Red
Area VI (Technical Morh)	1477.91	217.92	0.147	4	Red
Area VII (Jatrabari)	1779.99	335.08	0.188	4	Red
Area VIII (Mohakhali)	1868.61	317.41	0.170	4	Red
Area IX (Science lab)	2363.18	285.57	0.121	4	Red
Area X (Farm gate)	2440.20	289.00	0.118	4	Red

Supplementary Figures:

Figure 1S: Average Per-capita carbon dioxide emission from different vehicle classes.

Supplementary Tables

Table 1S: Yield Factors for different countries and the world

Yield	Cropland (Also used for built-up)	Forest	Grazing Land	Fishing Ground/ Inland water
World Average	1.0	1.0	1.0	1.0
Algeria	0.3	0.4	0.7	0.9
Bangladesh*	1.85	0.35	1.89	1.0
Germany	2.2	4.1	2.2	3.0
Hungary	1.1	2.6	1.9	0.0
Japan	1.3	1.4	2.2	0.8
Jordan	1.1	1.5	0.4	0.7
New Zealand	0.7	2.0	2.5	1.0
Zambia	0.2	0.2	1.5	0.0

*Bangladesh Yield Factor obtained from Shakil et al., (2014), who obtained Bangladesh specific yield factor via personal email correspondence with Global footprint Network.

Source: Ecological Footprint Atlas 2010 (p, 14), (Global Footprint Network, 2011)

Table 2S: Equivalence Factors

Area Type	Equivalence Factor [Global Hectares per hectare]
Cropland	2.51
Forest	1.26
Grazing Land	0.46
Marine and Inland Water	0.37
Built-Up Land*	2.51

*According to Global Footprint network, Built-Up land assumed to be have similar Equivalence Factor as cropland, the assumption is “built-up land occupies what was previously cropland. Tis assumption is based on the theory that human settlements are generally situated in highly fertile areas”.

Source: Ecological Footprint Atlas 2010 (p, 14), (Global Footprint Network, 2011)

Table 3S: Details of land cover types used for bio-productive area estimation.

Land cover type	Description
Buildings	Residential buildings, Slum areas, Commercial and industrial areas, Other katcha (ie traditional bamboo or similar framed structures), semi-pacca (ie walled but not permanent roofed) and building structures
Infrastructure	Road network, Crossing facilities, Rail road tracks/facilities
Vegetation	Cropland, Grass, Trees, Other Vegetation, Gardens, Parks, Grass Land
Water	River, Permanent open water, Lakes, Ponds, Canals
Vacant	Areas without grass cover, Earth and sand land in-fillings, Construction sites, Developed land, open space, bare and exposed soils

Source: Ahmed & Ahmed, 2012 and Author's Observation of the study areas

Table 4S: Natural break classes (Grey shaded cells) with original classes (using equal intervals). In this case, the natural break class intervals were generated from the computed EBI values for the ten study nodes in the case study sites. Natural breaks method optimize the classification based on the given set of data. *The comparisons of outcomes of EBI of these two approaches give in Table 52S (End of this document).*

Emission bio-capacity index (EBI) [Equal Class]	Emission bio-capacity index (EBI) [Natural Break]	Emission bio-capacity score (EBS)	Descriptor	Color Code
≥ 1.0	≥ 1.0	1	Bio-capacity is very good and capable of sequestering all CO ₂ emissions in area.	Green
0.67 to <1.00	0.34 to <1.00	2	Bio-capacity is not adequate to absorb all CO ₂ emissions.	Yellow
0.33 to <0.67	0.21 to < 0.34	3	Bio-capacity is extremely low in comparison to net CO ₂ emissions.	Orange
< 0.33	<0.21	4	Bio-capacity is in critically short supply in area and net CO ₂ emissions are extremely high.	Red

Table 5S: Vehicular carbon dioxide emission at link M1 in Mirpur 10 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	397	0.5	258	51159.15
	CNG	86.20%	2477	0.5	237	293548.69
Bus	Diesel	24.20%	631	0.5	887	279817.23
	CNG	75.80%	1976	0.5	968	956489.11
CNG Auto Rickshaw	CNG	100.00%	711	0.5	75	26664.00
Motorcycle	Petrol	100.00%	341	0.5	40	6814.13
Microbus/Ambulance	Petrol	6.50%	48	0.5	331	7888.04
	CNG	85.50%	627	0.5	162	50781.92
	Diesel	8.00%	59	0.5	344	10089.66
Jeep/Station wagon	Petrol	24.70%	40	0.5	331	6661.02
	CNG	57.80%	94	0.5	363	17094.25
	Diesel	17.50%	29	0.5	332.5	4740.73
Taxicab	CNG	100.00%	111	0.5	237	13165.35
Leguna/Tempo/Human Hauler	CNG	100.00%	200	0.5	450	44995.50
Pick up/Minitruck	Diesel	9.00%	19	0.5	500	4832.85
	CNG	91.00%	195	0.5	450	43978.94
Truck	Diesel	82.60%	24	0.5	887	10853.17
	CNG	17.40%	5	0.5	450	1159.88
Total	In (gm)					1830733.61
	In (ton)					1.83

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 6S: Vehicular carbon dioxide emission at link M2 in Mirpur 10 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	341	0.50	258	44039.06
	CNG	86.20%	2132	0.50	237	252693.97
Bus	Diesel	24.20%	504	0.50	887	223376.82
	CNG	75.80%	1578	0.50	968	763560.91
CNG Auto Rickshaw	CNG	100.00%	793	0.50	75	29719.25
Motorcycle	Petrol	100.00%	822	0.50	40	16442.80
Microbus/Ambulance	Petrol	6.50%	31	0.50	331	5179.02
	CNG	85.50%	412	0.50	162	33341.67
	Diesel	8.00%	39	0.50	344	6624.52
Jeep/Station wagon	Petrol	24.70%	48	0.50	331	7872.11
	CNG	57.80%	111	0.50	363	20202.29
	Diesel	17.50%	34	0.50	332.5	5602.68
Taxicab	CNG	100.00%	67	0.50	237	7899.21
Leguna/Tempo/Human Hauler	CNG	100.00%	726	0.50	450	163317.00
Pick up/Minitruck	Diesel	9.00%	24	0.50	500	5999.40
	CNG	91.00%	243	0.50	450	54594.54
Truck	Diesel	82.60%	37	0.50	887	16279.75
	CNG	17.40%	8	0.50	450	1739.83
Total	In (gm)					1658484.83
	In (ton)					1.658

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 7S: Vehicular carbon dioxide emission at link M3 in Mirpur 10 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	487	0.51	258	64268.55
	CNG	86.20%	3039	0.51	237	368769.78
Bus	Diesel	24.20%	746	0.51	887	338629.72
	CNG	75.80%	2336	0.51	968	1157525.73
CNG Auto Rickshaw	CNG	100.00%	1007	0.51	75	38680.58
Motorcycle	Petrol	100.00%	1104	0.51	40	22601.59
Microbus/Ambulance	Petrol	6.50%	52	0.51	331	8811.66
	CNG	85.50%	684	0.51	162	56728.02
	Diesel	8.00%	64	0.51	344	11271.06
Jeep/Station wagon	Petrol	24.70%	55	0.51	331	9301.20
	CNG	57.80%	128	0.51	363	23869.78
	Diesel	17.50%	39	0.51	332.5	6619.78
Taxicab	CNG	100.00%	96	0.51	237	11683.81
Leguna/Tempo/Human Hauler	CNG	100.00%	363	0.51	450	83618.30
Pick up/Minitruck	Diesel	9.00%	31	0.51	500	8020.53
	CNG	91.00%	317	0.51	450	72986.83
Truck	Diesel	82.60%	18	0.51	887	8335.23
	CNG	17.40%	4	0.51	450	890.79
Total	In (gm)					2292612.97
	In (ton)					2.2926129

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 8S: Vehicular carbon dioxide emission at link M4 in Mirpur 10 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	193	0.51	258	25368.87
	CNG	86.20%	1207	0.51	237	145851.33
Bus	Diesel	24.20%	294	0.51	887	132716.04
	CNG	75.80%	921	0.51	968	453658.44
CNG Auto Rickshaw	CNG	100.00%	311	0.51	75	11875.48
Motorcycle	Petrol	100.00%	481	0.51	40	9801.98
Microbus/Ambulance	Petrol	6.50%	21	0.51	331	3568.90
	CNG	85.50%	279	0.51	162	22976.00
	Diesel	8.00%	26	0.51	344	4565.01
Jeep/Station wagon	Petrol	24.70%	20	0.51	331	3390.46
	CNG	57.80%	47	0.51	363	8700.97
	Diesel	17.50%	14	0.51	332.5	2413.03
Taxicab	CNG	100.00%	37	0.51	237	4467.44
Leguna/Tempo/Human Hauler	CNG	100.00%	741	0.51	450	169649.70
Pick up/Minitruck	Diesel	9.00%	12	0.51	500	3053.69
	CNG	91.00%	121	0.51	450	27788.62
Truck	Diesel	82.60%	24	0.51	887	11048.52
	CNG	17.40%	5	0.51	450	1180.76
Total	In (gm)					1042075.25
	In (ton)					1.042075255

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 9S: Vehicular carbon dioxide emission at link T1 in Technical morh area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	503	0.50	258	64871.91
	CNG	86.20%	3141	0.50	237	372231.84
Bus	Diesel	24.20%	896	0.50	887	397467.66
	CNG	75.80%	2807	0.50	968	1358649.31
CNG Auto Rickshaw	CNG	100.00%	4540	0.50	75	170260.75
Motorcycle	Petrol	100.00%	2955	0.50	40	59105.20
Microbus/Ambulance	Petrol	6.50%	57	0.50	331	9481.59
	CNG	85.50%	754	0.50	162	61040.90
	Diesel	8.00%	71	0.50	344	12127.97
Jeep/Station wagon	Petrol	24.70%	227	0.50	331	37543.90
	CNG	57.80%	531	0.50	363	96349.39
	Diesel	17.50%	161	0.50	332.5	26720.48
Taxicab	CNG	100.00%	141	0.50	237	16676.11
Leguna/Tempo/Human Hauler	CNG	100.00%	333	0.50	450	74992.50
Pick up/Minitruck	Diesel	9.00%	79	0.50	500	19664.70
	CNG	91.00%	795	0.50	450	178948.77
Truck	Diesel	82.60%	306	0.50	887	135664.58
	CNG	17.40%	64	0.50	450	14498.55
Total	In (gm)					3106296.10
	In (ton)					3.10629609

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 10S: Vehicular carbon dioxide emission at link T2 in Technical morh area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1643	0.51	258	216973.87
	CNG	86.20%	10260	0.51	237	1244985.37
Bus	Diesel	24.20%	477	0.51	887	216527.66
	CNG	75.80%	1493	0.51	968	740148.67
CNG Auto Rickshaw	CNG	100.00%	5199	0.51	75	199660.03
Motorcycle	Petrol	100.00%	3452	0.51	40	70686.86
Microbus/Ambulance	Petrol	6.50%	103	0.51	331	17378.56
	CNG	85.50%	1349	0.51	162	111880.27
	Diesel	8.00%	126	0.51	344	22229.04
Jeep/Station wagon	Petrol	24.70%	263	0.51	331	44645.76
	CNG	57.80%	616	0.51	363	114574.96
	Diesel	17.50%	187	0.51	332.5	31774.96
Taxicab	CNG	100.00%	141	0.51	237	17076.34
Leguna/Tempo/Human Hauler	CNG	100.00%	311	0.51	450	71672.83
Pick up/Minitruck	Diesel	9.00%	59	0.51	500	15017.16
	CNG	91.00%	593	0.51	450	136656.20
Truck	Diesel	82.60%	122	0.51	887	55568.21
	CNG	17.40%	26	0.51	450	5938.61
Total	In (gm)					3333395.35
	In (ton)					3.33339535

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 11S: Vehicular carbon dioxide emission at link T3 in Technical morh area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	2145	0.50	258	276760.45
	CNG	86.20%	13401	0.50	237	1588037.87
Bus	Diesel	24.20%	1373	0.50	887	608920.45
	CNG	75.80%	4301	0.50	968	2081450.74
CNG Auto Rickshaw	CNG	100.00%	8007	0.50	75	300247.75
Motorcycle	Petrol	100.00%	6073	0.50	40	121469.33
Microbus/Ambulance	Petrol	6.50%	170	0.50	331	28205.73
	CNG	85.50%	2242	0.50	162	181583.84
	Diesel	8.00%	210	0.50	344	36078.17
Jeep/Station wagon	Petrol	24.70%	617	0.50	331	102034.64
	CNG	57.80%	1443	0.50	363	261852.77
	Diesel	17.50%	437	0.50	332.5	72619.36
Taxicab	CNG	100.00%	630	0.50	237	74603.65
Leguna/Tempo/Human Hauler	CNG	100.00%	659	0.50	450	148318.50
Pick up/Minitruck	Diesel	9.00%	141	0.50	500	35329.80
	CNG	91.00%	1429	0.50	450	321501.18
Truck	Diesel	82.60%	336	0.50	887	149231.04
	CNG	17.40%	71	0.50	450	15948.41
Total	In (gm)					6404193.68
	In (ton)					6.40419368

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 12S: Vehicular carbon dioxide emission at link S1 in Shymoli area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1889	0.50	258	276760.45
	CNG	86.20%	11799	0.50	237	1588037.87
Bus	Diesel	24.20%	1346	0.50	887	608920.45
	CNG	75.80%	4216	0.50	968	2081450.74
CNG Auto Rickshaw	CNG	100.00%	6622	0.50	75	300247.75
Motorcycle	Petrol	100.00%	6073	0.50	40	121469.33
Microbus/Ambulance	Petrol	6.50%	170	0.50	331	28205.73
	CNG	85.50%	2242	0.50	162	181583.84
	Diesel	8.00%	210	0.50	344	36078.17
Jeep/Station wagon	Petrol	24.70%	617	0.50	331	102034.64
	CNG	57.80%	1443	0.50	363	261852.77
	Diesel	17.50%	437	0.50	332.5	72619.36
Taxicab	CNG	100.00%	630	0.50	237	74603.65
Leguna/Tempo/Human Hauler	CNG	100.00%	659	0.50	450	148318.50
Pick up/Minitruck	Diesel	9.00%	141	0.50	500	35329.80
	CNG	91.00%	1429	0.50	450	321501.18
Truck	Diesel	82.60%	336	0.50	887	149231.04
	CNG	17.40%	71	0.50	450	15948.41
Total	In (gm)					3281351.55
	In (ton)					3.281351545

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 13S: Vehicular carbon dioxide emission at link S2 in Shymoli area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1800	0.23	258	106809.23
	CNG	86.20%	11243	0.23	237	612866.11
Bus	Diesel	24.20%	1445	0.23	887	294730.22
	CNG	75.80%	4525	0.23	968	1007465.63
CNG Auto Rickshaw	CNG	100.00%	9155	0.23	75	157917.54
Motorcycle	Petrol	100.00%	8310	0.23	40	76454.58
Microbus/Ambulance	Petrol	6.50%	193	0.23	331	14697.26
	CNG	85.50%	2539	0.23	162	94618.52
	Diesel	8.00%	238	0.23	344	18799.38
Jeep/Station wagon	Petrol	24.70%	723	0.23	331	55013.93
	CNG	57.80%	1691	0.23	363	141182.93
	Diesel	17.50%	512	0.23	332.5	39154.12
Taxicab	CNG	100.00%	667	0.23	237	36336.37
Leguna/Tempo/Human Hauler	CNG	100.00%	1059	0.23	450	109622.37
Pick up/Minitruck	Diesel	9.00%	122	0.23	500	14028.60
	CNG	91.00%	1233	0.23	450	127660.23
Truck	Diesel	82.60%	251	0.23	887	51172.68
	CNG	17.40%	53	0.23	450	5468.85
Total	In (gm)					2963998.53
	In (ton)					2.963998533

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 14S: Vehicular carbon dioxide emission at link S3 in Shymoli area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1005	0.50	258	129611.97
	CNG	86.20%	6276	0.50	237	743707.11
Bus	Diesel	24.20%	945	0.50	887	418930.91
	CNG	75.80%	2959	0.50	968	1432016.37
CNG Auto Rickshaw	CNG	100.00%	4888	0.50	75	183315.00
Motorcycle	Petrol	100.00%	5585	0.50	40	111692.53
Microbus/Ambulance	Petrol	6.50%	168	0.50	331	27807.35
	CNG	85.50%	2210	0.50	162	179019.10
	Diesel	8.00%	207	0.50	344	35568.59
Jeep/Station wagon	Petrol	24.70%	715	0.50	331	118384.41
	CNG	57.80%	1674	0.50	363	303811.37
	Diesel	17.50%	507	0.50	332.5	84255.69
Taxicab	CNG	100.00%	518	0.50	237	61438.30
Leguna/Tempo/Human Hauler	CNG	100.00%	341	0.50	450	76659.00
Pick up/Minitruck	Diesel	9.00%	86	0.50	500	21497.85
	CNG	91.00%	869	0.50	450	195630.44
Truck	Diesel	82.60%	190	0.50	887	84112.04
	CNG	17.40%	40	0.50	450	8989.10
Total	In (gm)					4216447.13
	In (ton)					4.21644713

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 15S: Vehicular carbon dioxide emission at link S4 in Shymoli area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	480	0.51	258	63086.62
	CNG	86.20%	3001	0.51	237	362699.07
Bus	Diesel	24.20%	498	0.51	887	224969.87
	CNG	75.80%	1561	0.51	968	769006.38
CNG Auto Rickshaw	CNG	100.00%	778	0.51	75	29688.70
Motorcycle	Petrol	100.00%	1215	0.51	40	24731.16
Microbus/Ambulance	Petrol	6.50%	52	0.51	331	8760.03
	CNG	85.50%	684	0.51	162	56395.63
	Diesel	8.00%	64	0.51	344	11205.02
Jeep/Station wagon	Petrol	24.70%	152	0.51	331	25582.54
	CNG	57.80%	355	0.51	363	65652.78
	Diesel	17.50%	108	0.51	332.5	18207.42
Taxicab	CNG	100.00%	89	0.51	237	10721.86
Leguna/Tempo/Human Hauler	CNG	100.00%	748	0.51	450	171346.20
Pick up/Minitruck	Diesel	9.00%	46	0.51	500	11705.83
	CNG	91.00%	465	0.51	450	106523.05
Truck	Diesel	82.60%	61	0.51	887	27621.31
	CNG	17.40%	13	0.51	450	2951.90
Total	In (gm)					1990855.37
	In (ton)					1.99085537

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 16S: Vehicular carbon dioxide emission at link Mk1 in Mohakhali area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1747	0.50	258	225337.60
	CNG	86.20%	10911	0.50	237	1292976.05
Bus	Diesel	24.20%	1217	0.50	887	539761.08
	CNG	75.80%	3812	0.50	968	1845045.76
CNG Auto Rickshaw	CNG	100.00%	5229	0.50	75	196091.50
Motorcycle	Petrol	100.00%	3259	0.50	40	65178.67
Microbus/Ambulance	Petrol	6.50%	59	0.50	331	9800.30
	CNG	85.50%	779	0.50	162	63092.69
	Diesel	8.00%	73	0.50	344	12535.64
Jeep/Station wagon	Petrol	24.70%	161	0.50	331	26644.06
	CNG	57.80%	377	0.50	363	68376.98
	Diesel	17.50%	114	0.50	332.5	18962.92
Taxicab	CNG	100.00%	570	0.50	237	67582.13
Leguna/Tempo/Human Hauler	CNG	100.00%	1067	0.50	450	239976.00
Pick up/Minitruck	Diesel	9.00%	101	0.50	500	25330.80
	CNG	91.00%	1024	0.50	450	230510.28
Truck	Diesel	82.60%	24	0.50	887	10853.17
	CNG	17.40%	5	0.50	450	1159.88
Total	In (gm)					4939215.49
	In (ton)					4.9392154

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 17S: Vehicular carbon dioxide emission at link Mk2 in Mohakhali area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1659	0.51	258	219134.15
	CNG	86.20%	10362	0.51	237	1257381.00
Bus	Diesel	24.20%	1242	0.51	887	564111.54
	CNG	75.80%	3891	0.51	968	1928282.05
CNG Auto Rickshaw	CNG	100.00%	6007	0.51	75	230661.38
Motorcycle	Petrol	100.00%	3992	0.51	40	81760.12
Microbus/Ambulance	Petrol	6.50%	155	0.51	331	26271.81
	CNG	85.50%	2039	0.51	162	169133.55
	Diesel	8.00%	191	0.51	344	33604.47
Jeep/Station wagon	Petrol	24.70%	309	0.51	331	52396.76
	CNG	57.80%	723	0.51	363	134466.45
	Diesel	17.50%	219	0.51	332.5	37291.44
Taxicab	CNG	100.00%	267	0.51	237	32355.16
Leguna/Tempo/Human Hauler	CNG	100.00%	1111	0.51	450	255974.40
Pick up/Minitruck	Diesel	9.00%	114	0.51	500	29181.08
	CNG	91.00%	1153	0.51	450	265547.84
Truck	Diesel	82.60%	49	0.51	887	22227.28
	CNG	17.40%	10	0.51	450	2375.44
Total	In (gm)					5342155.92
	In (ton)					5.34215592

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 18S: Vehicular carbon dioxide emission at link Mk3 in Mohakhali area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	590	0.50	258	76079.46
	CNG	86.20%	3684	0.50	237	436540.19
Bus	Diesel	24.20%	959	0.50	887	425290.39
	CNG	75.80%	3004	0.50	968	1453754.76
CNG Auto Rickshaw	CNG	100.00%	5644	0.50	75	211645.50
Motorcycle	Petrol	100.00%	3437	0.50	40	68733.87
Microbus/Ambulance	Petrol	6.50%	136	0.50	331	22468.98
	CNG	85.50%	1786	0.50	162	144651.53
	Diesel	8.00%	167	0.50	344	28740.24
Jeep/Station wagon	Petrol	24.70%	276	0.50	331	45718.79
	CNG	57.80%	646	0.50	363	117328.69
	Diesel	17.50%	196	0.50	332.5	32538.64
Taxicab	CNG	100.00%	252	0.50	237	29841.46
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.50	450	0.00
Pick up/Minitruck	Diesel	9.00%	173	0.50	500	43162.35
	CNG	91.00%	1746	0.50	450	392777.39
Truck	Diesel	82.60%	110	0.50	887	48839.25
	CNG	17.40%	23	0.50	450	5219.48
Total	In (gm)					3583330.95
	In (ton)					3.58333094

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 19S: Vehicular carbon dioxide emission at link Mk4 in Mohakhali area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1129	0.35	258	101988.67
	CNG	86.20%	7055	0.35	237	585205.95
Bus	Diesel	24.20%	812	0.35	887	252073.99
	CNG	75.80%	2543	0.35	968	861655.39
CNG Auto Rickshaw	CNG	100.00%	3015	0.35	75	79130.98
Motorcycle	Petrol	100.00%	3170	0.35	40	44380.75
Microbus/Ambulance	Petrol	6.50%	81	0.35	331	9425.81
	CNG	85.50%	1070	0.35	162	60681.83
	Diesel	8.00%	100	0.35	344	12056.63
Jeep/Station wagon	Petrol	24.70%	278	0.35	331	32215.09
	CNG	57.80%	651	0.35	363	82673.99
	Diesel	17.50%	197	0.35	332.5	22927.89
Taxicab	CNG	100.00%	96	0.35	237	7986.98
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.35	450	0.00
Pick up/Minitruck	Diesel	9.00%	96	0.35	500	16798.32
	CNG	91.00%	971	0.35	450	152864.71
Truck	Diesel	82.60%	153	0.35	887	47482.60
	CNG	17.40%	32	0.35	450	5074.49
Total	In (gm)					2374624.08
	In (ton)					2.37462407

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 20S: Vehicular carbon dioxide emission at link G1 in Gulshan 1 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1257	0.50	258	162179.78
	CNG	86.20%	7853	0.50	237	930579.60
Bus	Diesel	24.20%	174	0.50	887	77108.73
	CNG	75.80%	545	0.50	968	263577.97
CNG Auto Rickshaw	CNG	100.00%	3289	0.50	75	123321.00
Motorcycle	Petrol	100.00%	1355	0.50	40	27108.40
Microbus/Ambulance	Petrol	6.50%	145	0.50	331	23982.84
	CNG	85.50%	1906	0.50	162	154397.56
	Diesel	8.00%	178	0.50	344	30676.64
Jeep/Station wagon	Petrol	24.70%	295	0.50	331	48746.52
	CNG	57.80%	689	0.50	363	125098.80
	Diesel	17.50%	209	0.50	332.5	34693.52
Taxicab	CNG	100.00%	711	0.50	237	84258.24
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.50	450	0.00
Pick up/Minitruck	Diesel	9.00%	50	0.50	500	12498.75
	CNG	91.00%	506	0.50	450	113738.63
Truck	Diesel	82.60%	61	0.50	887	27132.92
	CNG	17.40%	13	0.50	450	2899.71
Total	In (gm)					2241999.59
	In (ton)					2.24199959

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 21S: Vehicular carbon dioxide emission at link G2 in Gulshan 1 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1332	0.51	258	175928.41
	CNG	86.20%	8319	0.51	237	1009468.54
Bus	Diesel	24.20%	866	0.51	887	393168.65
	CNG	75.80%	2712	0.51	968	1343954.16
CNG Auto Rickshaw	CNG	100.00%	3318	0.51	75	127418.37
Motorcycle	Petrol	100.00%	2940	0.51	40	60220.35
Microbus/Ambulance	Petrol	6.50%	87	0.51	331	14767.69
	CNG	85.50%	1146	0.51	162	95071.96
	Diesel	8.00%	107	0.51	344	18889.47
Jeep/Station wagon	Petrol	24.70%	263	0.51	331	44645.76
	CNG	57.80%	616	0.51	363	114574.96
	Diesel	17.50%	187	0.51	332.5	31774.96
Taxicab	CNG	100.00%	356	0.51	237	43140.22
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.51	450	0.00
Pick up/Minitruck	Diesel	9.00%	81	0.51	500	20819.25
	CNG	91.00%	822	0.51	450	189455.19
Truck	Diesel	82.60%	104	0.51	887	47232.98
	CNG	17.40%	22	0.51	450	5047.82
Total	In (gm)					3735578.72
	In (ton)					3.73557871

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 22S: Vehicular carbon dioxide emission at link G3 in Gulshan 1 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1339	0.50	258	172728.06
	CNG	86.20%	8364	0.50	237	991105.10
Bus	Diesel	24.20%	124	0.50	887	54850.54
	CNG	75.80%	387	0.50	968	187493.60
CNG Auto Rickshaw	CNG	100.00%	3407	0.50	75	127765.00
Motorcycle	Petrol	100.00%	1541	0.50	40	30811.73
Microbus/Ambulance	Petrol	6.50%	143	0.50	331	23584.46
	CNG	85.50%	1874	0.50	162	151832.82
	Diesel	8.00%	175	0.50	344	30167.06
Jeep/Station wagon	Petrol	24.70%	304	0.50	331	50260.39
	CNG	57.80%	711	0.50	363	128983.86
	Diesel	17.50%	215	0.50	332.5	35770.96
Taxicab	CNG	100.00%	933	0.50	237	110588.94
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.50	450	0.00
Pick up/Minitruck	Diesel	9.00%	75	0.50	500	18664.80
	CNG	91.00%	755	0.50	450	169849.68
Truck	Diesel	82.60%	86	0.50	887	37986.08
	CNG	17.40%	18	0.50	450	4059.59
Total	In (gm)					2326502.66
	In (ton)					2.32650266

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 23S: Vehicular carbon dioxide emission at link G4 in Gulshan 1 area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1360	0.51	258	178655.93
	CNG	86.20%	8498	0.51	237	1027132.91
Bus	Diesel	24.20%	896	0.51	887	404622.07
	CNG	75.80%	2807	0.51	968	1383104.99
CNG Auto Rickshaw	CNG	100.00%	3266	0.51	75	124692.53
Motorcycle	Petrol	100.00%	3126	0.51	40	63637.49
Microbus/Ambulance	Petrol	6.50%	88	0.51	331	14843.39
	CNG	85.50%	1159	0.51	162	95559.27
	Diesel	8.00%	108	0.51	344	18986.29
Jeep/Station wagon	Petrol	24.70%	311	0.51	331	52397.97
	CNG	57.80%	728	0.51	363	134469.55
	Diesel	17.50%	220	0.51	332.5	37292.30
Taxicab	CNG	100.00%	437	0.51	237	52715.82
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.51	450	0.00
Pick up/Minitruck	Diesel	9.00%	81	0.51	500	20697.26
	CNG	91.00%	822	0.51	450	188345.10
Truck	Diesel	82.60%	104	0.51	887	46956.22
	CNG	17.40%	22	0.51	450	5018.24
Total	In (gm)					3849127.33
	In (ton)					3.84912732

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 24S: Vehicular carbon dioxide emission at link F1 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	2157	0.45	258	250389.76
	CNG	86.20%	13471	0.45	237	1436724.11
Bus	Diesel	24.20%	1074	0.45	887	428549.63
	CNG	75.80%	3363	0.45	968	1464895.68
CNG Auto Rickshaw	CNG	100.00%	6984	0.45	75	235726.43
Motorcycle	Petrol	100.00%	4548	0.45	40	81858.48
Microbus/Ambulance	Petrol	6.50%	153	0.45	331	22731.91
	CNG	85.50%	2007	0.45	162	146344.26
	Diesel	8.00%	188	0.45	344	29076.56
Jeep/Station wagon	Petrol	24.70%	578	0.45	331	86108.76
	CNG	57.80%	1353	0.45	363	220981.98
	Diesel	17.50%	410	0.45	332.5	61284.70
Taxicab	CNG	100.00%	281	0.45	237	30017.00
Leguna/Tempo/Human Hauler	CNG	100.00%	333	0.45	450	67493.25
Pick up/Minitruck	Diesel	9.00%	105	0.45	500	23547.65
	CNG	91.00%	1058	0.45	450	214283.57
Truck	Diesel	82.60%	202	0.45	887	80584.76
	CNG	17.40%	43	0.45	450	8612.14
Total	In (gm)					4889210.63
	In (ton)					4.88921062

Source: ¹Jahan, 2013

²Field Survey, 2014

³ Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 25S: Vehicular carbon dioxide emission at link F2 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1369	0.46	258	162427.66
	CNG	86.20%	8549	0.46	237	932001.95
Bus	Diesel	24.20%	1545	0.46	887	630415.50
	CNG	75.80%	4839	0.46	968	2154926.49
CNG Auto Rickshaw	CNG	100.00%	3044	0.46	75	105022.83
Motorcycle	Petrol	100.00%	3889	0.46	40	71548.40
Microbus/Ambulance	Petrol	6.50%	215	0.46	331	32766.46
	CNG	85.50%	2831	0.46	162	210945.02
	Diesel	8.00%	265	0.46	344	41911.83
Jeep/Station wagon	Petrol	24.70%	276	0.46	331	42061.28
	CNG	57.80%	646	0.46	363	107942.39
	Diesel	17.50%	196	0.46	332.5	29935.55
Taxicab	CNG	100.00%	637	0.46	237	69442.83
Leguna/Tempo/Human Hauler	CNG	100.00%	741	0.46	450	153318.00
Pick up/Minitruck	Diesel	9.00%	55	0.46	500	12725.39
	CNG	91.00%	559	0.46	450	115801.09
Truck	Diesel	82.60%	80	0.46	887	32450.97
	CNG	17.40%	17	0.46	450	3468.05
Total	In (gm)					4909111.71
	In (ton)					4.90911170

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 26S: Vehicular carbon dioxide emission at link F3 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	520	0.44	258	59059.81
	CNG	86.20%	3250	0.44	237	338882.29
Bus	Diesel	24.20%	830	0.44	887	323888.44
	CNG	75.80%	2599	0.44	968	1107136.15
CNG Auto Rickshaw	CNG	100.00%	1770	0.44	75	58416.38
Motorcycle	Petrol	100.00%	1318	0.44	40	23203.61
Microbus/Ambulance	Petrol	6.50%	96	0.44	331	13953.07
	CNG	85.50%	1260	0.44	162	89827.58
	Diesel	8.00%	118	0.44	344	17847.48
Jeep/Station wagon	Petrol	24.70%	267	0.44	331	38900.33
	CNG	57.80%	625	0.44	363	99830.40
	Diesel	17.50%	189	0.44	332.5	27685.86
Taxicab	CNG	100.00%	437	0.44	237	45569.66
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.44	450	0.00
Pick up/Minitruck	Diesel	9.00%	68	0.44	500	14958.50
	CNG	91.00%	687	0.44	450	136122.39
Truck	Diesel	82.60%	135	0.44	887	52529.33
	CNG	17.40%	28	0.44	450	5613.84
Total	In (gm)					2453425.11
	In (ton)					2.45342511

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 27S: Vehicular carbon dioxide emission at link F4 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	399	0.43	258	44223.66
	CNG	86.20%	2490	0.43	237	253753.17
Bus	Diesel	24.20%	0	0.43	887	0.00
	CNG	75.80%	0	0.43	968	0.00
CNG Auto Rickshaw	CNG	100.00%	1355	0.43	75	43712.30
Motorcycle	Petrol	100.00%	978	0.43	40	16816.10
Microbus/Ambulance	Petrol	6.50%	59	0.43	331	8428.26
	CNG	85.50%	779	0.43	162	54259.71
	Diesel	8.00%	73	0.43	344	10780.65
Jeep/Station wagon	Petrol	24.70%	185	0.43	331	26298.90
	CNG	57.80%	432	0.43	363	67491.19
	Diesel	17.50%	131	0.43	332.5	18717.26
Taxicab	CNG	100.00%	385	0.43	237	39250.30
Leguna/Tempo/Human Hauler	CNG	100.00%	837	0.43	450	161950.47
Pick up/Minitruck	Diesel	9.00%	38	0.43	500	8169.18
	CNG	91.00%	384	0.43	450	74339.57
Truck	Diesel	82.60%	31	0.43	887	11667.15
	CNG	17.40%	6	0.43	450	1246.88
Total	In (gm)					841104.73
	In (ton)					0.84110473

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 28S: Vehicular carbon dioxide emission at link F5 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	2435	0.56	258	351763.99
	CNG	86.20%	15208	0.56	237	2018404.45
Bus	Diesel	24.20%	1321	0.56	887	656171.41
	CNG	75.80%	4138	0.56	968	2242966.97
CNG Auto Rickshaw	CNG	100.00%	8355	0.56	75	350898.24
Motorcycle	Petrol	100.00%	5518	0.56	40	123602.45
Microbus/Ambulance	Petrol	6.50%	182	0.56	331	33821.38
	CNG	85.50%	2400	0.56	162	217736.46
	Diesel	8.00%	225	0.56	344	43261.19
Jeep/Station wagon	Petrol	24.70%	679	0.56	331	125808.41
	CNG	57.80%	1588	0.56	363	322863.69
	Diesel	17.50%	410	0.56	332.5	76265.41
Taxicab	CNG	100.00%	407	0.56	237	54065.70
Leguna/Tempo/Human Hauler	CNG	100.00%	474	0.56	450	119454.72
Pick up/Minitruck	Diesel	9.00%	134	0.56	500	37516.25
	CNG	91.00%	1355	0.56	450	341397.86
Truck	Diesel	82.60%	275	0.56	887	136749.90
	CNG	17.40%	58	0.56	450	14614.54
Total	In (gm)					7267363.02
	In (ton)					7.26736302

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 29S: Vehicular carbon dioxide emission at link F6 in Farmgate area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	306	0.57	258	44943.58
	CNG	86.20%	1909	0.57	237	257884.03
Bus	Diesel	24.20%		0.57	887	0.00
	CNG	75.80%		0.57	968	0.00
CNG Auto Rickshaw	CNG	100.00%	3044	0.57	75	130136.99
Motorcycle	Petrol	100.00%	3889	0.57	40	88657.80
Microbus/Ambulance	Petrol	6.50%	37	0.57	331	6994.07
	CNG	85.50%	488	0.57	162	45026.64
	Diesel	8.00%	46	0.57	344	8946.16
Jeep/Station wagon	Petrol	24.70%	77	0.57	331	14496.79
	CNG	57.80%	180	0.57	363	37203.30
	Diesel	17.50%	54	0.57	332.5	10317.55
Taxicab	CNG	100.00%	81	0.57	237	11006.23
Leguna/Tempo/Human Hauler	CNG	100.00%	481	0.57	450	123487.65
Pick up/Minitruck	Diesel	9.00%	19	0.57	500	5319.47
	CNG	91.00%	189	0.57	450	48407.16
Truck	Diesel	82.60%	24	0.57	887	12372.61
	CNG	17.40%	5	0.57	450	1322.27
Total	In (gm)					846522.29
	In (ton)					0.84652228

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 30S: Vehicular carbon dioxide emission at link Mb1 in Mogbazar area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	298	0.50	258	38468.25
	CNG	86.20%	1863	0.50	237	220728.94
Bus	Diesel	24.20%	844	0.50	887	374414.53
	CNG	75.80%	2644	0.50	968	1279847.65
CNG Auto Rickshaw	CNG	100.00%	928	0.50	75	34788.19
Motorcycle	Petrol	100.00%	1017	0.50	40	20331.30
Microbus/Ambulance	Petrol	6.50%	35	0.50	331	5736.76
	CNG	85.50%	456	0.50	162	36932.31
	Diesel	8.00%	43	0.50	344	7337.93
Jeep/Station wagon	Petrol	24.70%	11	0.50	331	1816.64
	CNG	57.80%	26	0.50	363	4662.07
	Diesel	17.50%	8	0.50	332.5	1292.93
Taxicab	CNG	100.00%	189	0.50	237	22381.10
Leguna/Tempo/Human Hauler	CNG	100.00%	939	0.50	450	211228.88
Pick up/Minitruck	Diesel	9.00%	13	0.50	500	3249.68
	CNG	91.00%	131	0.50	450	29572.04
Truck	Diesel	82.60%	28	0.50	887	12209.81
	CNG	17.40%	6	0.50	450	1304.87
Total	In (gm)					2306303.86
	In (ton)					2.30630386

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 31S: Vehicular carbon dioxide emission at link Mb2 in Mogbazar area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	149	0.50	258	19283.57
	CNG	86.20%	934	0.50	237	110648.18
Bus	Diesel	24.20%	176	0.50	887	78102.39
	CNG	75.80%	552	0.50	968	266974.59
CNG Auto Rickshaw	CNG	100.00%	578	0.50	75	21664.50
Motorcycle	Petrol	100.00%	905	0.50	40	18109.30
Microbus/Ambulance	Petrol	6.50%	32	0.50	331	5258.70
	CNG	85.50%	418	0.50	162	33854.61
	Diesel	8.00%	39	0.50	344	6726.44
Jeep/Station wagon	Petrol	24.70%	16	0.50	331	2724.96
	CNG	57.80%	39	0.50	363	6993.10
	Diesel	17.50%	12	0.50	332.5	1939.39
Taxicab	CNG	100.00%	228	0.50	237	26988.97
Leguna/Tempo/Human Hauler	CNG	100.00%	22	0.50	450	4999.50
Pick up/Minitruck	Diesel	9.00%	28	0.50	500	6999.30
	CNG	91.00%	283	0.50	450	63693.63
Truck	Diesel	82.60%	9	0.50	887	4069.94
	CNG	17.40%	2	0.50	450	434.96
Total	In (gm)					679466.03
	In (ton)					0.67946603

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 32S: Vehicular carbon dioxide emission at link Mb3 in Mogbazar area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	610	0.52	258	82180.05
	CNG	86.20%	3812	0.52	237	471545.11
Bus	Diesel	24.20%	778	0.52	887	360389.49
	CNG	75.80%	2438	0.52	968	1231906.35
CNG Auto Rickshaw	CNG	100.00%	1539	0.52	75	60241.48
Motorcycle	Petrol	100.00%	2011	0.52	40	41987.80
Microbus/Ambulance	Petrol	6.50%	56	0.52	331	9607.64
	CNG	85.50%	731	0.52	162	61852.38
	Diesel	8.00%	68	0.52	344	12289.20
Jeep/Station wagon	Petrol	24.70%	16	0.52	331	2844.86
	CNG	57.80%	39	0.52	363	7300.80
	Diesel	17.50%	12	0.52	332.5	2024.72
Taxicab	CNG	100.00%	300	0.52	237	37110.49
Leguna/Tempo/Human Hauler	CNG	100.00%	1250	0.52	450	293595.64
Pick up/Minitruck	Diesel	9.00%	26	0.52	500	6785.32
	CNG	91.00%	263	0.52	450	61746.42
Truck	Diesel	82.60%	0	0.52	887	0.00
	CNG	17.40%	0	0.52	450	0.00
Total	In (gm)					2743407.75
	In (ton)					2.74340775

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 33S: Vehicular carbon dioxide emission at link Mb4 in Mogbazar area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	360	0.53	258	49267.05
	CNG	86.20%	2251	0.53	237	282691.92
Bus	Diesel	24.20%	859	0.53	887	403831.11
	CNG	75.80%	2691	0.53	968	1380401.28
CNG Auto Rickshaw	CNG	100.00%	1583	0.53	75	62931.21
Motorcycle	Petrol	100.00%	967	0.53	40	20491.28
Microbus/Ambulance	Petrol	6.50%	32	0.53	331	5700.90
	CNG	85.50%	427	0.53	162	36701.48
	Diesel	8.00%	40	0.53	344	7292.07
Jeep/Station wagon	Petrol	24.70%	10	0.53	331	1684.93
	CNG	57.80%	22	0.53	363	4324.07
	Diesel	17.50%	7	0.53	332.5	1199.19
Taxicab	CNG	100.00%	594	0.53	237	74660.70
Leguna/Tempo/Human Hauler	CNG	100.00%	1428	0.53	450	340490.95
Pick up/Minitruck	Diesel	9.00%	56	0.53	500	14971.00
	CNG	91.00%	571	0.53	450	136236.13
Truck	Diesel	82.60%	50	0.53	887	23727.74
	CNG	17.40%	11	0.53	450	2535.80
Total	In (gm)					2849138.82
	In (ton)					2.84913881

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 34S: Vehicular carbon dioxide emission at link Sc1 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	2309	0.50	258	297857.01
	CNG	86.20%	14423	0.50	237	1709088.87
Bus	Diesel	24.20%	1334	0.50	887	591431.87
	CNG	75.80%	4177	0.50	968	2021670.17
CNG Auto Rickshaw	CNG	100.00%	8584	0.50	75	321912.25
Motorcycle	Petrol	100.00%	7984	0.50	40	159687.73
Microbus/Ambulance	Petrol	6.50%	267	0.50	331	44141.18
	CNG	85.50%	3508	0.50	162	284173.58
	Diesel	8.00%	328	0.50	344	56461.32
Jeep/Station wagon	Petrol	24.70%	869	0.50	331	143817.38
	CNG	57.80%	2034	0.50	363	369080.31
	Diesel	17.50%	616	0.50	332.5	102356.66
Taxicab	CNG	100.00%	1570	0.50	237	186070.28
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.50	450	0.00
Pick up/Minitruck	Diesel	9.00%	88	0.50	500	21997.80
	CNG	91.00%	890	0.50	450	200179.98
Truck	Diesel	82.60%	214	0.50	887	94965.21
	CNG	17.40%	45	0.50	450	10148.99
Total	In (gm)					6615040.58
	In (ton)					6.615040583

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 35S: Vehicular carbon dioxide emission at link Sc2 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1003	0.48	258	124174.33
	CNG	86.20%	6263	0.48	237	712506.21
Bus	Diesel	24.20%	821	0.48	887	349517.16
	CNG	75.80%	2571	0.48	968	1194741.85
CNG Auto Rickshaw	CNG	100.00%	2615	0.48	75	94123.92
Motorcycle	Petrol	100.00%	2407	0.48	40	46217.60
Microbus/Ambulance	Petrol	6.50%	139	0.48	331	22105.65
	CNG	85.50%	1830	0.48	162	142312.49
	Diesel	8.00%	171	0.48	344	28275.50
Jeep/Station wagon	Petrol	24.70%	412	0.48	331	65399.06
	CNG	57.80%	963	0.48	363	167834.41
	Diesel	17.50%	292	0.48	332.5	46545.35
Taxicab	CNG	100.00%	770	0.48	237	87628.57
Leguna/Tempo/Human Hauler	CNG	100.00%	363	0.48	450	78392.16
Pick up/Minitruck	Diesel	9.00%	50	0.48	500	11998.80
	CNG	91.00%	506	0.48	450	109189.08
Truck	Diesel	82.60%	128	0.48	887	54699.96
	CNG	17.40%	27	0.48	450	5845.82
Total	In (gm)					6615040.58
	In (ton)					6.615040583

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 36S: Vehicular carbon dioxide emission at link Sc3 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	2435	0.50	258	314074.99
	CNG	86.20%	15208	0.50	237	1802146.83
Bus	Diesel	24.20%	1267	0.50	887	562019.27
	CNG	75.80%	3969	0.50	968	1921130.12
CNG Auto Rickshaw	CNG	100.00%	8355	0.50	75	313302.00
Motorcycle	Petrol	100.00%	5296	0.50	40	105915.33
Microbus/Ambulance	Petrol	6.50%	182	0.50	331	30197.67
	CNG	85.50%	2400	0.50	162	194407.56
	Diesel	8.00%	225	0.50	344	38626.06
Jeep/Station wagon	Petrol	24.70%	679	0.50	331	112328.94
	CNG	57.80%	1588	0.50	363	288271.15
	Diesel	17.50%	481	0.50	332.5	79945.94
Taxicab	CNG	100.00%	407	0.50	237	48272.95
Leguna/Tempo/Human Hauler	CNG	100.00%	474	0.50	450	106656.00
Pick up/Minitruck	Diesel	9.00%	134	0.50	500	33496.65
	CNG	91.00%	1355	0.50	450	304819.52
Truck	Diesel	82.60%	220	0.50	887	97678.50
	CNG	17.40%	46	0.50	450	10438.96
Total	In (gm)					6363728.42
	In (ton)					6.363728425

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 37S: Vehicular carbon dioxide emission at link Sc4 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	661	0.50	258	85309.20
	CNG	86.20%	4131	0.50	237	489500.00
Bus	Diesel	24.20%	672	0.50	887	298100.74
	CNG	75.80%	2105	0.50	968	1018986.98
CNG Auto Rickshaw	CNG	100.00%	1963	0.50	75	73603.75
Motorcycle	Petrol	100.00%	2111	0.50	40	42218.00
Microbus/Ambulance	Petrol	6.50%	112	0.50	331	18564.79
	CNG	85.50%	1476	0.50	162	119517.05
	Diesel	8.00%	138	0.50	344	23746.37
Jeep/Station wagon	Petrol	24.70%	331	0.50	331	54801.99
	CNG	57.80%	775	0.50	363	140639.02
	Diesel	17.50%	235	0.50	332.5	39003.28
Taxicab	CNG	100.00%	800	0.50	237	94790.52
Leguna/Tempo/Human Hauler	CNG	100.00%	563	0.50	450	126654.00
Pick up/Minitruck	Diesel	9.00%	43	0.50	500	10832.25
	CNG	91.00%	438	0.50	450	98573.48
Truck	Diesel	82.60%	61	0.50	887	27132.92
	CNG	17.40%	13	0.50	450	2899.71
Total	In (gm)					2764874.04
	In (ton)					2.764874039

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 38S: Vehicular carbon dioxide emission at link Sc5 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	362	0.36	258	33606.81
	CNG	86.20%	2260	0.36	237	192834.25
Bus	Diesel	24.20%	0	0.36	887	0.00
	CNG	75.80%	0	0.36	968	0.00
CNG Auto Rickshaw	CNG	100.00%	2563	0.36	75	69193.08
Motorcycle	Petrol	100.00%	1955	0.36	40	28157.18
Microbus/Ambulance	Petrol	6.50%	82	0.36	331	9752.49
	CNG	85.50%	1077	0.36	162	62784.92
	Diesel	8.00%	101	0.36	344	12474.49
Jeep/Station wagon	Petrol	24.70%	243	0.36	331	28993.58
	CNG	57.80%	569	0.36	363	74406.59
	Diesel	17.50%	616	0.36	332.5	73696.80
Taxicab	CNG	100.00%	311	0.36	237	26541.35
Leguna/Tempo/Human Hauler	CNG	100.00%	563	0.36	450	91190.88
Pick up/Minitruck	Diesel	9.00%	33	0.36	500	5879.41
	CNG	91.00%	330	0.36	450	53502.65
Truck	Diesel	82.60%	0	0.36	887	0.00
	CNG	17.40%	0	0.36	450	0.00
Total	In (gm)					763014.48
	In (ton)					0.763014484

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 39S: Vehicular carbon dioxide emission at link Sc6 in Science lab area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	278	0.60	258	43036.98
	CNG	86.20%	1737	0.60	237	246944.05
Bus	Diesel	24.20%		0.60	887	0.00
	CNG	75.80%		0.60	968	0.00
CNG Auto Rickshaw	CNG	100.00%	2615	0.60	75	117654.90
Motorcycle	Petrol	100.00%	2407	0.60	40	57772.00
Microbus/Ambulance	Petrol	6.50%	37	0.60	331	7362.17
	CNG	85.50%	488	0.60	162	47396.46
	Diesel	8.00%	46	0.60	344	9417.01
Jeep/Station wagon	Petrol	24.70%	77	0.60	331	15259.78
	CNG	57.80%	180	0.60	363	39161.36
	Diesel	17.50%	54	0.60	332.5	10860.58
Taxicab	CNG	100.00%	81	0.60	237	11585.51
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.60	450	0.00
Pick up/Minitruck	Diesel	9.00%	27	0.60	500	8199.18
	CNG	91.00%	276	0.60	450	74612.54
Truck	Diesel	82.60%	0	0.60	887	0.00
	CNG	17.40%	0	0.60	450	0.00
Total	In (gm)					689262.52
	In (ton)					0.689262525

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 40S: Vehicular carbon dioxide emission at link Mt1 in Motijheel area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	737	0.50	258	95132.29
	CNG	86.20%	4606	0.50	237	545864.37
Bus	Diesel	24.20%	993	0.50	887	440592.90
	CNG	75.80%	3112	0.50	968	1506062.76
CNG Auto Rickshaw	CNG	100.00%	2433	0.50	75	91240.88
Motorcycle	Petrol	100.00%	2044	0.50	40	40884.80
Microbus/Ambulance	Petrol	6.50%	78	0.50	331	12967.47
	CNG	85.50%	1031	0.50	162	83482.40
	Diesel	8.00%	96	0.50	344	16586.79
Jeep/Station wagon	Petrol	24.70%	25	0.50	331	4087.44
	CNG	57.80%	58	0.50	363	10489.65
	Diesel	17.50%	17	0.50	332.5	2909.08
Taxicab	CNG	100.00%	467	0.50	237	55294.47
Leguna/Tempo/Human Hauler	CNG	100.00%	44	0.50	450	9999.00
Pick up/Minitruck	Diesel	9.00%	36	0.50	500	8999.10
	CNG	91.00%	364	0.50	450	81891.81
Truck	Diesel	82.60%	161	0.50	887	71223.90
	CNG	17.40%	34	0.50	450	7611.74
Total	In (gm)					3085320.84
	In (ton)					3.085320843

Source: ¹Jahan, 2013

²Field Survey, 2014

³ Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 41S: Vehicular carbon dioxide emission at link Mt2 in Motijheel area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	1238	0.50	258	159707.53
	CNG	86.20%	7733	0.50	237	916393.93
Bus	Diesel	24.20%	1281	0.50	887	568180.02
	CNG	75.80%	4013	0.50	968	1942189.18
CNG Auto Rickshaw	CNG	100.00%	2894	0.50	75	108530.81
Motorcycle	Petrol	100.00%	2072	0.50	40	41440.30
Microbus/Ambulance	Petrol	6.50%	132	0.50	331	21811.64
	CNG	85.50%	1734	0.50	162	140419.71
	Diesel	8.00%	162	0.50	344	27899.43
Jeep/Station wagon	Petrol	24.70%	10	0.50	331	1589.56
	CNG	57.80%	22	0.50	363	4079.31
	Diesel	17.50%	7	0.50	332.5	1131.31
Taxicab	CNG	100.00%	489	0.50	237	57927.54
Leguna/Tempo/Human Hauler	CNG	100.00%	33	0.50	450	7499.25
Pick up/Minitruck	Diesel	9.00%	33	0.50	500	8249.18
	CNG	91.00%	334	0.50	450	75067.49
Truck	Diesel	82.60%	37	0.50	887	16279.75
	CNG	17.40%	8	0.50	450	1739.83
Total	In (gm)					4100135.76
	In (ton)					4.100135763

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 42S: Vehicular carbon dioxide emission at link Mt3 in Motijheel area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	978	0.51	258	129212.19
	CNG	86.20%	6110	0.51	237	741413.19
Bus	Diesel	24.20%	1222	0.51	887	554953.88
	CNG	75.80%	3828	0.51	968	1896978.77
CNG Auto Rickshaw	CNG	100.00%	2305	0.51	75	88524.48
Motorcycle	Petrol	100.00%	1878	0.51	40	38453.04
Microbus/Ambulance	Petrol	6.50%	69	0.51	331	11748.88
	CNG	85.50%	912	0.51	162	75637.36
	Diesel	8.00%	85	0.51	344	15028.09
Jeep/Station wagon	Petrol	24.70%	8	0.51	331	1395.18
	CNG	57.80%	19	0.51	363	3580.47
	Diesel	17.50%	6	0.51	332.5	992.97
Taxicab	CNG	100.00%	739	0.51	237	89650.77
Leguna/Tempo/Human Hauler	CNG	100.00%	44	0.51	450	10238.98
Pick up/Minitruck	Diesel	9.00%	63	0.51	500	16126.39
	CNG	91.00%	637	0.51	450	146750.12
Truck	Diesel	82.60%	50	0.51	887	22921.89
	CNG	17.40%	11	0.51	450	2449.68
Total	In (gm)					3846056.32
	In (ton)					3.846056324

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 43S: Vehicular carbon dioxide emission at link J1 in Jatrabari area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	346	0.50	258	44698.33
	CNG	86.20%	2164	0.50	237	256476.82
Bus	Diesel	24.20%	1423	0.50	887	631178.64
	CNG	75.80%	4458	0.50	968	2157535.10
CNG Auto Rickshaw	CNG	100.00%	1992	0.50	75	74714.75
Motorcycle	Petrol	100.00%	3859	0.50	40	77177.47
Microbus/Ambulance	Petrol	6.50%	91	0.50	331	15138.67
	CNG	85.50%	1203	0.50	162	97460.25
	Diesel	8.00%	113	0.50	344	19363.99
Jeep/Station wagon	Petrol	24.70%	234	0.50	331	38755.00
	CNG	57.80%	548	0.50	363	99457.43
	Diesel	17.50%	166	0.50	332.5	27582.43
Taxicab	CNG	100.00%	644	0.50	237	76359.03
Leguna/Tempo/Human Hauler	CNG	100.00%	163	0.50	450	36663.00
Pick up/Minitruck	Diesel	9.00%	266	0.50	500	66493.35
	CNG	91.00%	2689	0.50	450	605089.49
Truck	Diesel	82.60%	1383	0.50	887	613203.90
	CNG	17.40%	291	0.50	450	65533.45
Total	In (gm)					5002881.08
	In (ton)					5.002881084

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 44S: Vehicular carbon dioxide emission at link J2 in Jatrabari area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	346	0.51	258	45771.09
	CNG	86.20%	2164	0.51	237	262632.26
Bus	Diesel	24.20%	1423	0.51	887	646326.93
	CNG	75.80%	4458	0.51	968	2209315.94
CNG Auto Rickshaw	CNG	100.00%	1992	0.51	75	76507.90
Motorcycle	Petrol	100.00%	3859	0.51	40	79029.73
Microbus/Ambulance	Petrol	6.50%	91	0.51	331	15502.00
	CNG	85.50%	1203	0.51	162	99799.30
	Diesel	8.00%	113	0.51	344	19828.73
Jeep/Station wagon	Petrol	24.70%	234	0.51	331	39685.12
	CNG	57.80%	548	0.51	363	101844.41
	Diesel	17.50%	166	0.51	332.5	28244.40
Taxicab	CNG	100.00%	644	0.51	237	78191.65
Leguna/Tempo/Human Hauler	CNG	100.00%	163	0.51	450	37542.91
Pick up/Minitruck	Diesel	9.00%	266	0.51	500	68089.19
	CNG	91.00%	2689	0.51	450	619611.63
Truck	Diesel	82.60%	1383	0.51	887	627920.80
	CNG	17.40%	291	0.51	450	67106.25
Total	In (gm)					5122950.23
	In (ton)					5.12295023

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 45S: Vehicular carbon dioxide emission at link J3 in Jatrabari area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	248	0.50	258	32040.40
	CNG	86.20%	1551	0.50	237	183846.21
Bus	Diesel	24.20%	850	0.50	887	376799.34
	CNG	75.80%	2661	0.50	968	1287999.54
CNG Auto Rickshaw	CNG	100.00%	674	0.50	75	25275.25
Motorcycle	Petrol	100.00%	1304	0.50	40	26071.47
Microbus/Ambulance	Petrol	6.50%	60	0.50	331	9959.65
	CNG	85.50%	792	0.50	162	64118.59
	Diesel	8.00%	74	0.50	344	12739.47
Jeep/Station wagon	Petrol	24.70%	190	0.50	331	31488.44
	CNG	57.80%	445	0.50	363	80809.16
	Diesel	17.50%	135	0.50	332.5	22410.72
Taxicab	CNG	100.00%	170	0.50	237	20186.87
Leguna/Tempo/Human Hauler	CNG	100.00%	0	0.50	450	0.00
Pick up/Minitruck	Diesel	9.00%	91	0.50	500	22831.05
	CNG	91.00%	923	0.50	450	207762.56
Truck	Diesel	82.60%	746	0.50	887	331021.58
	CNG	17.40%	157	0.50	450	35376.46
Total	In (gm)					2770736.75
	In (ton)					2.770736747

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 46S: Vehicular carbon dioxide emission at link J4 in Jatrabari area

Vehicle Type	Fuel Type	% according to Source [1]	Number of Vehicles (AADT) [2]	Length (L)	CO ₂ Emission Factor (EF _{jk}) gm/km [3]	Total CO ₂ Emission, gm AADT*L*EF _{jk}
Car	Petrol	13.80%	310	0.51	258	40670.73
	CNG	86.20%	1935	0.06	237	27050.36
Bus	Diesel	24.20%	665	0.51	887	300229.58
	CNG	75.80%	2083	0.51	968	1026263.91
CNG Auto Rickshaw	CNG	100.00%	941	0.51	75	35909.19
Motorcycle	Petrol	100.00%	2585	0.51	40	52629.11
Microbus/Ambulance	Petrol	6.50%	33	0.51	331	5596.69
	CNG	85.50%	437	0.51	162	36030.54
	Diesel	8.00%	41	0.51	344	7158.76
Jeep/Station wagon	Petrol	24.70%	154	0.51	331	25890.76
	CNG	57.80%	360	0.51	363	66443.78
	Diesel	17.50%	109	0.51	332.5	18426.78
Taxicab	CNG	100.00%	311	0.51	237	37526.51
Leguna/Tempo/Human Hauler	CNG	100.00%	889	0.51	450	203579.64
Pick up/Minitruck	Diesel	9.00%	104	0.51	500	26465.35
	CNG	91.00%	1051	0.51	450	240834.71
Truck	Diesel	82.60%	844	0.51	887	381174.06
	CNG	17.40%	178	0.51	450	40736.29
Total	In (gm)					2572616.76
	In (ton)					2.572616757

Source: ¹Jahan, 2013

²Field Survey, 2014

³Wadud and Khan (2011); Neema and Jahan, (2014); Labib et al., (2013)

Table 47S: Total CO₂ emissions for each AOI

AOI	Tons CO₂/Day	Tons CO₂/Year
Area I (Mirpur 10)	6.82	2,489.30
Area II (Mog bazaar)	8.57	3,128.05
Area III (Motijheel)	11.03	4,025.95
Area IV (Gulshan 1)	12.15	4,434.75
Area V (Shymoli)	12.45	4,544.25
Area VI (Technical Morh)	12.84	4,686.60
Area VII (Jatrabari)	15.46	5,642.90
Area VIII (Mohakhali)	16.23	5,923.95
Area IX (Science lab)	20.53	7,493.45
Area X (Farm gate)	21.20	7,738.00
Total	137.28	50,107.20

Table 48S: Accuracy Test points, with GPS coordinate values for UTM zone 46 N for the study areas

Area	Land cover types	Easting	Northing
Technical Morh	Road	230150.0330	2632668.9530
	Water	230476.6620	2632777.1680
	Building	230193.2260	2632800.4570
	Vacant	230513.5050	2632900.8010
	Vegetation	230209.7630	2632757.3960
Mirpur-10	Road	231993.8260	2635536.3830
	Water	231858.8350	2635563.5640
	Vaccant land	231928.6850	2635593.1980
	Building	232036.2250	2635477.2440
	Vegetation	231976.6540	2635563.4720
Shyamoli	Road	231703.8680	2631741.1610
	Building	231679.1960	2631765.9660
	Vegetation	231768.1620	2631789.4480
	Vacant Land	231336.5600	2631786.4710
	Water	231824.1590	2632183.9200
Farmgate	Road	234140.1320	2629682.1300
	Buildng	234075.9710	2629912.3180
	Vacant	233749.2100	2629998.9690
	Vegetation	233826.6010	2630061.1460
	Vegetation	234275.7320	2629881.2290
Science Laboratory	Road	233404.4570	2627610.7030
	Vacant	233294.5220	2627609.1150
	Vegetation	233438.8530	2627835.2020
	Building	233334.0510	2627893.0400
	Water	232902.7400	2627599.5770
Mogbazar	Road	235426.0760	2628919.6780
	Building	235241.9260	2628840.3030
	Vegetation	235484.8140	2628734.7340
	Water	235261.2400	2629343.8060
	Vacant	235842.3550	2628715.5520
Mohakhali	Road	234888.7950	2632140.1930
	Vacant	234534.2520	2631949.0310
	Vegetation	234673.7540	2632137.1500
	Building	234907.2760	2632049.8380
	Water	235228.3480	2632019.4110
Gulshan-1	Road	236763.1990	2632400.0150
	Building	236741.7680	2632440.4960
	Water	236968.3840	2632456.3710
	Vegetation	236568.3330	2632378.5830
	Vacant	236341.4970	2632322.3150

Motijheel	Road	237264.4180	2626359.1240
	Water	237069.6840	2626337.9570
	Vegetation	237257.5390	2626803.6250
	Vacant	237067.0390	2626677.8680
	Building	237137.0870	2626515.4270
Jatrabari	Road	240080.8800	2623788.1960
	Vegetation	239763.4130	2624022.2860
	Water	239669.0890	2623850.7700
	Building	240068.3460	2623821.8640
	Vacant	240454.1090	2623644.5400

Table 49S: Error matrix for supervised classification

		Ground Truth			
Classified in Satellite Image as	Classified	Built-up	Vegetation	Water	No of classified pixel
	Built-up	18	0	0	18
	Vegetation	1	17	3	21
	Water	1	3	7	11
	No of ground truth pixel	20	20	10	50

Table 50S: Image classification accuracy test result for all AOIs

Land use type	Producer's accuracy	User's accuracy	Overall accuracy	Kappa
Built-up	90.00%	100.00%	84%	0.75
Vegetation	85.00%	80.95%		
Water	70.00%	63.64%		

Table 51S: Bio-capacity calculation for each study area

Area	Land Use	Area (Hectare) (A)		Yield Factor (YF)		Equivalency Factor (EQF) (gha/hectare)		Biocapacity (gha)
Mirpur 10	Built-Up Land	55.80	×	1.85	×	2.51	=	259.40
	Forestland	22.58	×	0.35	×	1.26	=	9.99
	Fishing Ground	0.15	×	1.00	×	0.37	=	0.06
	Total Bio-capacity in Mirpur 10						=	269.44
Technical Morh	Built-Up Land	43.74	×	1.85	×	2.51	=	203.34
	Forestland	23.59	×	0.35	×	1.26	=	10.43
	Fishing Ground	11.21	×	1.00	×	0.37	=	4.15
	Total Bio-capacity in Technical Morh						=	217.92
Shyamoli	Built-Up Land	47.41	×	1.85	×	2.51	=	220.40
	Forestland	27.65	×	0.35	×	1.26	=	12.23
	Fishing Ground	3.48	×	1.00	×	0.37	=	1.29
	Total Bio-capacity in Shyamoli						=	233.92
Mohakhali	Built-Up Land	67.21	×	1.85	×	2.51	=	312.42
	Forestland	11.12	×	0.35	×	1.26	=	4.92
	Fishing Ground	0.21	×	1.00	×	0.37	=	0.08
	Total Bio-capacity in Mohakhali						=	317.41
Gulshan 1	Built-Up Land	49.72	×	1.85	×	2.51	=	231.14
	Forestland	11.14	×	0.35	×	1.26	=	4.93
	Fishing Ground	17.68	×	1.00	×	0.37	=	6.54
	Total Bio-capacity in Gulshan 1						=	242.60
Farm-Gate	Built-Up Land	60.45	×	1.85	×	2.51	=	281.00
	Forestland	18.09	×	0.35	×	1.26	=	8.00
	Fishing Ground	0.00	×	1.00	×	0.37	=	0.00
	Total Bio-capacity in Farm-gate						=	289.00
Mog-bazaar	Built-Up Land	62.62	×	1.85	×	2.51	=	291.10
	Forestland	14.97	×	0.35	×	1.26	=	6.62
	Fishing Ground	0.95	×	1.00	×	0.37	=	0.35
	Total Bio-capacity in Mog-bazaar						=	298.07
Science Lab	Built-Up Land	59.64	×	1.85	×	2.51	=	277.26
	Forestland	18.32	×	0.35	×	1.26	=	8.10
	Fishing Ground	0.57	×	1.00	×	0.37	=	0.21
	Total Bio-capacity in Science Lab						=	285.58
Motijheel	Built-Up Land	57.95	×	1.85	×	2.51	=	269.37
	Forestland	16.83	×	0.35	×	1.26	=	7.44
	Fishing Ground	3.77	×	1.00	×	0.37	=	1.39
	Total Bio-capacity in Motijheel						=	278.20
Jatrabari	Built-Up Land	71.42	×	1.85	×	2.51	=	331.99
	Forestland	6.30	×	0.35	×	1.26	=	2.78
	Fishing Ground	0.82	×	1.00	×	0.37	=	0.30
	Total Bio-capacity in Jatrabari						=	335.08

Table 52S: Comparisons of EBI classes between equal class and natural breaks.

Area	Carbon Uptake Land (gha)	Bio- capacity Area (gha)	EBI	EBS (Equal Class)	Color Code (Equal Class)	EBS (Natural Breaks)	Color Code (Natural Breaks)
Area I (Mirpur 10)	785.20	269.43	0.343	3	Orange	2	Yellow
Area II (Mog bazaar)	987.08	298.06	0.302	4	Red	3	Orange
Area III (Motijheel)	1269.36	278.20	0.219	4	Red	3	Orange
Area IV (Gulshan 1)	1398.43	242.60	0.173	4	Red	4	Red
Area V (Shymoli)	1432.89	233.91	0.163	4	Red	4	Red
Area VI (Technical Morh)	1477.91	217.92	0.147	4	Red	4	Red
Area VII (Jatrabari)	1779.99	335.08	0.188	4	Red	4	Red
Area VIII (Mohakhali)	1868.61	317.41	0.170	4	Red	4	Red
Area IX (Science lab)	2363.18	285.57	0.121	4	Red	4	Red
Area X (Farm gate)	2440.20	289.00	0.118	4	Red	4	Red