Transient numerical model of magma ascent dynamics

DOI:

[10.1016/j.jvolgeores.2017.02.013](https://doi.org/10.1016/j.jvolgeores.2017.02.013)

Document Version

Accepted author manuscript

[Link to publication record in Manchester Research Explorer](#)

Citation for published version (APA):

La Spina, G., de' Michieli Vitturi, M., & Clarke, A. B. (2017). Transient numerical model of magma ascent dynamics: application to the explosive eruptions at the Soufrière Hills Volcano. *Journal of Volcanology and Geothermal Research*, 336, 118-139. <https://doi.org/10.1016/j.jvolgeores.2017.02.013>

Published in:

Journal of Volcanology and Geothermal Research

Citing this paper

Please note that where the full-text provided on Manchester Research Explorer is the Author Accepted Manuscript or Proof version this may differ from the final Published version. If citing, it is advised that you check and use the publisher's definitive version.

General rights

Copyright and moral rights for the publications made accessible in the Research Explorer are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

Takedown policy

If you believe that this document breaches copyright please refer to the University of Manchester's Takedown Procedures [<http://man.ac.uk/04Y6Bo>] or contact uml.scholarlycommunications@manchester.ac.uk providing relevant details, so we can investigate your claim.

Transient numerical model of magma ascent dynamics: application to the explosive eruptions at the Soufrière Hills Volcano

G. La Spina^{a,*}, M. de' Michieli Vitturi^b, A.B. Clarke^{c,b}

^a*School of Earth and Environmental Sciences, The University of Manchester, UK.*

^b*Istituto Nazionale di Geofisica e Vulcanologia, Sezione di Pisa, Italy.*

^c*School of Earth and Space Exploration, Arizona State University, Tempe, Arizona, USA*

Abstract

Volcanic activity exhibits a wide range of eruption styles, from relatively slow effusive eruptions that produce lava flows and lava domes, to explosive eruptions that can inject large volumes of fragmented magma and volcanic gases high into the atmosphere. Although controls on eruption style and scale are not fully understood, previous research suggests that the dynamics of magma ascent in the shallow subsurface (< 10 km depth) may in part control the transition from effusive to explosive eruption and variations in eruption style and scale. Here we investigate the initial stages of explosive eruptions using a 1D transient model for magma ascent through a conduit based on the theory of the thermodynamically compatible systems. The model is novel in that it implements finite rates of volatile exsolution and velocity and pressure relaxation between the phases. We validate the model against a simple two-phase Riemann problem, the Air-Water Shock Tube problem, which contains strong shock and rarefaction waves. We then use the model to explore the role of the aforementioned finite rates in controlling eruption style and duration, within the context of two types of eruptions at the Soufrière Hills Volcano, Montserrat: Vulcanian and sub-Plinian eruptions. Exsolution and pressure-velocity relaxation rates all appear to exert important controls on eruption duration. More significantly, however, a single finite exsolution rate characteristic of the Soufrière Hills magma composition is able to produce both end-member eruption durations observed in nature. The duration therefore appears to be largely controlled by the timescales available for exsolution, which depend on dynamic processes such as ascent rate and fragmentation wave speed.

Keywords: magma ascent; conduit dynamics; Soufrière Hills Volcano; finite-rate exsolution; pressure relaxation; velocity relaxation.

1. Introduction

Volcanic activity has extensively shaped the surface of Earth, Mars and the moon (Lopes and Gregg (2004)). That activity exhibits a wide range of eruption styles. Relatively slow effusive eruptions generate lava flows (low viscosity

*Corresponding author.

Email address: giuseppe.laspina@manchester.ac.uk (G. La Spina)

magma) and lava domes (high viscosity magma) and tend to evolve over days to decades. Alternatively, explosive eruptions can inject very large volumes of fragmented magma and volcanic gases high into the atmosphere over shorter periods (minutes to weeks to months). Although controls on eruption style and scale are not well-constrained, previous research suggests that the fluid mechanics governing magma ascent in the shallow subsurface (< 10 km depth) may in part control the transition from effusive to explosive eruption and variations in explosion scale (Eichelberger et al. (1986); Jaupart and Allègre (1991); Woods and Koyaguchi (1994); Eichelberger (1995); Melnik and Sparks (2002b); Melnik and Sparks (2005); Starostin et al. (2005); Mason et al. (2006)).

The term explosive is used to denote any eruption in which magma is fragmented and ejected from the vent as a jet or plume. As the magma rises through the conduit toward the surface, the confining pressure decreases, causing dissolved volatile species, such as water and carbon dioxide, to exsolve from the melt forming gas bubbles, thus providing a driving force for the eruption (Sparks (1978); Pyle and Pyle (1995); Woods and Cardoso (1997)). Fragmentation of silicic magma is caused by high strain rates associated with acceleration of the bubbly mixture (Melnik and Sparks (1999); Papale (1999a); Gonnermann and Manga (2003); Gonnermann (2015)) and bubble overpressure associated with restricted bubble expansion (Sparks (1978); Alidibirov (1994); Papale (1999b); Zhang (1999); Spieler et al. (2004); Kueppers et al. (2006); Gonnermann (2015)). Ascent and fragmentation are influenced not only by the nucleation and growth of gas bubbles, but also by magma rheology and its behaviour under high strain rates. The transition between effusive and explosive eruptions is a direct consequence of the behaviour of the exsolved gas phase within the conduit; whether it is trapped within growing bubbles and unable to expand, trapped in the bubbles and easily able to expand, or separated via permeable gas flow from the viscous melt.

Here we are interested in the initial stages of explosive eruptions, in particular the beginning phases of Vulcanian explosions driven by the collapse of a dome overlying the conduit, as occurred in the 1997 eruptions at the Soufrière Hills Volcano, Montserrat, British West Indies (Druitt and Kokelaar (2002)). Vulcanian eruptions are named after the 1888–1890 eruptions of Vulcano, Aeolian Islands, Italy (Mercalli (1907)), and are defined as short-lived, discrete explosions resulting from sudden decompression of a volcanic conduit that commonly contains high-pressure, vesiculated (bubbly) magma (Self et al. (1979); Woods (1995b); Sparks et al. (1997); Stix et al. (1997); Morrissey and Mastin (2000); Druitt et al. (2002); Clarke (2013); Clarke et al. (2015)). Resulting eruptions typically last only seconds to minutes and may produce buoyant columns, pyroclastic density currents, or both.

The past decade has seen much progress in modelling magma ascent processes during explosive eruptions (Woods and Koyaguchi (1994); Proussevitch and Sahagian (1998); Massol and Jaupart (1999); Melnik (2000); Massol et al. (2001); Papale (2001); Clarke et al. (2002a); Clarke et al. (2002b); Mastin (2002); Melnik and Sparks (2002b); Dufek and Bergantz (2005); Koyaguchi and Mitani (2005); Macedonio et al. (2005); Sahagian (2005); Diller et al. (2006); Clarke et al. (2007); de' Michieli Vitturi et al. (2008); Kozono and Koyaguchi (2009); de' Michieli Vitturi et al. (2010a); de' Michieli Vitturi et al. (2013a); Zeidan et al. (2014); Zeidan (2016)). In contrast to effusive eruptions, explosive eruptions exhibit strong gradients in velocity, density, pressure, and other characteristics. In particular, the zone of fragmentation represents a sharp transition between flow of a bubbly magma and a gas-pyroclasts dispersion. Further, explosive eruptions may

produce shocks and rarefaction waves. Therefore, a model of explosive eruptions should be able to accurately describe very different regimes: a bubbly flow region where the gas is the dispersed phase with low volume fractions (below the fragmentation level), a gas-pyroclasts region where the gas is the continuous carrier phase (above the fragmentation level), as well as the sharp boundary between the two.

Due to the potential significance of these complexities in controlling eruptive regime and style, we investigate the early stages of vulcanian eruptions using the conduit model presented below. It is based on the theory of the thermodynamically compatible systems, which is a generalization of the theory of hyperbolic systems of conservation laws (Godunov and Romenskii (2003); Romenski et al. (2010)). Thermodynamically compatible systems allow the formulation of new governing equations for complex media and processes, such as multiphase flows. Every system of partial differential equations is written in terms of *generating variables* and *generating functions* (Godunov and Romenskii (2003); Romenski et al. (2010)), and can be reduced to a symmetric hyperbolic system. In addition, these systems of partial differential equations satisfy an additional entropy balance law, ensuring that the entropy of the system is not decreasing (as described by the second law of thermodynamics). Using this theory, we will derive a single set of equations to: 1) treat both dilute and dense flow regimes without corresponding simplifications (as done by Pelanti and LeVeque (2006) and Saito et al. (2003) where the assumption of dilute flow is adopted by neglecting the non-conservative terms of the system that model the exchange of momentum and energy between the phases); 2) describe flow above and below the fragmentation level; 3) quantify the interaction between the phases forming the bubbly magma by using two distinct pressures and velocities; 4) prescribe multiple criteria for modelling the fragmentation transition; and 5) account for disequilibrium degassing. While some of these processes have been separately implemented previously (Melnik and Sparks (2002b); Burgisser and Gardner (2004); Dufek and Bergantz (2005); Melnik and Sparks (2005)), the model presented is the first to combine all of these characteristics.

2. Conduit model

In this section the mathematical model for magma ascent in a volcanic conduit is presented. Here we focus on the initial stage of Vulcanian eruptions following the collapse of a lava dome. As the overlying dome collapses, the pressure at the top of the conduit rapidly decreases. Conditions within the conduit soon thereafter exceed a critical condition for fragmentation and explosive activity begins. A rarefaction wave propagates down the conduit into vesiculated magma. As the rarefaction wave passes, the vesiculated magma expands and accelerates upward and fragments when a critical condition is reached, to be discussed below in detail. The fragmented magma forms a gas-particle dispersion, which accelerates up the conduit and exits the vent to form a volcanic column in the atmosphere. Although we model the vent condition feeding the column, the column itself is not treated here. Fig. 1 shows schematically the processes which occur in the conduit. For a more detailed description of the mechanisms and the dynamics of Vulcanian eruptions, the reader is referred to Clarke (2013).

In the past, this type of eruption has often been treated as shock-driven flow (shock-tube) (Ishihara (1985);

Turcotte et al. (1990); Woods (1995a); Chojnicki et al. (2006)) to calculate the velocity and density of the expanding mixture and the velocity and strength of shock waves (Saad (1985)). Here we adopt the same approach, and model the relevant processes with a modification of the single temperature model proposed in Romenski et al. (2010) and studied in La Spina and de' Michieli Vitturi (2012) and La Spina et al. (2014). The single temperature model is a physically-based compressible two phase flow model which has been validated against laboratory experiments (La Spina and de' Michieli Vitturi (2012)). This model has been derived using the theory of thermodynamically compatible systems (Romenski et al. (2010)), and with respect to the common two phase flow model proposed by Baer and Nunziato (1986), all the equations are written in conservative (divergent) form. Note that the divergent form of equations is very attractive because it allows application of known mathematical tools and accurate and robust numerical methods to solve the system of equations, even when strong shock waves are present in the solution. Furthermore, from the system of equations derived from the theory of thermodynamically compatible systems it is possible to derive an additional balance equation for the mixture entropy, which ensures that the entropy of the mixture is not decreasing over time.

With respect to the original system of equations reported in La Spina and de' Michieli Vitturi (2012) and La Spina et al. (2014), the new approach here:

- adds a transport equation for the dissolved volatiles,
- includes terms to account for viscous effects using an appropriate description of magma rheology (as in Hess and Dingwell (1996), Melnik and Sparks (1999) and de' Michieli Vitturi et al. (2010a)) as well as viscous dissipation due to wall friction following Poiseuille's 1D approximation for laminar flow (e.g. Degruyter et al. (2012); Melnik and Sparks (2002b)),
- considers finite relaxation rates for relative velocity and pressure difference, where relaxation rate is the rate at which the values of the two phases approach a common value.

As is also done in the single temperature model of Romenski et al. (2010), the flow of the magmatic multi-phase multi-component mixture along the z -axis is treated as a continuum and the state of each of the phases, denoted by the index $i = 1, 2$, is characterized by its volume fraction α_i , mass density ρ_i , velocity u_i , and specific entropy s_i . Below the fragmentation level the first phase represents the mixture of melt, crystals and dissolved volatiles (carrier phase), while the second phase represents the bubbles of exsolved gases (dispersed phase). Above the fragmentation level the first phase represents the dispersed fragments of magma with dissolved volatiles (dispersed phase), while the second phase is the mixture of exsolved gases (carrier phase). Thus, for the volume fractions, the saturation constraint $\alpha_1 + \alpha_2 = 1$ holds.

Given that the second phase always refers to the exsolved gas phase, we will use without ambiguity the subscript g to refer to this phase, the subscript d to refer to the dissolved volatiles phase, and the subscript m to refer to melt (liquid+crystals+dissolved volatiles).

Figure 1: Schematic illustration of the conduit in the first stages of an eruption.

Given our interest in the multi-phase characteristics of the phenomenon, we allow the pressure and the velocity of the mixture of melt, crystals, and dissolved volatiles to be different from that of the exsolved gas phase. The temperatures of the two phases are assumed to be equal ($T_1 = T_2$).

Finally, denoting with $c_i = \frac{\alpha_i \rho_i}{\rho}$ the mass fraction of the i -th phase, the following mixture parameters of state are introduced:

$$\begin{aligned} \rho &= \alpha_1 \rho_1 + \alpha_2 \rho_2, & P &= \alpha_1 P_1 + \alpha_2 P_2, & u &= c_1 u_1 + c_2 u_2, \\ w &= u_1 - u_2, & s &= c_1 s_1 + c_2 s_2, & e &= c_1 e_1 + c_2 e_2, & E &= e + c_1 c_2 \frac{|w|^2}{2}. \end{aligned} \quad (1)$$

where ρ is the mixture density, u is the mixture velocity, w is the relative velocity, s is the mixture specific entropy and e is the specific internal energy of the mixture.

Using these notations, we write the one-dimensional system of conservation equations derived from the theory of thermodynamically compatible systems (Romenski et al. (2010)). Here, dissipative non-equilibrium processes, such as pressure relaxation, inter-facial friction and gas exsolution, and volumetric force terms, such as gravity and viscosity, are included as source terms:

$$\frac{\partial \rho}{\partial t} + \frac{\partial \rho u}{\partial z} = 0, \quad (2)$$

$$\frac{\partial \rho \alpha_1}{\partial t} + \frac{\partial \rho u \alpha_1}{\partial z} = -\frac{1}{\tau^{(p)}} (P_2 - P_1), \quad (3)$$

$$\frac{\partial \alpha_1 \rho_1}{\partial t} + \frac{\partial \alpha_1 \rho_1 u_1}{\partial z} = -\frac{1}{\tau^{(d)}} (1 - \phi_f) (x_d - x_d^{eq}) \alpha_1 \rho_1, \quad (4)$$

$$\frac{\partial \rho u}{\partial t} + \frac{\partial(\alpha_1 \rho_1 u_1^2 + \alpha_2 \rho_2 u_2^2 + \alpha_1 P_1 + \alpha_2 P_2)}{\partial z} = -\rho g - (1 - \phi_f) \frac{8\mu_1 u_1}{R^2} - \phi_f \frac{8\mu_2 u_2}{R^2}, \quad (5)$$

$$\frac{\partial w}{\partial t} + \frac{\partial}{\partial z} \left(\frac{u_1^2}{2} - \frac{u_2^2}{2} + e_1 + \frac{P_1}{\rho_1} - e_2 - \frac{P_2}{\rho_2} - (s_1 - s_2)T \right) = -\frac{1}{\tau^{(f)}} \frac{c_1 c_2 w}{\rho} - (1 - \phi_f) \frac{8\mu_1 u_1}{\alpha_1 \rho_1 R^2} + \phi_f \frac{8\mu_2 u_2}{\alpha_2 \rho_2 R^2}, \quad (6)$$

$$\frac{\partial}{\partial t} \left[\rho \left(E + \frac{u^2}{2} \right) \right] + \frac{\partial}{\partial z} \left[\alpha_1 \rho_1 u_1 \left(e_1 + \frac{p_1}{\rho_1} + \frac{u_1^2}{2} \right) + \alpha_2 \rho_2 u_2 \left(e_2 + \frac{p_2}{\rho_2} + \frac{u_2^2}{2} \right) - \rho c_1 c_2 w (s_1 - s_2) T \right] =$$

$$-\rho g u - (1 - \phi_f) \frac{8\mu_1 u_1^2}{R^2} - \phi_f \frac{8\mu_2 u_2^2}{R^2}$$

$$\frac{\partial}{\partial t} (\alpha_1 \rho_1 x_d) + \frac{\partial}{\partial z} (\alpha_1 \rho_1 x_d u_1) = -\frac{1}{\tau^{(d)}} (1 - \phi_f) (x_d - x_d^{eq}) \alpha_1 \rho_1. \quad (8)$$

$$\frac{\partial}{\partial t} (\alpha_1 \rho_c \beta) + \frac{\partial}{\partial z} (\alpha_1 \rho_c \beta u_1) = -\frac{1}{\tau^{(c)}} (\beta - \beta^{eq}) \alpha_1 \rho_c. \quad (9)$$

The equations here are expressed in a conservative (or divergent) form, and, in this specific case, there are the governing differential equations for, respectively, the total mass (Eq. 2), the first phase volume fraction (Eq. 3), the first phase bulk density (Eq. 4), the total momentum (Eq. 5), the relative velocity (Eq. 6), the total mixture energy (Eq. 7), the dissolved volatiles bulk density (Eq. 8), and the crystal bulk density (Eq. 9). We note here that the term “conservative equations” refers to equations written in a conservative mathematical form, and emphasize that they are not conservation laws for these variables. And, although some of these equations are conservation laws in the traditional sense (such as Eq. 2, 5 and 7), others are not (such as Eq. 3, 6). Furthermore, we highlight that it is possible to rewrite these equations as the common two phase flow model proposed by Baer and Nunziato (1986), which consists of conservation laws for mass, momentum and energy of each phase, completed by a balance equation for the volume fraction.

The fragmentation flag $\phi_f \in \{0, 1\}$ is a variable that allows us to consider the transition from the magma/bubble region ($\phi_f = 0$) to the gas/particle zone ($\phi_f = 1$). The viscosity terms included in the momentum, relative velocity and mixture energy equations are derived from Poiseuille’s approximation for fully-developed, steady, 1D laminar flow through a pipe. In Eqs. (4,8) we use the notation x_d for the mass fraction of the dissolved volatiles and x_d^{eq} for the equilibrium mass fraction. Here we used a different approach with respect to that of La Spina et al. (2014) to model mass transfer of the volatile phase. La Spina et al. (2014) modelled mass transfer by balancing the Gibbs free energies of both the liquid and volatile phases. In the formulation presented here, we instead quantify the mass transfer rate according to the difference between the actual dissolved volatile content and the equilibrium value, which is calculated using Henry’s law (see Section 3.3.1). Similarly for the dissolved volatile content, in Eq. (9) we use the notation β for the volume fraction of crystals and β^{eq} for the equilibrium volume fraction. Furthermore, we indicate with ρ_c the

density of the crystals. In this work, following Melnik and Sparks (2002b), we will assume a constant crystal volume fraction within the conduit, allowing us to neglect Eq. (9) from the system of equations solved here.

The parameter $\tau^{(p)}$ is the pressure relaxation rate, $\tau^{(f)}$ is the velocity relaxation rate and $\tau^{(d)}$ is the degassing rate, all to be discussed further in subsequent sections. In the equation for momentum conservation g is the absolute value of the gravitational acceleration, μ_1 is the magma viscosity, which is a function of the melt viscosity and the crystal content, μ_2 is the gas viscosity, and R is the conduit radius, here assumed to be constant. In this model we assume that the constant crystal content affects only the viscosity of the magma.

For effusive eruptions and explosive eruptions below the fragmentation level ($\phi_f = 0$) the viscous force term depends only on magma viscosity, μ_1 , while for explosive eruptions above the fragmentation level ($\phi_f = 1$) the viscous forces depend only on the gas viscosity, μ_2 .

Following the same analysis presented in La Spina and de' Michieli Vitturi (2012) and La Spina et al. (2014), it is possible to show that the system of equations (2-8), describing the conduit dynamics, allows an additional entropy balance law written in the following form:

$$\frac{\partial}{\partial t}(\rho s) + \frac{\partial}{\partial z}(\rho u s) = \Pi, \quad (10)$$

where the right hand side Π is a positive term representing the entropy production. It is worth noting that in most of the existing conduit models entropy production is neglected.

The theory of thermodynamically compatible systems ensures that the system of differential equations (2-8) is hyperbolic, which means that all the eigenvalues of the system are real numbers and guarantees that the solutions of the system are "wave-like", i.e. disturbances and discontinuities propagate at finite speed. The calculation of these speeds, given by the eigenvalues of the system, is extremely important for the implementation of the numerical solver, and that is why a characteristic analysis of the system is required. The characteristic analysis of the system (2-8) is reported in Appendix A.

3. Constitutive equations and equations of state

The conduit model presented above collects the partial differential equations governing the ascent dynamics of a magmatic mixture. In order to reproduce the ascent dynamics of a specific volcanic system reasonably, we need to provide appropriate constitutive equations and equations of state. Solubility, rheology and fragmentation models vary depending on the volcanic system and style of eruption. Here we focus on constitutive equations appropriate for the physical and chemical properties of andesite melts, such as that of the Soufrière Hills Volcano, Montserrat.

3.1. Magma rheology

During magma ascent, even within a single volcanic eruption, viscosity can vary by several orders of magnitude. Viscosity of the melt mostly depends on the degree of polymerization, a function of chemical composition and volatile

content (Giordano and Dingwell (2003)). For example, within realistic ranges of compositional variability, eruptive temperatures, and volatile contents, the viscosity of basaltic melts may vary between about 10 and 10^3 Pa·s, and silicic melts may vary between about 10^4 and 10^{12} Pa·s. Changes in viscosity during individual eruptions are especially pronounced at low pressures where most of the water exsolves. In rhyolitic melts, the viscosity is controlled mainly by the temperature and by the water and crystal contents (Hess and Dingwell (1996); Hui and Zhang (2007); Zhang et al. (2007); Giordano et al. (2008)).

With the assumption of a Newtonian fluid, following de' Michieli Vitturi et al. (2010a), the viscosity of the magmatic phase in the explosive regime below the fragmentation level is modelled as:

$$\mu_1 = \mu_{melt} \cdot \theta(\beta), \quad (11)$$

where μ_{melt} is the viscosity of the bubble-free, crystal-free liquid phase and θ is a factor which increases viscosity due to the presence of crystals (Lejeune and Richet (1995); Caricchi et al. (2007)).

We use an empirical relationship to estimate μ_{melt} as a function of water concentration and temperature, as in Hess and Dingwell (1996) (based on the Vogel-Fulcher-Tammann equation):

$$\log(\mu_{melt}) = [-3.545 + 0.833 \ln(w_{H_2O})] + \frac{[9601 - 2368 \ln(w_{H_2O})]}{T - [195.7 + 32.25 \ln(w_{H_2O})]}, \quad (12)$$

where the viscosity μ_{melt} is in Pa·s, w_{H_2O} is H_2O concentration in weight percent ($w = 100 \cdot x_d$) and T is the temperature in Kelvin.

Furthermore, as crystallization proceeds, viscosity increases according to the empirical model described in Melnik and Sparks (1999):

$$\log\left(\frac{\theta}{\theta_0}\right) = \arctan(\omega_\star(\beta - \beta_\star)), \quad (13)$$

where θ_0 , $\omega_\star$, $\beta_\star$ are constants. We remind the reader here that in this model we assumed a constant crystal content, making β constant. Other models for θ_1 were tested by Dingwell et al. (1993), Lejeune and Richet (1995), and Costa (2005), resulting in similar general trends for the parameter space explored here.

3.2. Magma fragmentation

Decompression during magma ascent causes volatiles to exsolve and form bubbles containing a supercritical fluid phase. Viscous magmas, such as rhyolite or crystal-rich magmas, do not allow bubbles to ascend buoyantly and may also hinder bubble growth. This condition can lead to significant gas overpressure and brittle magma fragmentation. During fragmentation in vulcanian, subplinian, and plinian eruptions, gas is released explosively into the atmosphere, carrying with it magma fragments known as pyroclasts.

Here we focus on ordinary magma fragmentation, which we define as fragmentation not caused by interaction with non-magmatic water. The type and efficiency of the fragmentation process determines pyroclast size and how

much magmatic gas is released per unit mass of magma. These values in turn, have implications for the volcanic jet, plume and column that are produced when the gas-pyroclast mixture exits the volcanic vent.

Fragmentation is thought to occur when specific conditions are reached within the conduit. In the literature there exist several fragmentation criteria, but the most common are (a) the critical volume fraction; (b) the stress criterion; and (c) the strain-rate criterion. Traditionally, it had been assumed that fragmentation occurs at a critical volume fraction, presumably due to the instability of thin bubble walls (Verhoogen (1951); Sparks (1978); Gardner et al. (1996); Dufek and Bergantz (2005)) and the high velocity gradient associated with decreasing magma density. According to a series of numerical solutions (Sparks (1978)), bubbles should stop growing long before explosive fragmentation, primarily because of increasing melt viscosity. The solutions led to the concept that bubble volume fraction never exceeds 66 – 83%.

In the proposed model we have chosen to adopt the critical volume fraction criterion. Thus, we assume that the fragmentation of the magma occurs when the volume fraction of the bubbles reaches a limit threshold $\alpha_{2,f}$. Following this criterion we define the fragmentation flag ϕ_f as:

$$\phi_f = \begin{cases} 0 & \text{if } \alpha_2 < \alpha_{2,f} \\ 1 & \text{otherwise} \end{cases} . \quad (14)$$

3.3. Disequilibrium processes

The numerical model presented here takes into account several finite-rate processes, such as exsolution, overpressurization, and outgassing. The rate of these processes is controlled in the model by specific relaxation parameters, τ . In nature, overpressurization and outgassing are strongly coupled processes, suggesting that there exists a relationship between the two corresponding relaxation parameters. Such a relationship, however, is not easy to determine, and therefore, for simplicity, we have treated them independently.

3.3.1. Degassing

Volatile solubility is primarily controlled by pressure, whereas other factors such as temperature and chemical variations play a minor role. Formulations for volatile solubility can be thermodynamic (Papale (1999a); Papale et al. (2006)) or empirical (Moore et al. (1998); Liu et al. (2005)). In either case, calibration is achieved experimentally using measurements of dissolved volatile concentrations in quenched melts, equilibrated with a volatile phase of known composition at a fixed pressure and temperature.

In our model, kinetic disequilibrium in gas exsolution is modelled by an equation that treats disequilibrium as a relaxation process

$$\frac{\partial}{\partial t} (\alpha_1 \rho_1 x_d) + \frac{\partial}{\partial z} (\alpha_1 \rho_1 x_d u_1) = -\frac{1}{\tau(d)} (1 - \phi_f) (x_d - x_d^{eq}) \alpha_1 \rho_1 . \quad (15)$$

The equilibrium mass concentration (relative to the crystal- and bubble-free magma) of the dissolved volatile x_d^{eq} is defined by Henry's law

$$x_d^{eq} = \sigma \sqrt{P_2}, \quad (16)$$

where σ is the solubility constant of the gas (for water in silicic melts, for instance, $\sigma = 4.11 \times 10^{-6} \text{Pa}^{-\frac{1}{2}}$ (Burnham (1979))).

The rate of degassing is controlled in the model by the relaxation parameter $\tau^{(d)}$ (s). This coefficient is the characteristic timescale of the degassing process, which reflects the time required to reduce the difference between the actual and the equilibrium value to $1/e$ ($\sim 37\%$) of the initial difference, in response to a perturbation of the system. Therefore, if $x_{d,0}$ is the initial value at the time $t = 0$ and x_d^{eq} is the equilibrium value at the new state after a perturbation of the system, then, after a time $\tau^{(d)}$, we have $x_d(\tau^{(d)}) = x_d^{eq} + (x_{d,0} - x_d^{eq})/e$. The smaller the time constant the faster the system converges towards its equilibrium state.

3.3.2. Overpressure

The term in Eq. (3), $-\frac{1}{\tau^{(p)}}(P_2 - P_1)$, represents the growing rate of the volume fraction α_1 required to reach pressure equilibrium. The physical meaning of this term is simple. If the various phases are not in pressure equilibrium after any pressure change, such as after the passage of a rarefaction or shock wave, the volume of each phase must change in order to reach pressure equilibrium. The variable $\tau^{(p)}$ specifies the rate at which this equilibrium is reached. The existence of this variable has been demonstrated theoretically according to the second law of thermodynamics and mechanics of irreversible process (Baer and Nunziato (1986)). It has been shown by Saurel and Abgrall (1999) that these terms are crucial for the computation of pressure waves in two-phase mixtures, but are also critical for restoring the pressure interface condition when solving for interfaces between compressible materials.

For a magmatic mixture rising in a conduit, bubble overpressure develops primarily because of viscous-limited growth of bubbles (Sparks (1978); Proussevitch and Sahagian (1996); Navon and Lyakhovsky (1998)). The gas phase expands in response to decreasing ambient magma pressure, while on the other hand, bubble-growth is resisted by surrounding high-viscosity melt, resulting in a trapped high-pressure gas phase.

Here the relaxation parameter $\tau^{(p)}$ (m^2/s) is assumed to be a function of the volumetric fractions, melt viscosity and mixture density in the magma/bubble region, while it is assumed to be constant in the gas/particle zone, i.e.

$$\tau^{(p)} = \tau_0^{(p)} \left[(1 - \phi_f) \frac{\mu_1}{\rho \alpha_2 \alpha_1} + 0.001 \phi_f \Psi_{\text{m}^2/\text{s}} \right], \quad (17)$$

where $\Psi_{\text{m}^2/\text{s}} = 1 \text{ m}^2/\text{s}$ is a constant parameter inserted to maintain the same units within square brackets and $\tau_0^{(p)}$ is a 0/1 non-dimensional constant used to turn off and on the pressure disequilibrium. In general, when $\tau^{(p)}$ tends towards zero we are forcing both pressures to be equal, whereas when $\tau^{(p)}$ tends towards infinity the pressures are completely decoupled.

3.3.3. Outgassing

The efficiency of gas escape during the ascent of silicic magma governs the transition between effusive and explosive eruptions (Woods and Koyaguchi (1994); Gonnermann and Manga (2007)). If the gas phase can separate easily

from the magma, an effusive eruption occurs. On the other hand, when the gas stays trapped within the ascending magma, it provides the potential energy needed to fragment the magma and produce an explosive eruption.

Degruyter et al. (2012) suggest that outgassing during magma ascent can be described by Forchheimer's law (Rust and Cashman (2004)), an extension of Darcy's law, which accounts for the effects of turbulence:

$$\left| \frac{dP}{dz} \right| = \frac{\mu_g}{k_1} U + \frac{\rho_g}{k_2} U^2,$$

where z is the direction of flow, P is the pressure, U is the volume flux, μ_g is the viscosity, ρ_g is the density of the gas phase. The Darcian permeability, k_1 , and the inertial permeability, k_2 , account for the influence of the geometry of the network of bubbles preserved in the juvenile pyroclasts.

Here the relative velocity between the two phases is modelled through the interphase force defined by the velocity relaxation rate $\tau^{(f)}$ ($\text{m}^3\text{s/kg}$). Below the fragmentation level (f.l.) we use Forchheimer's law to model the outgassing, while above the fragmentation depth we use the model reported in Yoshida and Koyaguchi (1999), which represents the drag between gas and a population of pyroclasts. With these choices for the outgassing models, the velocity relaxation rate takes the form

$$\tau^{(f)} = \begin{cases} \tau_0^{(f)} \left[\frac{\alpha_1 \alpha_2}{c_1^2 c_2^2} \left(\frac{\mu_2}{k_1} + \frac{\rho_2 |u_1 - u_2|}{k_2} \right) \right]^{-1} & \text{below f.l.} \\ \tau_0^{(f)} \left[\frac{\alpha_1 \alpha_2}{c_1^2 c_2^2} \left(\frac{3C_d}{8r_a} \rho_2 |u_1 - u_2| \right) \right]^{-1} & \text{above f.l.} \end{cases}, \quad (18)$$

or in a more compact form

$$\frac{1}{\tau^{(f)}} = \frac{1}{\tau_0^{(f)}} \frac{\alpha_1 \alpha_2}{c_1^2 c_2^2} \left[(1 - \phi_f) \left(\frac{\mu_2}{k_1} + \frac{\rho_2 |u_1 - u_2|}{k_2} \right) + \phi_f \left(\frac{3C_d}{8r_a} \rho_2 |u_1 - u_2| \right) \right], \quad (19)$$

where

$$k_1 = \frac{(f_{ib} r_b)^2}{8} (\alpha_2)^m, \quad k_2 = \frac{f_{ib} r_b}{f_0} (\alpha_2)^{(1+3m)/2}. \quad (20)$$

In Eq. (20), f_{ib} is the throat-bubble size ratio and r_b is the average bubble size, which, following Gonnermann and Manga (2005), can be determined from the bubble number density and the gas volume fraction according to

$$r_b = \left(\frac{\alpha_2}{\frac{4\pi}{3} N_d \alpha_1} \right)^{1/3}. \quad (21)$$

Bounds on the four parameters can be found in the literature: $N_d = 10^8 - 10^{16} \text{m}^{-3}$ (Klug and Cashman (1994); Polacci et al. (2006); Sable et al. (2006); Giachetti et al. (2010)); $f_{ib} = 0.1-1$ (Saar and Manga (1999); Degruyter et al. (2010)); $m = 1 - 10$ (Le Pennec et al. (2001); Bernard et al. (2007); Wright et al. (2009)); and Degruyter et al. (2010) estimated f_0 between 10 and 100 for pumices.

Similar to the pressure disequilibrium term, $\tau_0^{(f)}$ is a 0/1 non-dimensional constant used to turn off and on the velocity disequilibrium between phases. When $\tau_0^{(f)}$ tends towards zero we are forcing both velocities to be equal, whereas when $\tau_0^{(f)}$ tends towards infinity the velocities are completely decoupled.

3.4. Equations of state

Pressure waves, and thus the propagation of a rarefaction front, occur only in compressible media. For this reason in our work, unlike most of the existing conduit models (such as those in Melnik and Sparks (2002b) and Degruyter et al. (2012)), both the gas and liquid phases are treated as compressible. The Mie-Grüneisen equations of state (EOS) are frequently used to model media at high pressure and high temperature conditions (Menikoff (2000); Huang et al. (2016)), and they have been adopted here in a linearized form (Menikoff and Plohr (1989); Le Métayer et al. (2004); Le Métayer et al. (2005); Romenski et al. (2010)):

$$e_i(\rho_i, T) = \bar{e}_i + c_{v,i}T + \frac{\rho_{0,i}C_{0,i}^2 - \gamma_i P_{0,i}}{\gamma_i \rho_i}, \quad (22)$$

$$P_i(\rho_i, T) = c_{v,i}(\gamma_i - 1)\rho_i T - \frac{\rho_{0,i}C_{0,i}^2 - \gamma_i P_{0,i}}{\gamma_i}, \quad (23)$$

$$s_i(\rho_i, T) = s_{0,i} + c_{v,i} \ln \left[\frac{T}{T_{0,i}} \left(\frac{\rho_{0,i}}{\rho_i} \right)^{\gamma_i - 1} \right]. \quad (24)$$

Here, $\bar{e}_i$ is a constant parameter representing the formation energy of the fluid, $c_{v,i}$ is the specific heat capacity at constant volume, γ_i is the adiabatic exponent, $\rho_{0,i}$ is the reference density, $T_{0,i}$ is the reference temperature, and $C_{0,i}$, $P_{0,i}$, $s_{0,i}$ are respectively the speed of sound, the pressure and the entropy at the reference state $(\rho_{0,i}, T_{0,i})$. In this work, the reference pressure of the liquid phase is given as an independent parameter, whilst, for the gas phase, it is assumed to be a function of the reference density, the adiabatic exponent, and the speed of sound at the reference state, i.e.

$$P_{0,2} = \frac{\rho_{0,2}C_{0,2}^2}{\gamma_2}. \quad (25)$$

With this assumption, the last term in the expression for P_2 and e_2 cancels, and the Mie-Grüneisen equations of state for the gas phase become the equations of state for an ideal gas.

As is generally done for volcanic conduit models (e.g. Melnik and Sparks (2002b); de' Michieli Vitturi et al. (2008, 2010a)), we assume here that the dissolved volatile content does not affect the density and the equation of state of the melt.

4. Numerical Tests

The system of equations (2-8) is solved using an Implicit-Explicit (IMEX), Diagonally-Implicit Runge-Kutta scheme (DIRK), because such schemes are well-suited for solving stiff systems of partial differential equations, and

	P_0 (Pa)	ρ_0 (kg/m ³)	C_0 (m/s)	γ	c_v (J/(kg · K))	$\bar{e}$ (J/kg)	s_0 (J/(kg · K))
Water	10 ⁵	1000	1625	4.4	951	0.0	0.0
Air	99911.429	1	374	1.4	714	0.0	0.0

Table 1: Parameters of the equation of state for water and air.

this system is expected to be stiff given the sharp gradients associated with the natural system. The solution scheme is described in detail in the Appendix B.

Before adopting the conduit model to simulate the initial stages of an explosive eruption, we validate a simplified version of the model itself against a well-known 1D Riemann gas-liquid problem: the Air-Water Shock Tube Problem. Similar to the conduit case, the initial state is described as an overpressured liquid, above which is present a gas at low pressure. Due to the presence of strong shock and rarefaction waves in the solution, with this test we will also assess the correctness and the robustness of the numerical scheme used to solve the model. Testing the ability of the numerical scheme to accurately describe the propagation of shock and rarefaction waves is essential to using the conduit model, since, during an eruption, these waves are present and propagate along the conduit. Furthermore, assuming that the constitutive equations from the literature cited in the manuscript reasonably describe the volcanic system, and noting that the model and solver generally capture the propagation of discontinuities with fidelity, it is therefore reasonable to conclude that our solution reasonably describes magma dynamics in a volcanic conduit.

4.1. Validation of the simplified model: the Air-Water Shock Tube Problem

The test presented here extends the strong-shock Riemann problem described in Toro (2009) to two phases, and was previously presented by Romenski et al. (2010) and studied in detail in La Spina and de' Michieli Vitturi (2012).

We simulate an air-water shock tube by considering an initial solution in which pure water and pure air are separated by an interface. In this test we do not consider the exsolution process, and thus we pose $x_d = x_d^{eq} = 0$. We assume also inviscid conditions for both phases, i.e. $\mu_1 = \mu_2 = 0$. Furthermore, gravitational acceleration is not taken into account for this simulation (i.e. $g = 0$). Finally, we consider instantaneous relaxation for the velocity and pressure, which translates to $\tau_0^{(p)} = \tau_0^{(f)} = 0$, such that the two phases have common pressures and velocities throughout the test.

The computational domain considered is $[0, 1]$ m with a Riemann problem being defined by the interface located at $x = 0.75$ m. The initial conditions of the test are:

$$\begin{cases} \alpha_1 = 1 - \epsilon, P_i = 10^9 \text{ Pa}, u_i = 0 \text{ m/s}, T = 495 \text{ K} & \forall x \in [0, 0.75] \text{ m} \\ \alpha_1 = \epsilon, P_i = 10^6 \text{ Pa}, u_i = 0 \text{ m/s}, T = 270 \text{ K} & \forall x \in [0.75, 1] \text{ m} \end{cases},$$

for $i = 1, 2$ and $\epsilon = 10^{-7}$. The indices 1 and 2 refer to the parameters of state of water and air, respectively, and the constants for the equations of state are given in Table 1. In the numerical initial conditions we must prescribe that at

Figure 2: Air-Water Shock - Comparison of the reference solutions (black lines) with those obtained using the numerical scheme proposed in this work with different cells grid: 250 (blue lines), 500 (green lines), 1000 (red lines) and 2000 (cyan lines) cells. Here we report the mixture density (a), the mixture pressure (b), the mixture temperature (c) and the mixture velocity (d).

least a small volume fraction ϵ (here equal to 10^{-7}) of each phase is present in both sections because the governing equations become invalid for phase volume fractions of 0 or 1.

At $x = 0$ and $x = 1$ we impose transmissive boundary conditions. We present here the numerical solutions computed at time 2.5×10^{-4} s using a Courant-Friedrichs-Lewy (CFL) coefficient equal to 0.49.

In Fig. 2 we plot the reference solutions (black lines) for the mixture density (a), mixture pressure (b), temperature (c) and mixture velocity (d) reported in La Spina and de' Michieli Vitturi (2012) for the same test problem. These reference solutions have been computed using a splitting approach in conjunction with the Kurganov, Noelle and Petrova numerical fluxes (Kurganov et al. (2001); La Spina and de' Michieli Vitturi (2012)) on a 16000-cell grid. We compare these reference solutions with those obtained using the numerical scheme proposed in this work (DIRK ARS-KNP, see Appendix B) with different numbers of cells making up the grid: 250 (blue lines), 500 (green lines), 1000 (red lines) and 2000 (cyan lines) cells.

Once the interface between water and air is removed, the propagation of a rarefaction wave and of shock waves begins. From Fig. 2 we can see the presence of rarefaction waves propagating towards the left into the water (the linear decrease in the mixture density) and a shock wave propagating towards the right into the air (the small discontinuity in the mixture density). Another shock wave, propagating towards the right, is visible in the mixture density, and it is the contact discontinuity between water and air. As we can see, both rarefaction and shock waves are well captured, without spurious oscillation. Furthermore, increasing the number of the grid cells leads to better agreement between our numerical solution and the reference solution.

In conclusion, the numerical scheme proposed here accurately solves the propagation of rarefaction and shock waves, and therefore, it can be applied to simulate the ascent dynamics of an explosive eruption.

4.2. Application of the conduit model: the explosive eruptions at the Soufrière Hills Volcano

Here we attempt to reproduce the initial stages of an explosive eruption. We focus our attention on the initial phases of a series of Vulcanian explosions that occurred in 1997 at the Soufrière Hills Volcano, Montserrat, since these events are well described by Druitt et al. (2002). Although we focus only on Vulcanian eruptions, the dynamics during the initial stages of any explosive eruption are quite similar, and therefore our results remain valid for explosive eruptions in general.

The Vulcanian activity considered here took place as a series of explosions (13 explosions between 3 and 12 August and 75 explosions between 22 September and 21 October). Each series involved quasi-periodic behavior, with magma ascending the conduit between each explosion. The repeated Vulcanian explosions were short-lived, with the most intense activity occurring over a few tens of seconds (Druitt et al. (2002)), followed by periods of strong ash-venting lasting typically 30 minutes to an hour. The explosions involved fountain collapse and generation of ground-hugging pumice-and-ash flows, simultaneous with plume rise. Ballistic clasts (up to 1.2m diameter) were ejected to distances up to 1.6 km from the vent with velocities of $110 - 140 \text{ ms}^{-1}$ (de' Michieli Vitturi et al. (2010b)). Eruption column heights ranged from 3 km to a 15 km, with inferred peak discharge rates of hundreds to a few thousands of cubic meters per second. Druitt et al. (2002) estimated the typical volume of ejecta per eruption as $3 \times 10^5 \text{ m}^3 \text{ DRE}$ (dense rock equivalent), although volumes of the largest individual explosions may have exceeded $10^6 \text{ m}^3 \text{ DRE}$. If the conduit has a diameter of 30 m (Melnik and Sparks (2002a)) then typical drawdown depths were 200 – 1000 m.

The initial conditions and the assumptions for the numerical simulations of the conduit processes involved in the Vulcanian eruptions are similar to those used by Melnik and Sparks (2002b). First we consider an initial equilibrium between melt and exsolved gas pressures. We assume constant temperature and zero velocity in the conduit prior to the explosion because of the presence of a plugging dome or plug. The common pressure is defined as a decreasing linear function from the magma chamber to the vent. As done in Melnik and Sparks (2002b), in order to avoid difficulties with boundary conditions at the initial stages of the eruption, we extend the conduit by 200 m toward the surface. We assume that this zone, as we can see from Fig. 3, is occupied mainly by the exsolved gas phase at atmospheric pressure, while all the other quantities remain constant. The initial exsolved gas volume fraction (below $z=0$ m) is

Figure 3: Initial profiles of pressure (a), bubbles volume fraction (b), temperature (c) and melt and gas velocity (d) for the simulated eruption of the Soufrière Hills Volcano.

	P_0 (Pa)	ρ_0 (kg/m ³)	C_0 (m/s)	γ	c_v (J/(kg K))	$\bar{e}$ (J/kg)	s_0 (J/(kg K))
Melt + Crystals	10^8	2500	2000	2.3	1200	0.0	0.0
Gas	99911.43	1	374	1.4	1154.0	0.0	0.0

Table 2: Parameters of the equation of state for melt and gas. The reference density ρ_0 for the melt is corrected due to the presence of the crystals.

obtained assuming closed-system degassing at equilibrium conditions, and, due to the initial conditions chosen, it remains under the fragmentation threshold. Therefore, unlike as done in Clarke et al. (2002b), at the beginning of the simulation, the magma is completely unfragmented. We also assume an initial constant crystal content of the melt.

The parameters for the equations of state used in these simulations are reported in Table 2. Since we do not have constraints on all the parameters for the melt+crystals phase, we set them such that the density all along the conduit is as close to 2500 kg m⁻³ as possible and such that the speed of sound is ~2000 m/s (the speed of sound of a silicate crystal-free melt should be around 1600 m/s, but the presence of the crystals increases it). Although the choice of the parameters for the equations of state of melt+crystals cannot be supported by experimental studies, the agreement of the numerical results presented below with the shock-tube experiments of Koyaguchi et al. (2008) and with the results of Clarke et al. (2002b) suggest that, at least to first order, the parameters for the equations of state here are appropriate.

The parameters used for the initial condition are reported in Table 3, while Fig. 3 shows the pre-eruptive profiles for pressures (a), volume fraction of bubbles (b), temperature (c) and melt and gas velocity (d). For all the simulations presented in this section, the solutions are obtained using a grid of 1300 cells. As boundary conditions, we assume that pressure, temperature and volume fraction of bubbles in the magma chamber (i.e. at the conduit inlet) remain constant during the simulations, while the pressure of both phases at the top of the computational domain remain

Parameter	Symbol	Value	Information sources
Conduit length	L	5 km	Barclay et al. (1998)
Melt water content	$x_{d,0}$	0.05	Barclay et al. (1998)
Crystalline content	β	0.60	Murphy et al. (2000)
Temperature	T	1123 K	Barclay et al. (1998)
Chamber Overpressure	P_{ch}	10 MPa	Melnik and Sparks (2002b)
Conduit radius	R	15 m	Devine et al. (1998)
Solubility	σ	$4.11 \times 10^{-6} \text{ Pa}^{-0.5}$	Burnham (1979)
Bubble number density	N	10^{15}	Degruyter et al. (2012)
Throat-bubble size ratio	f_{ib}	0.10	Degruyter et al. (2012)
Tortuosity factor	m	3.5	Degruyter et al. (2012)
Friction coefficient	f_0	10	Degruyter et al. (2012)
Ash particle size	r_a	0.001 m	Degruyter et al. (2012)
Gas-ash drag coefficient	C_d	0.8	Degruyter et al. (2012)
Gas-wall drag coefficient	λ_w	0.03	Degruyter et al. (2012)
	θ_0	1.6	Melnik and Sparks (1999)
	$\beta_\star$	0.62	Melnik and Sparks (1999)
	$\omega_\star$	20.6	Melnik and Sparks (1999)
Fragmentation threshold	$\alpha_{2,f}$	0.6	Melnik and Sparks (2002b)

Table 3: Parameters of the conduit model used for the simulated eruption of the Soufrière Hills Volcano.

fixed at atmospheric pressure. In reality, once the flow becomes sonic, the exit pressure can deviate from atmospheric pressure (choked flow condition); in this case all the eigenvalues of the system at the vent are non-negative (i.e. directed outside the vent), which means that information about pressure outside the conduit does not propagate into the conduit. With the current implementation of the model, we cannot consider a choked flow condition, however, for each simulation at each time step, we calculated the minimum eigenvalue at the vent, ensuring that choked flow is never reached, and, therefore, that the assumption of atmospheric pressure is still valid.

We conducted several numerical simulations assuming different relaxation parameters. First we assumed a single pressure and a single velocity, obtained by imposing $\tau_0^{(p)} = \tau_0^{(f)} = 0$. With these assumptions, we conducted three numerical simulations, considering respectively no exsolution, instantaneous exsolution, and finite rate exsolution. In particular, the numerical simulation at finite degassing rate is something new beyond the two end-member cases investigated in Melnik and Sparks (2002b). Afterwards, we relaxed the assumption of single pressure and single velocity by assuming $\tau_0^{(p)} = \tau_0^{(f)} = 1$, and performed three additional numerical simulations, again assuming no exsolution, instantaneous exsolution, and finite rate exsolution. A summary of the relaxation parameters adopted for

Run name	$\tau_0^{(p)}$	$\tau_0^{(f)}$	$\tau^{(d)}$ (s)
InstPU_NoEx	0	0	10^{15}
InstPU_InstEx	0	0	0.001
InstPU_FiniteRateEx	0	0	1000
FiniteRatePU_NoEx	1	1	10^{15}
FiniteRatePU_InstEx	1	1	0.001
FiniteRatePU_FiniteRateEx	1	1	1000

Table 4: Summary of the numerical simulations presented in sections 4.2.1 and 4.2.2 with the corresponding relaxation parameters adopted for each of them.

these numerical simulations is reported in Table 4.

4.2.1. Instantaneous pressure and velocity relaxation rates

As a first test, in order to compare the numerical results with those obtained by Melnik and Sparks (2002b), we assume instantaneous relaxation of pressure and velocity ($\tau_0^{(p)} = \tau_0^{(f)} = 0$), and use end-member relaxation rates for gas exsolution. More specifically, we aim to compare the solutions obtained with the proposed model to the simulations denoted in Melnik and Sparks (2002b) as “no mass transfer”(here imposed fixing $\tau^{(d)} = 10^{15}$ s) and “equilibrium mass transfer”(here obtained with $\tau^{(d)} = 0.001$ s).

In the first run (“InstPU_NoEx”) we consider a constant dissolved water content ($x_d \equiv x_{d,0}$) for the whole simulation and exsolution is not taken into account (no gas exsolution, $\tau^{(d)} = 10^{15}$ s). This end-member case is representative of an eruption in which the propagation of the fragmentation front is too fast for any volatiles to diffuse from the melt into pre-existing vesicles during the explosion process. This run is comparable to the simulation denoted in Melnik and Sparks (2002b) as “no mass transfer” and in the 2D simulations of Clarke et al. (2002b).

The second end-member run (“InstPU_InstEx”), has the same conditions as the first, except it assumes instantaneous exsolution, which represents an eruption in which the delay between the decompression and the fragmentation wave is sufficiently long to allow the volatile phase, via diffusion, to reach equilibrium between the melt phase and the free-gas phase. As the initial condition for this simulation, we assume an equilibrium profile in mass fraction of dissolved volatiles ($x_d = x_d^{eq}(P_g)$) instead of a constant value. This run is comparable to the simulation denoted in Melnik and Sparks (2002b) as “equilibrium mass transfer”.

Fig. 4 and Fig. 5 present profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times for the two end-member cases (InstPU_NoEx and InstPU_InstEx). In both cases, a rarefaction wave propagates into the conduit, decompressing and accelerating the mixture. The fragmentation wave, which follows the rarefaction wave, splits the domain into two different flow regions, the bubbly magma and gas-particle zones. The comparison shows significant differences between the two end-member runs, particularly in

Figure 4: InstPU_NoEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times assuming a single pressure and velocity and no exsolution. These solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

the behaviour of the fragmentation wave.

In InstPU_NoEx, the initial fragmentation wave velocity is -92 m/s (downward toward the base of the conduit), in agreement with that obtained from the shock tube experiments of Koyaguchi et al. (2008) (~ 90 – 100 m/s) using Montserrat samples with a vesicularity of 44–67 vol.%. The velocity of the fragmentation wave decreases to -12 m/s after 25 s, stops downward propagation at approximately 11 minutes, when at a depth of ~ 1.4 km, then rises gradually with the ascending magma (compare 500 s to 1000 s in Fig. 4). At 700 s the fragmentation wave is moving with a velocity of 0.14 m/s upward toward the vent, accelerating slightly reaching 0.28 m/s at 1000 s.

In the instantaneous-exsolution case, initially the fragmentation wave moves more slowly than that of the no-exsolution run (-76 m/s vs -92 m/s), but after 25 s it is twice as fast (-24 m/s vs -12 m/s) and, after about 9 minutes, continues to travel down the conduit with a velocity of -2.0 m/s, nearly stopping at 1000 s with a residual velocity of just -0.07 m/s at 4.6 km depth.

The exit velocity at the top of the computational domain, where atmospheric pressure is fixed, is similar for the two

Figure 5: InstPU_InstEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times assuming a single pressure and velocity and instantaneous exsolution. These solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

cases at 1 s where maximum exit velocities are 262 m/s and 263 m/s. Both cases also experience a rapid deceleration at 10 s to 164 m/s and 185 m/s, respectively. The no-exsolution case then continues to decrease more gently reaching 30 m/s by 1000 seconds, whereas in contrast, the instantaneous-exsolution case exhibits a second increase in exit velocity, reaching 223 m/s by 1000 seconds into the simulation.

The assumption that most closely captures any natural case depends heavily on the viscosity of the magma and local volatile diffusion rates, which are a function of crystal and dissolved volatile contents. We also remark that, during an eruption, the system can vary from no exsolution to equilibrium exsolution in both time and space. Immediately below the fragmentation level, the fragmentation wave and quench processes may be too fast for volatiles to diffuse into vesicles syn-eruptively; conversely, deeper in the conduit, away from the fragmentation front, ascent velocity, fragmentation, and quench are slow and diffusion may have time to maintain equilibrium.

These temporal and spatial variations are considered in the third run (“InstPU_FiniteRateEx”), where a finite-rate gas exsolution is prescribed. In the proposed model, the diffusive gas mass transfer is governed by the relaxation

Figure 6: InstPU.FiniteRateEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times assuming a single pressure and velocity and a finite rate exsolution. These solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

time $\tau^{(d)}$. We consider here a relaxation time $\tau^{(d)} = 1000$ s, and, as was done for the instantaneous-exsolution case, we assume an initial condition of $x_d = x_d^{eq}$. This value for the degassing relaxation parameter was investigated in de' Michieli Vitturi et al. (2013b) and calibrated with data from Mangan and Sisson (2000). Moreover, we tested our chosen $\tau^{(d)}$ against the experiments of Burgisser and Gardner (2004) using a steady version of the code presented in La Spina et al. (2015, 2016), where the rate of degassing is treated in the same way as here. Using the steady-state model of La Spina et al. (2015), we set the constitutive equations and the initial conditions to be consistent with the Burgisser and Gardner (2004) experiments, and decompressed the system from 100 MPa, 80 MPa, and 60 MPa, by 20 MPa each at decompression rates of 0.15 to 0.2 MPa/s. The calculated vesicularity values fall within 15% of experimental results.

Fig. 6 shows results of the run with finite-rate exsolution at different times, including profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h). As expected, the

fragmentation wave propagates deeper with respect to the no-exsolution case, but shallower than the instantaneous-exsolution case. The initial fragmentation wave velocity is -72 m/s, and it decreases to -16 m/s after 25 s and to -1.0 m/s after about 9 minutes. After 1000 s of simulated eruption the fragmentation wave is at ~ 2.2 km depth and still moving downward with a velocity of -0.7 m/s. An extended simulation shows that by 2000 seconds the fragmentation wave continues its descent, although decelerating (about -0.3 m/s by the end). The maximum exit velocity is similar to those of the other two runs for the first 10 s.

From these simulations, we observe that the rate of gas exsolution plays a key role in the propagation of the fragmentation wave along the volcanic conduit, changing the fragmentation propagation behaviour, the maximum fragmentation depth, and the eruption rate trends in time.

4.2.2. Finite pressure and velocity relaxation rates

In this section we examine model solutions for which we allow the two phases to have different pressures and velocities. To do so, we prescribe a finite relaxation rates by setting the non-dimensional constants $\tau_0^{(p)}$ and $\tau_0^{(f)}$ to 1, and investigate solutions obtained for the same three exsolution cases discussed above: no exsolution, instantaneous exsolution, and finite-rate exsolution.

For the run with no exsolution and finite-rate pressure and velocity relaxation (“FiniteRatePU.NoEx”), Fig. 7 shows the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at several different times. As in the first case above, the initial mass fraction of dissolved volatiles is constant along the conduit and equal to $x_{d,0}$.

Using parameters reported in Table 3 for the Darcian and the inertial permeability, the gas and melt rise with the same velocity up to the point of fragmentation. In the gas/particle region, above the fragmentation level, we can see from the relative velocity in Fig. 7, the gas phase begins to decouple and move faster than the particles.

The decoupling of pressures is evident only in the zone immediately below the downward-propagating fragmentation wave, where the gas pressure has a higher value with respect to the melt phase. In the first 60 s, the fragmentation wave propagates down the conduit with an initial velocity of -88 m/s, reaching a maximum depth of 940 m. After 60 s, the fragmentation wave starts to move back up the conduit toward the vent, and we observe different behavior compared to the no-exsolution case with instantaneous relaxation of pressure and velocity above; here a local maximum in bubble volume fraction appears just below the fragmentation wave (Fig. 7). Once the discharge rate reaches zero, we assume that the eruption has ended and interrupt the computation.

The velocity of the fragmented phase at the exit reaches a maximum value of 267 m/s after 1 s, then decreases rapidly to 157 m/s in 10 s continuing to decrease reaching zero in about 3 minutes. Due to the effect of the finite rate relaxation of velocity, the velocity of the gas phase is higher than that of the fragmented phase, reaching a maximum value of 389 m/s after 1 s, then decreasing rapidly to 244 m/s at 10 s and 19 m/s at 175 s.

At approximately 50 s, near the fragmentation front, the pressure of the gas becomes lower than that of the liquid

Figure 7: FiniteRatePU_NoEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times (up to 175 s) assuming the finite rate relaxation of pressures and velocities and no exsolution. The solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

phase (Fig. 7). These gas underpressures correspond to peaks in gas relative velocity that are located between the leading decompression wave and the trailing fragmentation wave. Those peaks appear to correspond to rapid gas escape from the permeable magma, which depressurizes the gas phase with respect to that of the liquid.

Now, we analyse the solutions for which we allowed two different pressures and velocities, but assumed instantaneous exsolution (“FiniteRatePU_InstEx”). The initial condition for the mass fraction of the dissolved volatiles was equilibrium values ($x_d = x_d^{eq}$), as in the instantaneous-exsolution run of the previous section. Fig. 8 presents profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) for this case. Similar to the instantaneous-exsolution case in the previous section, the fragmentation wave propagates far into the conduit, reaching almost the bottom of the conduit (~ 4.5 km depth) at the end of the simulation ($t = 1000$ s).

In addition, initially the fragmentation wave velocity is slower than the no exsolution case (FiniteRatePU_NoEx)

Figure 8: FiniteRatePU_InstEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times assuming the finite rate relaxation of pressures and velocities and instantaneous exsolution. The solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

(−64 m/s vs −88 m/s), but after 25 s it is almost twice as fast (−20 m/s vs −12 m/s). Then it decreases to −2 m/s after about 9 minutes and after 1000 s of simulated eruption the fragmentation wave reaches nearly 4.5 km deep with a velocity of −1 m/s. An extended simulation up to 2000 s shows that from 1200 s the fragmentation wave remains at approximately the same depth.

The velocity of the fragmented phase at the exit reaches a maximum value of 271 m/s after 1 s, then decrease rapidly to 180 m/s in 10 s and after that we notice an increase in the velocity reaching 206 m/s in about 16 minutes. Due to the effect of finite-rate velocity relaxation, the velocity of the gas phase is higher than that of the fragmented phase. At the exit, it reaches a maximum value of 399 m/s after 1 s, then decreases rapidly to 275 m/s in 10 s and then accelerates to 353 m/s in about 16 minutes.

Comparing the results observed from this simulation with those obtained assuming instantaneous pressure and velocity relaxation, we notice similar profiles of the solutions and similar data for the discharge rate and for the

velocity of the fragmentation wave. However, due to the effect of the finite relaxation rate of the velocity, we observe a decoupling between the exsolved gas and the fragmented phase (which is not present in the case of instantaneous velocity relaxation), that is particularly evident at the exit where we observe a lower velocity for the fragmented phase compared to the gas phase. Prescribing a finite relaxation rate for pressure produces a peak in bubble pressure relative to that of the melt immediately below the fragmentation level. This peak propagates along the conduit going from a maximum of 14 MPa to a minimum of about 1.5 MPa (see Fig. 8-(b)).

Finally, with the last test we investigate solutions obtained prescribing finite relaxation rates in pressure and velocity, and a finite exsolution rate (“FiniteRatePU_FiniteRateEx”). As we have done for the InstPU_FiniteRateEx run, we consider the relaxation time $\tau^{(d)} = 1000$ s. Furthermore, as was done for the instantaneous-exsolution case, we assume the initial condition $x_d = x_d^{eq}$.

Fig. 9 presents profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) for this case. Similar to results presented above, the fragmentation wave propagates deeper compared to the case of no exsolution, but shallower than the case of instantaneous exsolution.

The initial fragmentation wave velocity is -60 m/s, but it decreases to -16 m/s after 25 s and then continues to decelerate until the wave stops at a depth of 1072 m after about 144 s of simulated eruption. After that, the fragmentation wave reverses and moves up towards the vent. At time $t = 200$ s the fragmentation wave is moving with a velocity of 0.8 m/s (i.e. towards the vent), and continues to decelerate. It reaches a velocity of 0.25 m/s after 500 s and 0.15 m/s at time $t = 1000$ s. An extended simulation up to 2000 s shows that, at that time, the fragmentation wave is at a depth of 704 m with a residual velocity of 0.1 m/s.

Again, due to the effects of the finite relaxation rate of velocity, we observe a lower exit velocity for the fragmented phase than for the gas phase (max of 259 m/s vs. 389 m/s; 154 m/s vs. 246 at 10 s). The peak in overpressure in the bubbles compared to that in the melt phase propagates along the conduit with a maximum of 9 MPa after the first second of the eruption.

5. Discussion

From these numerical simulations we see that the rate of the processes under consideration have significant impact on magma ascent dynamics and eruption style. To illustrate these points, Fig. 10 shows the fragmentation depth (a) and discharge rate (b) at the exit against time for the numerical simulations presented above. The cases in which we assumed instantaneous pressure and velocity relaxations are plotted with solid lines in Fig. 10, while those with finite relaxation rates for pressure and velocity are plotted with dashed lines. The colors represent exsolution conditions: no exsolution (blue), instantaneous exsolution (green), and finite-rate exsolution (red).

In comparing the first two runs (solid blue and solid green, Figure 10), we see that the corresponding discharge rates are similar in the first seconds of the eruption (maxima of 2.6×10^7 kg/s and 2.5×10^7 kg/s). The no-exsolution

Figure 9: FiniteRatePU_FiniteRateEx: profiles of the mixture pressure (a), gas overpressure (b), temperature (c), volume fraction of bubbles and fragmentation flag (d), melt and gas velocity (e), gas relative velocity (f), dissolved water content (g) and mixture density (h) at different times assuming the finite rate relaxation of pressures, velocities and exsolution. The solutions are obtained using DIRK KNP scheme with a grid of 1300 cells.

case (solid blue) then decreases almost linearly with the logarithm of time reaching a value of 1.1×10^6 kg/s after 9 minutes. On the other hand, the instantaneous-exsolution case (solid green) decreases very gently and retains a mass discharge rate of 6.1×10^6 kg/s at time 1000 s.

For comparison, with the same fragmentation threshold ($\alpha_f = 0.6$) and no-exsolution, Melnik and Sparks (2002b) obtained a peak discharge rate of $\approx 2.2 \times 10^7$ kg/s after a few seconds and a discharge rate of about 2×10^6 kg/s after 9 minutes. As a possible explanation of the small differences between their work and the runs presented here, we note that the model proposed here also solves the energy equation (different from the model of Melnik and Sparks (2002b)), thus we are able to track the temperature evolution during the eruption. At 1000 s after the onset of the eruption, we observe a decrease in temperature at the top of the conduit of about 20 K in the no-exsolution case and 30 K in the instantaneous -exsolution case, and an almost linear increase in temperature with depth along the conduit (Figs. 4c, 5c). This change in temperature produces feedback effects, changing the viscosity of the mixture and thus

Figure 10: Comparison of different numerical solutions: fragmentation depth (a) and discharge rate (b) at the vent of the conduit as function of time obtained from the previous numerical simulations.

the ascent rate and discharge rate.

We also observe good agreement with the mass flux in the first 30 s of the 2D simulations in Clarke et al. (2002b), although their results produce a higher peak discharge rate in the very first seconds. The exit velocity, on the other hand, reported by Clarke et al. (2002b) is lower than that computed in this test (≈ 100 m/s vs 146 m/s after 30 s of simulated eruption). These differences are related to several factors, such as the fact that they consider a pre-fragmented magma in the conduit, thus their runs are never in the viscous regime as we have in our simulations. We adopt a Poiseuille approximation for 1D laminar flow, whereas Clarke et al. (2002b) instead consider the viscous stress tensors for each phase of the mixture, taking into account turbulence in the two-phase flow.

We now compare the runs in which we prescribed a finite relaxation rate for pressure and velocity (dashed lines) to their instantaneous relaxation counterparts (solid lines of same color). Note that the fragmentation depth and discharge rates are similar for companion runs in the first 10s of seconds (Figure 10, compare solid and dashed lines of the same color), but they generally diverge later in the simulations. For example, FiniteRatePU_NoEx (blue dashed) produces a maximum discharge rate of 2.5×10^7 kg/s in the first seconds of the eruption, similar to the counterpart run with instantaneous relaxation of pressure and velocity (solid blue). However, by 100s into the simulation, the two runs exhibit very different behavior. In InstPU_NoEx run (Fig. 10, solid blue) the fragmentation wave reaches a maximum depth of about 1500 m and then starts to accelerate upwards. The corresponding mass discharge rate seems to indicate a continuous decrease, suggesting that after a certain amount of time the eruption stops. This continuous decrease is significantly more evident in the FiniteRatePU_NoEx run (Fig. 10, dashed blue), where the eruption stops about 3 minutes after onset, consistent with a short-lived Vulcanian-style eruption.

In contrast, in the instantaneous exsolution run InstPU_InstEx run (Fig. 10, solid green line), the fragmentation wave reaches almost the bottom of the conduit until it appears to stop and remain stable. The mass discharge rate remains stable at 6×10^6 kg/s, consistent with a steady-state sub-Plinian eruption. For the FiniteRatePU_InstEx run

(Fig. 10, dashed green line), results show that the fragmentation wave, at the same time, is shallower than that of the InstPU_InstEx run. The mass discharge rates for these two runs are, however, very similar, with both consistent with production of a steady-state sub-Plinian eruption.

An intermediate case is obtained when a finite exsolution rate is considered. When instantaneous pressure and velocity relaxation are considered (Fig. 10, solid red line) we obtain a stable discharge rate of 2×10^6 kg/s, consistent with a sub-Plinian eruption. However, when finite pressure and velocity relaxation rates are taken into account (Figure 10, dashed red line), the discharge rate decreases rapidly, consistent with a short-lived Vulcanian eruption. Note the presence in this run of fluctuations in the mass discharge rate after a few hundred seconds. These fluctuations are not related to oscillations in the numerical solution, but are caused by temporal variations in exit velocity at the top of the domain. Similar fluctuations in mass discharge rate were also observed by Melnik and Sparks (2002b) when they considered the overpressure and the strain rate criteria as fragmentation model, but not with the volume fraction criterion.

We reiterate here that the gas exit velocity is significantly affected when we allow two different phase velocities, increasing compared to corresponding cases that assume instantaneous velocity relaxation. The downward propagation speed of the fragmentation wave is not strongly influenced when we allow two different pressures and velocities, however, the maximum fragmentation depth is significantly affected (compare solid lines with corresponding dashed lines in the left panel of Fig. 10). And, as shown in the right panel of Fig. 10, mass discharge rate is significantly changed by finite-rate velocity and pressure relaxation, in particular when exsolution is not instantaneous. This outcome suggests that these relaxation rates will also affect column height.

We estimate the duration of the eruption for each case investigated in this work by linearly extrapolating the mass discharge rate reported in Fig. 10 and assuming the eruption ends once the mass discharge rate drops to 100 kg/s. Given these assumptions, the eruption simulated in the InstPU_NoEx run should last for about a month (solid blue), whilst the run FiniteRatePU_NoEx should last just a few minutes (dashed blue). With instantaneous exsolution, instead, as we have already discussed, both runs InstPU_InstEx and FiniteRatePU_InstEx produce a steady-state eruption (green lines). Finally, the eruption simulated in the InstPU_FiniteRateEx is also steady-state (solid red), whilst that simulated in the FiniteRatePU_FiniteRateEx should last for only a couple of hours (dashed red). These extrapolations are most likely overestimates of eruption duration, given that the decay in mass discharge rate is probably not linear, but exponential (as we have for the FiniteRatePU_NoEx run). Nevertheless, differences in duration of several orders of magnitude suggest that differences in pressure and velocity of the two phases and diffusion rate could significantly control eruption duration.

6. Conclusions

In this work we have focused on conduit processes involved in the initial stages of Vulcanian eruptions driven by the collapse of a dome overlying the conduit. Using several numerical tests we attempted to reproduce the 1997

Vulcanian explosions at the Soufrière Hills Volcano, Montserrat, while investigating the effects of relaxation and diffusion rates on the solutions.

In agreement with Melnik and Sparks (2002b), in the limit of no exsolution Vulcanian explosions are predicted. In the limit of instantaneous exsolution, deeper propagation of the fragmentation wave and development of quasi-steady discharge rates suggest sub-Plinian activity, similar to that which occurred on 17 September 1996 at the Soufrière Hills Volcano.

Going beyond Melnik and Sparks (2002b), we demonstrate the effects of several finite-rate relaxations, which we think better represent a real volcanic system. The use of finite-rate relaxation in velocity produces a decoupling between the exsolved gas and the fragmented phase. We observe a lower exit velocity for the fragmented phase compared to that of the gas phase. Prescribing a finite-rate relaxation in pressure produces a peak in bubble overpressure that is located immediately below the fragmentation level and propagates with it along the conduit.

The relaxation rates of these processes also directly control eruption duration. Numerical solutions vary from a steady-state sub-Plinian eruption when exsolution has sufficient time to reach equilibrium, to short-lived Vulcanian explosions when dynamic timescales are too short to allow complete exsolution. Furthermore, for a given finite exsolution rate, the finite-rate relaxations for velocity and pressure can also affect the style of the eruption. Assuming the degassing relaxation parameter investigated in de' Michieli Vitturi et al. (2013b) and calibrated with data from Mangan and Sisson (2000), we obtain steady-state sub-Plinian eruptions when instantaneous pressure and velocity relaxation are assumed, whilst we obtain short-lived Vulcanian explosions when finite pressure and velocity relaxation rates are prescribed.

The Soufrière Hills volcano, without any significant changes in magma composition, produced both short-duration Vulcanian eruptions and longer-lived sub-Plinian eruptions. Our simulations show that Vulcanian and sub-Plinian styles are consistent with disequilibrium and equilibrium exsolution, respectively. Given that the Soufrière Hills magmatic system changed very little between eruption styles, only a finite rate exsolution can produce both behaviours, with end-member and intermediate behaviors determined by the timescales available for exsolution. These timescales are controlled by other dynamic processes such as ascent rate and decompression and fragmentation wave speeds.

Numerical results shown here demonstrate that finite-rate relaxations and diffusion play a fundamental role in describing magma ascent dynamics during eruption. Accurate modeling of these finite-rate relaxations and diffusion would represent a significant step toward a more realistic model of magma ascent dynamics, providing a good tool for investigating and forecasting the temporal evolution of explosive volcanic eruptions.

Acknowledgements

The research leading to these results has received funding from the European Research Council under the European Union's Seventh Framework Programme (FP/2007–2013)/ERC Grant Agreement n. 279802. We are also grateful to Wim Degruyter and Takehiro Koyaguchi for their careful review and useful and constructive comments which greatly

improved an earlier version of this work.

Appendix A. Characteristic analysis

In this section we present a characteristic analysis if the system of equations (2-8), revealing that the system is hyperbolic. The hyperbolic part of the equations (2-7) coincides with that of the Single Temperature Conservative Equations for Two-Phase Flow illustrated in Romenski et al. (2010), which is ensured to be hyperbolic. Therefore, this proves that our system of equations (2-7) is also hyperbolic. Now we need to demonstrate that including Eq. (8) in our model, the hyperbolicity of the system does not change.

The one-dimensional conservative form of the equations (2-8) can be summarized as

$$\frac{\partial \mathbf{Q}}{\partial t} + \frac{\partial \mathbf{F}(\mathbf{Q})}{\partial z} = \mathbf{S}(\mathbf{Q}). \quad (\text{A.1})$$

Since the presence of the right hand side of the system (A.1) does not affect the calculation of the characteristic polynomial, we pose, for simplicity, $\mathbf{S}(\mathbf{Q}) = 0$.

In order to study the eigenstructure of the equations we introduce the set of primitive variables:

$$\mathbf{W} = (v_1, \dots, v_7)^T = (\alpha_1, s, \rho_1, \rho_2, u_1, u_2, \rho_d^B)^T, \quad (\text{A.2})$$

where ρ_d^B is the bulk density of the dissolved volatiles, i.e. the density referenced to the total volume.

Similar to what was done by La Spina et al. (2014), we rewrite the system in the equivalent quasilinear form

$$\begin{aligned} \frac{\partial \alpha_1}{\partial t} + u \frac{\partial \alpha_1}{\partial z} &= 0, \\ \frac{\partial s}{\partial t} + u \frac{\partial s}{\partial z} &= 0, \\ \frac{\partial \rho_1}{\partial t} + \frac{\alpha_2 \rho_2 \rho_1}{\alpha_1 \rho} (u_1 - u_2) \frac{\partial \alpha_1}{\partial z} + u_1 \frac{\partial \rho_1}{\partial z} + \rho_1 \frac{\partial u_1}{\partial z} &= 0, \\ \frac{\partial \rho_2}{\partial t} + \frac{\alpha_1 \rho_1 \rho_2}{\alpha_2 \rho} (u_1 - u_2) \frac{\partial \alpha_1}{\partial z} + u_2 \frac{\partial \rho_2}{\partial z} + \rho_2 \frac{\partial u_2}{\partial z} &= 0, \\ \frac{\partial u_1}{\partial t} + u_1 \frac{\partial u_1}{\partial z} + \frac{1}{\rho_1} \frac{\partial P_1}{\partial z} + \frac{P_1 - P_2}{\rho} \frac{\partial \alpha_1}{\partial z} - c_2 (s_1 - s_2) \frac{\partial T}{\partial z} &= 0, \\ \frac{\partial u_2}{\partial t} + u_2 \frac{\partial u_2}{\partial z} + \frac{1}{\rho_2} \frac{\partial P_2}{\partial z} + \frac{P_1 - P_2}{\rho} \frac{\partial \alpha_1}{\partial z} + c_1 (s_1 - s_2) \frac{\partial T}{\partial z} &= 0, \\ \frac{\partial \rho_d^B}{\partial t} + \rho_d^B \frac{\partial u_1}{\partial z} + u_1 \frac{\partial \rho_d^B}{\partial z} &= 0. \end{aligned} \quad (\text{A.3})$$

As done by La Spina et al. (2014), we rewrite the pressures and the temperature as function of the primitive variables $\mathbf{W}$, i.e.

$$\begin{aligned}\tilde{P}_i &\equiv \tilde{P}_i(\alpha_1, \rho_1, \rho_2, s), \\ \tilde{T} &\equiv \tilde{T}(\alpha_1, \rho_1, \rho_2, s),\end{aligned}\tag{A.4}$$

allowing us to formulate the system of equation A.3 in the quasilinear form

$$\frac{\partial \mathbf{W}}{\partial t} + J(\mathbf{W}) \frac{\partial \mathbf{W}}{\partial z} = 0,\tag{A.5}$$

where

$$J(\mathbf{W}) = \begin{bmatrix} u & 0 & 0 & 0 & 0 & 0 & 0 \\ 0 & u & 0 & 0 & 0 & 0 & 0 \\ * & 0 & u_1 & 0 & \rho_1 & 0 & 0 \\ * & 0 & 0 & u_2 & 0 & \rho_2 & 0 \\ * & * & \frac{1}{\rho_1} \frac{\partial \tilde{P}_1}{\partial \rho_1} - c_2(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_1} & \frac{1}{\rho_1} \frac{\partial \tilde{P}_1}{\partial \rho_2} - c_2(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_2} & u_1 & 0 & 0 \\ * & * & \frac{1}{\rho_2} \frac{\partial \tilde{P}_2}{\partial \rho_1} + c_1(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_1} & \frac{1}{\rho_2} \frac{\partial \tilde{P}_2}{\partial \rho_2} + c_1(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_2} & 0 & u_2 & 0 \\ 0 & 0 & 0 & 0 & \rho_d^B & 0 & u_1 \end{bmatrix}\tag{A.6}$$

In the Jacobian matrix reported above we have indicated with the symbol * non-zero coefficients, which are not relevant to the computation of the characteristic polynomial. Finally, the characteristic polynomial of $J(\mathbf{W})$ can be expressed as

$$\pi(\lambda) = (u_1 - \lambda)(u - \lambda)^2 \tilde{\pi}(\lambda),\tag{A.7}$$

where $\tilde{\pi}(\lambda) = [\pi_1(\lambda) \cdot \pi_2(\lambda) - \pi_3]$ and

$$\begin{aligned}\pi_1(\lambda) &= \lambda^2 - 2u_1\lambda + u_1^2 - \frac{\partial \tilde{P}_1}{\partial \rho_1} + c_2\rho_1(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_1}, \\ \pi_2(\lambda) &= \lambda^2 - 2u_2\lambda + u_2^2 - \frac{\partial \tilde{P}_2}{\partial \rho_2} - c_1\rho_2(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_2},\end{aligned}\tag{A.8}$$

$$\pi_3 = \left(\frac{\partial \tilde{P}_2}{\partial \rho_1} + c_1\rho_2(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_1} \right) \cdot \left(\frac{\partial \tilde{P}_1}{\partial \rho_2} - c_2\rho_1(s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_2} \right).$$

We highlight that the polynomial $(u - \lambda)^2 \tilde{\pi}(\lambda)$ is the characteristic polynomial of the system (2-7), which we know to have real roots due to the hyperbolicity of that system (Romenski et al. (2010); La Spina et al. (2014)). Therefore, the complete characteristic polynomial $\pi(\lambda)$ has 7 real roots, which means that the system (2-8) is also hyperbolic.

The calculation of all the roots of characteristic polynomial is not trivial, since $\tilde{\pi}(\lambda)$ cannot be factored, and, therefore, an iterative method, such as Newton's method, need to be implemented to compute them. In some simplified cases, however, the roots of $\tilde{\pi}(\lambda)$ can be computed analytically.

For example, considering the case with a single velocity, i.e. $u_1 = u_2 = u$, the characteristic polynomial $\tilde{\pi}(\lambda)$ takes the following form:

$$\left[\varphi - \left(\frac{\partial \tilde{P}_1}{\partial \rho_1} - c_2 \rho_1 (s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_1} \right) \right] \left[\varphi - \left(\frac{\partial \tilde{P}_2}{\partial \rho_2} + c_1 \rho_2 (s_1 - s_2) \frac{\partial \tilde{T}}{\partial \rho_2} \right) \right] - \pi_3, \quad (\text{A.9})$$

where

$$\varphi = (\lambda - u)^2.$$

Now, the polynomial A.9 is a second order polynomial with respect to the variable φ , which allow us to compute the two solutions φ_1 e φ_2 , obtaining

$$\lambda_{1,2} = u \pm \sqrt{\varphi_1}; \quad \lambda_{3,4} = u \pm \sqrt{\varphi_2},$$

where the terms φ_1 and φ_2 do not depends on the velocities of the two phases. Furthermore, from the expression for $\frac{\partial \tilde{P}_i}{\partial \rho_i}$ and $\frac{\partial \tilde{T}}{\partial \rho_i}$ calculated in La Spina et al. (2014), we have that

$$\varphi_1 \rightarrow C_1^2 \quad \text{for} \quad \alpha_1 \rightarrow 0, \quad (\text{A.10})$$

$$\varphi_2 \rightarrow C_2^2 \quad \text{for} \quad \alpha_1 \rightarrow 1. \quad (\text{A.11})$$

where C_1 and C_2 are the sound speed of each phase respectively.

Thus, in the case of very dilute regime, two eigenvalues approach the usual characteristic velocities associated with the carrier phase, given by the velocity of the phase plus and minus the phase sound speed.

Appendix B. Numerical methods

Here we describe the Implicit-Explicit (IMEX) Runge-Kutta scheme adopted to solve the governing equations (2-8). The family of IMEX methods have been developed to solve stiff systems of partial differential equations written in the form

$$\frac{\partial \mathbf{U}}{\partial t} + \mathbf{G}(\mathbf{U}) = \frac{1}{\tau} \mathbf{R}(\mathbf{U}), \quad (\text{B.1})$$

where $\tau > 0$ is a constant called “stiffness parameter”. System (B.1) may represent a system of N ODE’s or a discretization of a system of PDE’s, such as, for example, convection-diffusion equations, reaction-diffusion equations or hyperbolic systems with relaxation.

707 Defining the vector of relaxation terms $\mathbf{R}(\mathbf{U})$ as

$$\mathbf{R}(\mathbf{U}) = \tau \begin{pmatrix} 0 \\ -\frac{1}{\tau^{(p)}}(P_2 - P_1) \\ -\frac{1}{\tau^{(d)}}(1 - \phi_f)(x_d - x_d^{eq})\alpha_1\rho_1 \\ 0 \\ -\frac{1}{\tau^{(f)}}\frac{c(1-c)w}{\rho} \\ 0 \\ -\frac{1}{\tau^{(d)}}(1 - \phi_f)(x_d - x_d^{eq})\alpha_1\rho_1 \end{pmatrix}, \quad (\text{B.2})$$

708 with $\tau = \min(\tau^{(p)}, \tau^{(c)}, \tau^{(f)})$, the system (2-8) can be expressed as in (B.1), where

$$\mathbf{G}(\mathbf{U}) = \frac{\partial}{\partial x}\mathbf{F}(\mathbf{U}) - \left[\mathbf{S}(\mathbf{U}) - \frac{1}{\tau}\mathbf{R}(\mathbf{U}) \right] = \frac{\partial}{\partial x}\mathbf{F}(\mathbf{U}) - \widehat{\mathbf{S}}(\mathbf{U}) \quad (\text{B.3})$$

709 and

$$\widehat{\mathbf{S}}(\mathbf{U}) = \begin{pmatrix} 0 \\ 0 \\ 0 \\ -\rho g - (1 - \phi_f)\frac{8\mu_1 u_1}{R^2} - \phi_f\frac{8\mu_2 u_2}{R^2} \\ -(1 - \phi_f)\frac{8\mu_1 u_1^2}{R^2} + \phi_f\frac{8\mu_2 u_2^2}{R^2}, \\ -\rho g u - (1 - \phi_f)\frac{8\mu_1 u_1^2}{R^2} - \phi_f\frac{8\mu_2 u_2^2}{R^2} \\ 0 \end{pmatrix}. \quad (\text{B.4})$$

710 An IMEX Runge-Kutta scheme consists of applying an implicit discretization to the relaxation terms and an
711 explicit one to the non stiff terms. Applying the scheme to the system (B.1) we obtain

$$\mathbf{U}^{(j)} = \mathbf{U}^n - \Delta t \sum_{k=1}^{j-1} \tilde{a}_{jk} \mathbf{G}(\mathbf{U}^{(k)}) + \Delta t \cdot \frac{1}{\tau} \sum_{k=1}^{\nu} a_{jk} \mathbf{R}(\mathbf{U}^{(k)}), \quad j = 1, \dots, \nu \quad (\text{B.5})$$

$$\mathbf{U}^{n+1} = \mathbf{U}^n - \Delta t \sum_{k=1}^{\nu} \tilde{b}_k \mathbf{G}(\mathbf{U}^{(k)}) + \Delta t \cdot \frac{1}{\tau} \sum_{k=1}^{\nu} b_k \mathbf{R}(\mathbf{U}^{(k)}). \quad (\text{B.6})$$

713 The choice of the $\nu \times \nu$ matrices $\tilde{A} = (\tilde{a}_{jk})$, $\tilde{a}_{jk} = 0$ for $j \geq k$, and $A = (a_{jk})$ and of the vectors $\tilde{b} = (\tilde{b}_1, \dots, \tilde{b}_{\nu})^T$
714 and $b = (b_1, \dots, b_{\nu})^T$ differentiates the IMEX Runge-Kutta schemes.

715 IMEX Runge-Kutta schemes can be represented by a *double tableau* in the usual Butcher notation,

$$\begin{array}{c|c} \tilde{c} & \tilde{A} \\ \hline & \tilde{b}^T \end{array} \quad \begin{array}{c|c} c & A \\ \hline & b^T \end{array}, \quad (\text{B.7})$$

716 where $\tilde{A} = (\tilde{a}_{jk})$ and $A = (a_{jk})$ for $j, k = 1, \dots, \nu$. Furthermore, $\tilde{c} = (\tilde{c}_j)$ and $c = (c_j)$ are given by

$$\tilde{c}_j = \sum_{k=1}^{j-1} \tilde{a}_{jk}, \quad c_j = \sum_{k=1}^j a_{jk}. \quad (\text{B.8})$$

0	0	0	0	0	0	0	0
γ	γ	0	0	γ	0	γ	0
1	δ	$1 - \delta$	0	1	0	$1 - \gamma$	γ
	δ	$1 - \delta$	0		0	$1 - \gamma$	γ

 $\gamma = 1 - \frac{1}{\sqrt{2}}, \delta = 1 - \frac{1}{2\gamma}$

Table B.5: Tableau Asher, Ruuth, Spiteri ARS(2,2,2)

The IMEX scheme used in this work satisfy a particular condition, i.e. $a_{jk} = 0$ for $j > k$. This family of IMEX schemes are called Direct Implicit Runge-Kutta (DIRK) schemes. The DIRK scheme adopted in this work is the ARS(2,2,2) proposed by Ascher et al. (1997). The *double tableau* for this scheme is reported in B.5.

This scheme satisfies the additional condition $b_k = a_{v,k}$ and $\tilde{b}_k = \tilde{a}_{v,k}$ for $k = 1, \dots, v$. In this way the equation (B.6) can be replaced by the more simple expression

$$\mathbf{U}^{n+1} = \mathbf{U}^{(v)}. \quad (\text{B.9})$$

Appendix B.1. Computation of the solution using IMEX DIRK schemes

When using Diagonally-Implicit Runge-Kutta (DIRK) schemes, at each internal Runge-Kutta step we have to solve an implicit problem for all the cells of the domain. Applying a DIRK scheme to the partial differential equation (2-8) we obtain

$$\mathbf{U}_i^{(j)} = \mathbf{U}_i^n - \Delta t \sum_{k=1}^{j-1} \tilde{a}_{jk} \left(\frac{\tilde{\mathbf{F}}_{i+\frac{1}{2}}^{(k)} - \tilde{\mathbf{F}}_{i-\frac{1}{2}}^{(k)}}{\Delta x} - \widehat{\mathbf{S}}(\mathbf{U}_i^{(k)}) \right) + \Delta t \cdot \frac{1}{\tau} \sum_{k=1}^j a_{jk} \mathbf{R}(\mathbf{U}_i^{(k)}), \quad (\text{B.10})$$

$$\mathbf{U}_i^{n+1} = \mathbf{U}_i^n - \Delta t \sum_{k=1}^v \tilde{b}_k \left(\frac{\tilde{\mathbf{F}}_{i+\frac{1}{2}}^{(k)} - \tilde{\mathbf{F}}_{i-\frac{1}{2}}^{(k)}}{\Delta x} - \widehat{\mathbf{S}}(\mathbf{U}_i^{(k)}) \right) + \Delta t \cdot \frac{1}{\tau} \sum_{k=1}^v b_k \mathbf{R}(\mathbf{U}_i^{(k)}), \quad (\text{B.11})$$

for all $j = 1, \dots, v$. In the previous equations the numerical fluxes $\tilde{\mathbf{F}}_{i+\frac{1}{2}}^{(k)}$ are appropriate approximations of the fluxes $\mathbf{F}_{i+\frac{1}{2}}^{(k)}$ at each cell interface. Indeed, the fluxes at each cell interface are defined as

$$\mathbf{F}_{i\pm\frac{1}{2}} = \frac{1}{\Delta t} \int_{t^n}^{t^{n+1}} \mathbf{F}(\mathbf{U}(x_{i\pm\frac{1}{2}}, \tau)) d\tau. \quad (\text{B.12})$$

Since the last integral cannot be computed exactly, a numerical integration is required, and according to the approximation adopted we have different expressions for the numerical fluxes $\tilde{\mathbf{F}}_{i\pm\frac{1}{2}}$. There exist several definitions of the numerical fluxes, and, in this work, we adopt that proposed by Kurganov et al. (2001) and studied in La Spina and de' Michieli Vitturi (2012) and in La Spina et al. (2014).

Since in the equation (B.2) no differential operators are present, $\mathbf{R}(\mathbf{U}_i^{(k)})$ depends only on the solution within the cell i . Thus, for each Runge-Kutta step, we must solve n independent implicit problems, one for each cell of the domain. All the implicit problems can be solved using a functional iterative method, like Newton-Raphson. For

simplicity, we rewrite the equation (B.10) as follows:

$$\begin{aligned}
\mathbf{U}_i^{(j)} &= \mathbf{U}_i^n - \Delta t \sum_{k=1}^{j-1} \tilde{a}_{jk} \left(\frac{\tilde{\mathbf{F}}_{i+\frac{1}{2}}^{(k)} - \tilde{\mathbf{F}}_{i-\frac{1}{2}}^{(k)}}{\Delta x} - \widehat{\mathbf{S}}(\mathbf{U}_i^{(k)}) \right) + \\
&+ \Delta t \cdot \frac{1}{\tau} \sum_{k=1}^{j-1} a_{jk} \mathbf{R}(\mathbf{U}_i^{(k)}) + \Delta t \cdot \frac{1}{\tau} a_{jj} \mathbf{R}(\mathbf{U}_i^{(j)}) \\
&\Downarrow \\
\mathbf{U}_i^{(j)} - \Lambda_i - \Delta t \cdot \frac{1}{\tau} a_{jj} \mathbf{R}(\mathbf{U}_i^{(j)}) &= 0 \\
&\Downarrow \\
\Gamma(\mathbf{U}_i^{(j)}) &= 0.
\end{aligned} \tag{B.13}$$

The term Λ_i contains the explicit part of the equation (B.10), thus it can be calculated once during the computation of the solution $\mathbf{U}_i^{(j)}$ with the iterative method.

Now, applying the Newton-Raphson method to $\Gamma(\mathbf{x}) = 0$ we obtain

$$\begin{cases} \mathbf{x}_{(k+1)} = \mathbf{x}_{(k)} - J_{|\mathbf{x}_{(k)}}^{-1} \cdot \Gamma(\mathbf{x}_{(k)}) \\ \mathbf{x}_{(0)} = \mathbf{U}_i^n \end{cases} \tag{B.14}$$

where $J_{|\mathbf{x}_{(k)}}^{-1}$ is the inverse of the Jacobian of the function Γ evaluated at $\mathbf{x}_{(k)}$. We emphasize here that the inversion of the Jacobian is not very expensive in terms of computational costs, since J is a $m \times m$ matrix where m is the number of the equations in the system (2-8).

The very difficult task is to compute an approximation of the Jacobian with the highest possible accuracy, since $\mathbf{R}(\mathbf{U})$ is strongly non-linear. However, this obstacle can be overcome using complex numbers.

Appendix B.2. Derivative approximation through complex numbers

The solution of the system (B.14) requires an accurate evaluation of the Jacobian matrix J , i.e. the partial derivatives of Γ with respect to the components of $\mathbf{x}$. Due to the strong non-linearity of $\mathbf{R}(\mathbf{U})$, this task requires particular attention and analysis.

Let us consider a continuous function $f(x)$. A common method to estimate the first derivative is the forward-difference formula

$$f'(x) \approx \frac{f(x+h) - f(x)}{h}, \tag{B.15}$$

where h is the finite-difference interval. This is a first-order approximation, but using the Taylor series expansion and increasing the stencil of the approximation, it is possible to achieve a higher order approximation.

However, when estimating sensitivities using finite-difference formulas we are faced with the “step-size dilemma”, that is the desire to choose a small step size to minimize truncation error while avoiding the use of a step so small that errors due to subtractive cancellation become dominant.

A way to overcome this problem is to use complex functions. The first use of complex variables to estimate derivatives starts with the work of Lyness and Moler (1967) and Lyness (1967). They introduce a reliable method of

Figure B.11: Normalized relative error of the derivative approximations with respect to the exact value.

calculating the derivatives of an analytic function, and later Squire and Trapp (1998) obtain a very simple expression for estimating the first derivative. It has been shown that this estimation is very accurate, extremely robust and easy to implement, with reasonable computational cost. Recently the method has been used for sensitivity analysis in computational fluid dynamics (CFD) by Anderson et al. (2001). Further research on the subject has been carried out by Martins et al. (2001, 2000, 2003).

For a small discrete h , the *complex-step derivative approximation* is defined as

$$\left. \frac{\partial f}{\partial x} \right|_{(x)} \approx (f'(x))_{CS} = \frac{\Im(\tilde{f}(x + ih))}{h}. \quad (\text{B.16})$$

To see the improvements with respect to the finite differences, we try to approximate the first derivative of the analytic function

$$f(x) = \frac{x^2}{1 + x^4} \quad (\text{B.17})$$

at $x = 0.25$. We compare the complex-step derivative approximation with the first order forward differences

$$(f'(x))_{F_1} = \frac{f(x + h) - f(x)}{h}, \quad (\text{B.18})$$

the first order backward differences

$$(f'(x))_{B_1} = \frac{f(x) - f(x - h)}{h}, \quad (\text{B.19})$$

the second order central differences

$$(f'(x))_{C_2} = \frac{f(x + \frac{h}{2}) - f(x - \frac{h}{2})}{h}, \quad (\text{B.20})$$

the second order forward differences

$$(f'(x))_{F_2} = \frac{-f(x + 2h) + 4f(x + h) - 3f(x)}{2h}, \quad (\text{B.21})$$

the second order backward differences

$$(f'(x))_{B_2} = \frac{3f(x) - 4f(x-h) + f(x-2h)}{2h}, \quad (\text{B.22})$$

and finally the forth order central differences

$$(f'(x))_{C_4} = \frac{-f(x+2h) + 8f(x+h) - 8f(x-h) + f(x-2h)}{12h}. \quad (\text{B.23})$$

In the Fig.B.11 we report the normalized relative error

$$\epsilon = \left| \frac{(f'(x))_{est} - f'(x)}{f'(x)} \right| \quad (\text{B.24})$$

of all the estimation presented above with respect to the exact value $f'(x)$ calculated at $x = 0.25$. As we can see, at the beginning the relative error of all the estimation decrease with the step-size, but at a certain point, for the finite differences, the subtractive cancellation errors become significant, and thus the relative error increases. With the complex step derivative approximation, instead, this does not happen, and the relative error continues to decrease until it reaches the machine working precision. Then, even decreasing the step size, the error remains almost constant. Thus, with the complex step derivative approximation we don't have anymore the "step-size dilemma" and we can chose the machine working precision as step-size obtaining the highest accuracy for the approximation of the first derivative.

So, with the complex-step derivative approximation we can approximate the Jacobian J needed for the Newton-Raphson method with an error of the same order as the machine working precision. We simply must extend the function Γ to the complex plane, introduce the new function $\tilde{\Gamma} : \mathbb{C} \rightarrow \mathbb{C}$ and compute the Jacobian at $\mathbf{x}$ as

$$J(\mathbf{x}) \cdot \mathbf{e}_j = \frac{\Im(\tilde{\Gamma}(\mathbf{x} + i h \mathbf{e}_j))}{h}, \quad (\text{B.25})$$

where $(\mathbf{e}_j)_{j=1,\dots,m}$ are the vectors $(0, \dots, 0, 1, 0, \dots, 0)^T$ with the 1 in the j -th position.

References

- Alidibirov, M.A., 1994. A model for viscous magma fragmentation during volcanic blasts. *Bulletin of Volcanology* 56, 459–465. doi:10.1007/BF00302827.
- Anderson, W.K., Newman, J.C., Whitfield, D.L., Nielsen, E.J., 2001. Sensitivity analysis for Navier-Stokes equations on unstructured meshes using complex variables. *AIAA Journal* 39, 56–63. doi:10.2514/2.1270.
- Ascher, U.M., Ruuth, S.J., Spiteri, R.J., 1997. Implicit-explicit Runge-Kutta methods for time-dependent partial differential equations. *Applied Numerical Mathematics* 25, 151–167. doi:10.1016/S0168-9274(97)00056-1.
- Baer, M., Nunziato, J., 1986. A two-phase mixture theory for the Deflagration-to-Detonation Transition (DDT) in reactive granular materials. *International Journal of Multiphase Flow* 12, 861–889. doi:10.1016/0301-9322(86)90033-9.
- Barclay, J., Rutherford, M.J., Carroll, M.R., Murphy, M.D., Devine, J.D., Gardner, J., Sparks, R.S.J., 1998. Experimental phase equilibria constraints on pre-eruptive storage conditions of the Soufrière Hills magma. *Geophysical Research Letters* 25, 3437–3440. doi:10.1029/98GL00856.

797 Bernard, M.L., Zamora, M., Géraud, Y., Boudon, G., 2007. Transport properties of pyroclastic rocks from montagne Pelée volcano (Martinique,
798 Lesser Antilles). *Journal of Geophysical Research: Solid Earth* (1978–2012) 112, B05205. doi:10.1029/2006JB004385.

799 Burgisser, A., Gardner, J.E., 2004. Experimental constraints on degassing and permeability in volcanic conduit flow. *Bulletin of volcanology* 67,
800 42–56. doi:10.1007/s00445-004-0359-5.

801 Burnham, C.W., 1979. Magmas and hydrothermal fluids, in: L.Barnes, H. (Ed.), *Geochemistry of Hydrothermal Ore Deposits*. J.Wiley and Sons,
802 pp. 71–136.

803 Caricchi, L., Burlini, L., Ulmer, P., Gerya, T., Vassalli, M., Papale, P., 2007. Non-Newtonian rheology of crystal-bearing magmas and implications
804 for magma ascent dynamics. *Earth and Planetary Science Letters* 264, 402–419. doi:10.1016/j.epsl.2007.09.032.

805 Chojnicki, K., Clarke, A.B., Phillips, J.C., 2006. A shock-tube investigation of the dynamics of gas-particle mixtures: Implications for explosive
806 volcanic eruptions. *Geophysical Research Letters* 33, L15309. doi:10.1029/2006GL026414.

807 Clarke, A., Ongaro, T., Belousov, A., 2015. Vulcanian eruptions, in: Sigurdsson, H., Houghton, B., McNutt, S., Rymer, H., Stix, J. (Eds.), *The*
808 *encyclopedia of volcanoes*. Elsevier. chapter 28, pp. 505–518.

809 Clarke, A.B., 2013. Unsteady explosive activity: vulcanian eruptions, in: Fagents, S.A., Gregg, T.K., Lopes, R.M. (Eds.), *Modeling Volcanic*
810 *Processes*. Cambridge Univ Press, pp. 129–152.

811 Clarke, A.B., Neri, A., Macedonio, G., Voight, B., 2002a. Transient dynamics of Vulcanian explosions and column collapse. *Nature* 415, 897–901.
812 doi:10.1038/415897a.

813 Clarke, A.B., Neri, A., Macedonio, G., Voight, B., Druitt, T.H., 2002b. Computational modelling of the transient dynamics of the August 1997
814 Vulcanian explosions at Soufrière Hills Volcano, Montserrat: influence of initial conduit conditions on near-vent pyroclastic dispersal, in:
815 Druitt, T., Kokelaar, B. (Eds.), *The Eruption of Soufrière Hills Volcano, Montserrat, from 1995 to 1999*. Geological Society, London, *Memoirs*.
816 volume 21, pp. 319–348. doi:10.1144/GSL.MEM.2002.021.01.15.

817 Clarke, A.B., Stephens, S., Teasdale, R., Sparks, R.S.J., Diller, K., 2007. Petrologic constraints on the decompression history of magma
818 prior to Vulcanian explosions at the Soufrière Hills volcano, Montserrat. *Journal of Volcanology and Geothermal Research* 161, 261–274.
819 doi:10.1016/j.jvolgeores.2006.11.007.

820 Costa, A., 2005. Viscosity of high crystal content melts: Dependence on solid fraction. *Geophysical Research Letters* 32, L22308.
821 doi:10.1029/2005GL024303.

822 Degruyter, W., Bachmann, O., Burgisser, A., 2010. Controls on magma permeability in the volcanic conduit during the climactic phase of the Kos
823 Plateau Tuff eruption (Aegean Arc). *Bulletin of volcanology* 72, 63–74. doi:10.1007/s00445-009-0302-x.

824 Degruyter, W., Bachmann, O., Burgisser, A., Manga, M., 2012. The effects of outgassing on the transition between effusive and explosive silicic
825 eruptions. *Earth and Planetary Science Letters* 349, 161–170. doi:10.1016/j.epsl.2012.06.056.

826 de' Michieli Vitturi, M., Clarke, A.B., Neri, A., Voight, B., 2008. Effects of conduit geometry on magma ascent dynamics in dome-forming
827 eruptions. *Earth and Planetary Science Letters* 272, 567–578. doi:10.1016/j.epsl.2008.05.025.

828 de' Michieli Vitturi, M., Clarke, A.B., Neri, A., Voight, B., 2010a. Transient effects of magma ascent dynamics along a geometrically variable
829 dome-feeding conduit. *Earth and Planetary Science Letters* 295, 541–553. doi:10.1016/j.epsl.2010.04.029.

830 de' Michieli Vitturi, M., Clarke, A.B., Neri, A., Voight, B., 2013a. Extrusion cycles during dome-building eruptions. *Earth and Planetary Science*
831 *Letters* 371–372, 37–48. doi:10.1016/j.epsl.2013.03.037.

832 de' Michieli Vitturi, M., Clarke, A.B., Neri, A., Voight, B., La Spina, G., 2013b. Investigating disequilibrium effects in magma ascent dynamics
833 with a new multiphase flow model, in: *EGU General Assembly Conference Abstracts*, p. 10536.

834 de' Michieli Vitturi, M., Neri, A., Esposti Ongaro, T., Lo Savio, S., Boschi, E., 2010b. Lagrangian modeling of large volcanic particles: Application
835 to Vulcanian explosions. *Journal of Geophysical Research* 115, B08206. doi:10.1029/2009JB007111.

836 Devine, J., Rutherford, M., Gardner, J., 1998. Petrologic determination of ascent rates for the 1995–1997 Soufrière Hills Volcano andesitic magma.
837 *Geophysical Research Letters* 25, 3673–3676. doi:10.1029/98GL00912.

838 Diller, K., Clarke, A.B., Voight, B., Neri, A., 2006. Mechanisms of conduit plug formation: Implications for vulcanian explosions. *Geophysical*
839 *Research Letters* 33, L20302. doi:10.1029/2006GL027391.

Dingwell, D.B., Bagdassarov, N.S., Bussod, J., Webb, S.L., 1993. Magma Rheology, in: Luth, R.W. (Ed.), Short course handbook on experiments at high pressure and applications to the Earth's mantle. Mineralogical Association of Canada, Edmonton. volume 21, pp. 131–196.

Druitt, T.H., Kokelaar, P. (Eds.), 2002. The Eruption of Soufrière Hills Volcano, Montserrat, from 1995 to 1999. volume 21. Geological Society, London, Memoirs.

Druitt, T.H., Young, S.R., Baptie, B., Bonadonna, C., Calder, E.S., Clarke, A.B., Cole, P.D., Harford, C.L., Herd, R.A., Luckett, R., Ryan, G., Voight, B., 2002. Episodes of cyclic Vulcanian explosive activity with fountain collapse at Soufrière Hills Volcano, Montserrat, in: Druitt, T.H., Kokelaar, B.P. (Eds.), The Eruption of Soufrière Hills Volcano, Montserrat, from 1995 to 1999. Geological Society, London, Memoirs. volume 21, pp. 281–306. doi:10.1144/GSL.MEM.2002.021.01.13.

Dufek, J., Bergantz, G.W., 2005. Transient two-dimensional dynamics of the upper conduit of a rhyolitic eruption: A comparison of the closure models for the granular stress. *Journal of Volcanology and Geothermal Research* 143, 113–132. doi:10.1016/j.jvolgeores.2004.09.013.

Eichelberger, J., 1995. Silicic volcanism: ascent of viscous magmas from crustal reservoirs. *Annual Review of Earth and Planetary Sciences* 23, 41–64.

Eichelberger, J.C., Carrigan, C.R., Westrich, H.R., Price, R.H., 1986. Non-explosive silicic volcanism. *Nature* 323, 598–602. doi:10.1038/323598a0.

Gardner, J.E., Thomas, R.M., Jaupart, C., Tait, S., 1996. Fragmentation of magma during plinian volcanic eruptions. *Bulletin of Volcanology* 58, 144–162. doi:10.1007/s004450050132.

Giachetti, T., Druitt, T., Burgisser, A., Arbaret, L., Galven, C., 2010. Bubble nucleation, growth and coalescence during the 1997 Vulcanian explosions of Soufrière Hills Volcano, Montserrat. *Journal of Volcanology and Geothermal Research* 193, 215–231. doi:10.1016/j.jvolgeores.2010.04.001.

Giordano, D., Dingwell, D., 2003. Viscosity of hydrous Etna basalt: implications for Plinian-style basaltic eruptions. *Bulletin of Volcanology* 65, 8–14. doi:10.1007/s00445-002-0233-2.

Giordano, D., Russell, J.K., Dingwell, D.B., 2008. Viscosity of magmatic liquids: a model. *Earth and Planetary Science Letters* 271, 123–134. doi:10.1016/j.epsl.2008.03.038.

Godunov, S., Romenskii, E., 2003. Elements of continuum mechanics and conservation laws. Springer Us.

Gonnermann, H.M., 2015. Magma fragmentation. *Annual Review of Earth and Planetary Sciences* 43, 431–458.

Gonnermann, H.M., Manga, M., 2003. Explosive volcanism may not be an inevitable consequence of magma fragmentation. *Nature* 426, 432–435. doi:10.1038/nature02138.

Gonnermann, H.M., Manga, M., 2005. Nonequilibrium magma degassing: results from modeling of the ca. 1340 A.D. eruption of Mono Craters, California. *Earth and Planetary Science Letters* 238, 1–16. doi:10.1016/j.epsl.2005.07.021.

Gonnermann, H.M., Manga, M., 2007. The fluid mechanics inside a volcano. *Annual Reviews of Fluid Mechanics* 39, 321–356. doi:10.1146/annurev.fluid.39.050905.110207.

Hess, K.U., Dingwell, D.B., 1996. Viscosities of hydrous leucogranitic melts: A non-Arrhenian model. *American Mineralogist* 81, 1297–1300. doi:10.2138/am-1996-9-1031.

Huang, X., Li, F., Zhou, Q., Meng, Y., Litasov, K.D., Wang, X., Liu, B., Cui, T., 2016. Thermal equation of state of Molybdenum determined from in situ synchrotron X-ray diffraction with laser-heated diamond anvil cells. *Scientific Reports* 6, 19923. doi:10.1038/srep19923.

Hui, H., Zhang, Y., 2007. Toward a general viscosity equation for natural anhydrous and hydrous silicate melts. *Geochimica et Cosmochimica Acta* 71, 403–416. doi:10.1016/j.gca.2006.09.003.

Ishihara, K., 1985. Dynamical analysis of volcanic explosion. *Journal of geodynamics* 3, 327–349. doi:10.1016/0264-3707(85)90041-9.

Jaupart, C., Allègre, C.J., 1991. Gas content, eruption rate and instabilities of eruption regime in silicic volcanoes. *Earth and Planetary Science Letters* 102, 413–429. doi:10.1016/0012-821X(91)90032-D.

Klug, C., Cashman, K.V., 1994. Vesiculation of May 18, 1980, Mount St. Helens magma. *Geology* 22, 468–472.

Koyaguchi, T., Mitani, N.K., 2005. A theoretical model for fragmentation of viscous bubbly magmas in shock tubes. *Journal of Geophysical Research* 110, B10202. doi:10.1029/2004JB003513.

- 883 Koyaguchi, T., Scheu, B., Mitani, N.K., Melnik, O., 2008. A fragmentation criterion for highly viscous bubbly magmas estimated from shock tube.
884 *Journal of Volcanology and Geothermal Research* 178, 58–71. doi:10.1029/2004JB003513.
- 885 Kozono, T., Koyaguchi, T., 2009. Effects of relative motion between gas and liquid on 1-dimensional steady flow in silicic volcanic conduits: 1.
886 An analytical method. *Journal of Volcanology and Geothermal Research* 180, 21–36. doi:10.1016/j.jvolgeores.2008.11.006.
- 887 Kueppers, U., Scheu, B., Spieler, O., Dingwell, D.B., 2006. Fragmentation efficiency of explosive volcanic eruptions: A study of experimentally
888 generated pyroclasts. *Journal of Volcanology and Geothermal Research* 153, 125–135. doi:10.1016/j.jvolgeores.2005.08.006.
- 889 Kurganov, A., Noelle, S., Petrova, G., 2001. Semidiscrete Central-Upwind Schemes for Hyperbolic Conservation Laws and Hamilton–Jacobi
890 Equations. *SIAM Journal on Scientific Computing* 23, 707–740. doi:10.1137/S1064827500373413.
- 891 La Spina, G., Burton, M., de’ Michieli Vitturi, M., 2015. Temperature evolution during magma ascent in basaltic effusive eruptions: A numerical
892 application to stromboli volcano. *Earth and Planetary Science Letters* 426, 89–100.
- 893 La Spina, G., Burton, M., de’ Michieli Vitturi, M., Arzilli, F., 2016. Role of syn-eruptive plagioclase disequilibrium crystallization in basaltic
894 magma ascent dynamics. *Nature Communications* 7, 13402. doi:10.1038/ncomms13402.
- 895 La Spina, G., de’ Michieli Vitturi, M., 2012. High-resolution finite volume central schemes for a compressible two-phase model. *SIAM Journal*
896 *on Scientific Computing* 34, B861–B880. doi:10.1137/12087089X?af=R.
- 897 La Spina, G., de’ Michieli Vitturi, M., Romenski, E., 2014. A compressible single-temperature conservative two-phase model with phase transitions.
898 *International Journal for Numerical Methods in Fluids* 76, 282–311. doi:10.1002/flid.3934.
- 899 Le Métayer, O., Massoni, J., Saurel, R., 2004. Élaboration des lois d’état d’un liquide et de sa vapeur pour les modèles d’écoulements diphasiques.
900 *International Journal of Thermal Sciences* 43, 265–276. doi:10.1016/j.ijthermalsci.2003.09.002.
- 901 Le Métayer, O., Massoni, J., Saurel, R., 2005. Modelling evaporation fronts with reactive riemann solvers. *Journal of Computational Physics* 205,
902 567–610. doi:10.1016/j.jcp.2004.11.021.
- 903 Le Pennec, J.L., Hermitte, D., Dana, I., Pezard, P., Coulon, C., Cochemé, J.J., Mulyadi, E., Ollagnier, F., Revest, C., 2001. Electrical conductivity
904 and pore-space topology of merapi lavas: Implications for the degassing of porphyritic andesite magmas. *Geophysical research letters* 28,
905 4283–4286. doi:10.1029/2001GL013401.
- 906 Lejeune, A.M., Richet, P., 1995. Rheology of crystal-bearing silicate melts: An experimental study at high viscosities. *Journal of Geophysical*
907 *Research* 100, 4215–4229. doi:10.1029/94JB02985.
- 908 Liu, Y., Zhang, Y., Behrens, H., 2005. Solubility of H₂O in rhyolitic melts at low pressures and a new empirical model for mixed H₂O–CO₂
909 solubility in rhyolitic melts. *Journal of Volcanology and Geothermal Research* 143, 219–235. doi:10.1016/j.jvolgeores.2004.09.019.
- 910 Lopes, R.M., Gregg, T.K., 2004. *Volcanic worlds: exploring the solar system’s volcanoes*. Springer Science & Business Media.
- 911 Lyness, J., 1967. Numerical algorithms based on the theory of complex variable, in: *Proceedings of the 1967 22nd national conference*, ACM. pp.
912 125–133. doi:10.1145/800196.805983.
- 913 Lyness, J.N., Moler, C.B., 1967. Numerical differentiation of analytic functions. *SIAM Journal on Numerical Analysis* 4, 202–210.
914 doi:10.1137/0704019.
- 915 Macedonio, G., Neri, A., Martí, J., Folch, A., 2005. Temporal evolution of flow conditions in sustained magmatic explosive eruptions. *Journal of*
916 *Volcanology and Geothermal Research* 143, 153–172. doi:10.1016/j.jvolgeores.2004.09.015.
- 917 Mangan, M., Sisson, T., 2000. Delayed, disequilibrium degassing in rhyolite magma: decompression experiments and implications for explosive
918 volcanism. *Earth and Planetary Science Letters* 183, 441–455. doi:10.1016/S0012-821X(00)00299-5.
- 919 Martins, J., Sturda, P., Alonso, J.J., 2001. The connection between the complex-step derivative approximation and algorithmic differentiation.
920 *AIAA paper* 921. doi:10.2514/6.2001-921.
- 921 Martins, J.R.R.A., Kroo, I.M., Alonso, J.J., 2000. An automated method for sensitivity analysis using complex variables, in: *AIAA paper* 2000-
922 0689, 38th Aerospace Sciences Meeting, pp. 2000–0689.
- 923 Martins, J.R.R.A., Sturda, P., Alonso, J.J., 2003. The complex-step derivative approximation. *ACM Trans. Math. Softw.* 29, 245–262.
924 doi:10.1145/838250.838251.
- 925 Mason, R.M., Starostin, A.B., Melnik, O.E., Sparks, R.S.J., 2006. From Vulcanian explosions to sustained explosive eruptions:

the role of diffusive mass transfer in conduit flow dynamics. *Journal of Volcanology and Geothermal Research* 153, 148–165. doi:10.1016/j.jvolgeores.2005.08.011.

Massol, H., Jaupart, C., 1999. The generation of gas overpressure in volcanic eruptions. *Earth and Planetary Science Letters* 166, 57–70. doi:10.1016/S0012-821X(98)00277-5.

Massol, H., Jaupart, C., Pepper, D.W., 2001. Ascent and decompression of viscous vesicular magma in a volcanic conduit. *Journal of Geophysical Research-Solid Earth* 106, 16223–16240. doi:10.1029/2001JB000385.

Mastin, L.G., 2002. Insights into volcanic conduit flow from an open-source numerical model. *Geochemistry Geophysics Geosystems* 3, 1–18. doi:10.1029/2001GC000192.

Melnik, O., Sparks, R.S.J., 1999. Nonlinear dynamics of lava dome extrusion. *Nature* 402, 37–41. doi:10.1038/46950.

Melnik, O., Sparks, R.S.J., 2002a. Dynamics of magma ascent and lava extrusion at Soufrière Hills Volcano, Montserrat, in: Druitt, T., Kokelaar, B. (Eds.), *The Eruption of Soufrière Hills Volcano, Montserrat, from 1995 to 1999*. Geological Society, London, Memoirs. volume 21, pp. 153–171. doi:10.1144/GSL.MEM.2002.021.01.07.

Melnik, O., Sparks, R.S.J., 2002b. Modelling of conduit flow dynamics during explosive activity at Soufrière Hills Volcano, Montserrat, in: Druitt, T., Kokelaar, B. (Eds.), *The Eruption of Soufrière Hills Volcano, Montserrat, from 1995 to 1999*. Geological Society, London, Memoirs. volume 21, pp. 307–317. doi:10.1144/GSL.MEM.2002.21.01.14.

Melnik, O., Sparks, R.S.J., 2005. Controls on conduit magma flow dynamics during lava dome building eruptions. *Journal of Geophysical Research* 110, B02209. doi:10.1029/2004JB003183.

Melnik, O.E., 2000. Dynamics of two-phase conduit flow of high-viscosity gas-saturated magma: Large variations of Sustained Explosive eruption intensity. *Bulletin of Volcanology* 62, 153–170. doi:10.1007/s004450000072.

Menikoff, R., Plohr, B.J., 1989. The riemann problem for fluid flow of real materials. *Rev. Mod. Phys.* 61, 75–130. doi:10.1103/RevModPhys.61.75.

Menikoff, R., 2000. Complete Mie-Grüneisen Equation of State (update). *Chem. Phys.* 113, 7492–7501. doi:10.2172/1241653.

Mercalli, G., 1907. *Vulcani attivi della Terra*. Ulrico Hoepli.

Moore, G., Vennemann, T., Carmichael, I., 1998. An empirical model for the solubility of H₂O in magmas to 3 kilobars. *American Mineralogist* 83, 36–42. doi:10.2138/am-1998-0103.

Morrissey, M., Mastin, L., 2000. Vulcanian eruptions. *Encyclopedia of volcanoes*, 463–475.

Murphy, M., Sparks, R., Barclay, J., Carroll, M., Brewer, T., 2000. Remobilization of andesite magma by intrusion of mafic magma at the Soufrière Hills Volcano, Montserrat, West Indies. *Journal of petrology* 41, 21–42. doi:10.1093/petrology/41.1.21.

Navon, O., Lyakhovsky, V., 1998. Vesiculation processes in silicic magmas. Geological Society, London, Special Publications 145, 27–50. doi:10.1144/GSL.SP.1996.145.01.03.

Papale, P., 1999a. Modeling of the solubility of a two-component H₂O+CO₂ fluid in silicate liquids. *American Mineralogist* 84, 477. doi:10.2138/am-1999-0402.

Papale, P., 1999b. Strain-induced magma fragmentation in explosive eruptions. *Nature* 397, 425–428. doi:10.1038/17109.

Papale, P., 2001. Dynamics of magma flow in volcanic conduits with variable fragmentation efficiency and nonequilibrium pumice degassing. *Journal of Geophysical Research* 106, 11043–11065. doi:10.1029/2000JB900428.

Papale, P., Moretti, R., Barbato, D., 2006. The compositional dependence of the saturation surface of H₂O+CO₂ fluids in silicate melts. *Chemical Geology* 229, 78–95. doi:10.1016/j.chemgeo.2006.01.013.

Pelanti, M., LeVeque, R.J., 2006. High-Resolution Finite Volume Methods for Dusty Gas Jets and Plumes. *SIAM Journal on Scientific Computing* 28, 1335–1360. doi:10.1137/050635018.

Polacci, M., Baker, D.R., Mancini, L., Tromba, G., Zanini, F., 2006. Three-dimensional investigation of volcanic textures by x-ray microtomography and implications for conduit processes. *Geophysical Research Letters* 33, L13312. doi:10.1029/2006GL026241.

Proussevitch, A., Sahagian, D., 1998. Dynamics and energetics of bubble growth in magmas: Analytical formulation and numerical modeling. *Journal of Geophysical Research* 103, 18223–18251. doi:10.1029/98JB00906.

- Proussevitch, A.A., Sahagian, D.L., 1996. Dynamics of coupled diffusive and decompressive bubble growth in magmatic systems. *Journal of Geophysical Research-Solid Earth* 101, 17447–17455. doi:10.1029/96JB01342.
- Pyle, D., Pyle, D., 1995. Bubble migration and the initiation of volcanic eruptions. *Journal of volcanology and geothermal research* 67, 227–232.
- Romenski, E., Drikakis, D., Toro, E., 2010. Conservative Models and Numerical Methods for Compressible Two-Phase Flow. *Journal of Scientific Computing* 42, 68–95. doi:10.1007/s10915-009-9316-y.
- Rust, A., Cashman, K., 2004. Permeability of vesicular silicic magma: inertial and hysteresis effects. *Earth and Planetary Science Letters* 228, 93–107. doi:10.1016/j.epsl.2004.09.025.
- Saad, M.A., 1985. *Compressible fluid flow*. Englewood Cliffs, NJ, Prentice-Hall, Inc. .
- Saar, M.O., Manga, M., 1999. Permeability-porosity relationship in vesicular basalts. *Geophysical Research Letters* 26, 111–114. doi:10.1029/1998GL900256.
- Sable, J.E., Houghton, B.F., Del Carlo, P., Coltelli, M., 2006. Changing conditions of magma ascent and fragmentation during the Etna 122 BC basaltic Plinian eruption: Evidence from clast microtextures. *Journal of Volcanology and Geothermal Research* 158, 333–354. doi:10.1016/j.jvolgeores.2006.07.006.
- Sahagian, D., 2005. Volcanic eruption mechanisms: insights from intercomparison of models of conduit processes. *Journal of Volcanology and Geothermal Research* 143, 1–15. doi:10.1016/j.jvolgeores.2004.12.006.
- Saito, T., Marumoto, M., Takayama, K., 2003. Numerical investigations of shock waves in gas-particle mixtures. *Shock Waves* 13, 299–322. doi:10.1007/s00193-003-0217-y.
- Saurel, R., Abgrall, R., 1999. A multiphase godunov method for compressible multifluid and multiphase flows. *Journal of Computational Physics* 150, 425–467. doi:10.1006/jcph.1999.6187.
- Self, S., Wilson, L., Nairn, I.A., 1979. Vulcanian eruption mechanism. *Nature* 277, 440–443. doi:10.1038/277440a0.
- Sparks, R., 1978. The dynamics of bubble formation and growth in magmas: a review and analysis. *Journal of Volcanology and Geothermal Research* 3, 1–37. doi:10.1016/0377-0273(78)90002-1.
- Sparks, R.S.J., Bursik, M.I., Carey, S.N., Gilbert, J.E., Glaze, L., Sigurdsson, H., Woods, A.W., 1997. *Volcanic plumes*. John Wiley & Sons Inc.
- Spieler, O., Kennedy, B., Kueppers, U., Dingwell, D., Scheu, B., Taddeucci, J., 2004. The fragmentation threshold of pyroclastic rocks. *Earth and Planetary Science Letters* 226, 139–148. doi:10.1016/j.epsl.2004.07.016.
- Squire, W., Trapp, G., 1998. Using complex variables to estimate derivatives of real functions. *Siam Review* 40, 110–112. doi:10.1137/S003614459631241X.
- Starostin, A., Barmin, A., Melnik, O., 2005. A transient model for explosive and phreatomagmatic eruptions. *Journal of Volcanology and Geothermal Research* 143, 133–151. doi:10.1016/j.jvolgeores.2004.09.014.
- Stix, J., Torres, R.C., Narvaez, M.L., Cortes, G.B., Raigosa, J.A., Gomes, D.M., Castonguay, R., 1997. A model of Vulcanian eruptions at Galeras volcano, Colombia. *Journal of Volcanology and Geothermal Research* 77, 285–303. doi:10.1016/S0377-0273(96)00100-X.
- Toro, E., 2009. *Riemann solvers and numerical methods for fluid dynamics: a practical introduction*. Springer Verlag.
- Turcotte, D., Ockendon, H., Ockendon, J., Cowley, S., 1990. A mathematical model of vulcanian eruptions. *Geophysical Journal International* 103, 211–217. doi:10.1111/j.1365-246X.1990.tb01763.x.
- Verhoogen, J., 1951. Mechanics of ash formation. *American Journal of Science* 249, 729–739.
- Woods, A., 1995a. The dynamics of explosive volcanic eruptions. *Reviews of geophysics* 33, 495–530. doi:10.1029/95RG02096.
- Woods, A.W., 1995b. A model of vulcanian explosions. *Nuclear Engineering and Design* 155, 345–357. doi:10.1016/0029-5493(94)00881-X.
- Woods, A.W., Cardoso, S.S., 1997. Triggering basaltic volcanic eruptions by bubble-melt separation. *Nature* 385, 518–520. doi:10.1038/385518a0.
- Woods, A.W., Koyaguchi, T., 1994. Transitions between explosive and effusive eruptions of silicic magmas. *Nature* 370, 641–644. doi:10.1038/370641a0.
- Wright, H., Cashman, K.V., Gottesfeld, E.H., Roberts, J.J., 2009. Pore structure of volcanic clasts: Measurements of permeability and electrical conductivity. *Earth and Planetary Science Letters* 280, 93–104. doi:10.1016/j.epsl.2009.01.023.

1012 Yoshida, S., Koyaguchi, T., 1999. A new regime of volcanic eruption due to the relative motion between liquid and gas. *Journal of volcanology*
1013 *and geothermal research* 89, 303–315. doi:10.1016/S0377-0273(99)00005-0.

1014 Zeidan, D., 2016. Assessment of mixture two-phase flow equations for volcanic flows using Godunov-type methods. *Applied Mathematics and*
1015 *Computation* 272, 707–719. doi:10.1016/j.amc.2015.09.038.

1016 Zeidan, D., Touma, R., Slaouti, A., 2014. Application of a thermodynamically compatible two-phase flow model to the high-resolution simulations
1017 of compressible gas–magma flow. *International Journal for Numerical Methods in Fluids* 76, 312–330. doi:10.1002/flid.3936.

1018 Zhang, Y., 1999. A criterion for the fragmentation of bubbly magma based on brittle failure theory. *Nature* 402, 648–650. doi:10.1038/45210.

1019 Zhang, Y., Xu, Z., Zhu, M., Wang, H., 2007. Silicate melt properties and volcanic eruptions. *Reviews of Geophysics* 45, RG4004.
1020 doi:10.1029/2006RG000216.